


### Overview



## Models

HP 6200-24G-mGBIC yl Switch

J8992A

## Introduction

The HP 6200-24G-mGBIC yl Switch is an advanced Layer 3 stackable switch in 1U height. It has 24 mini-GBIC slots and an expansion slot for an optional 4-port 10GbE module. Designed to be deployed as an aggregator of traffic from the edge to the core of the network, this switch supports a variety of Gigabit mini-GBICs, such as SX, LX, LH, and 1000BASE-T. The foundation for this switch is a purpose-built ProVision ASIC that allows the most demanding networking features, such as quality of service (QoS) and security, to be implemented in a scalable yet granular fashion. With its high-performance architecture, 10GbE capability, and programmable ASIC, this switch offers excellent investment protection, flexibility, and scalability.

## Key features

- Distribution layer
- Layer 2 to 4 and intelligent edge feature set
- High performance
- Low-cost mini-GBIC connectivity
- 10GbE uplinks

## Features and Benefits

### Software-defined networking

- **NEW OpenFlow**  
is a key technology enabling software-defined networking by allowing the separation of data (packet forwarding) and control (routing decision) paths

### Quality of Service (QoS)

- **Advanced classifier-based QoS**  
classifies traffic using multiple match criteria based on Layer 2, 3, and 4 information; applies QoS policies such as setting priority level and rate limit to selected traffic on a per-port or per-VLAN basis
- **Layer 4 prioritization**  
enables prioritization based on TCP/UDP port numbers
- **Traffic prioritization**  
allows real-time traffic classification into eight priority levels mapped to eight queues
- **Bandwidth shaping:**
  - **Port-based rate limiting**  
provides per-port ingress/egress enforced maximum bandwidth
  - **Classifier-based rate limiting**  
uses access control list (ACL) to enforce maximum bandwidth for ingress traffic on each port
  - **Guaranteed minimum**  
provides per-port, per-queue egress-based guaranteed minimum bandwidth

### Overview

- **Class of Service (CoS)**  
sets the IEEE 802.1p priority tag based on IP address, IP Type of Service (ToS), Layer 3 protocol, TCP/UDP port number, source port, and DiffServ

### Management

- **Remote intelligent mirroring**  
mirrors selected ingress/egress traffic based on ACL, port, MAC address, or VLAN to a local or remote HP 8200 zl, 6600, 6200 yl, 5400 zl, or 3500 Switch located anywhere on the network
- **RMON, XRMON, and sFlow**  
provide advanced monitoring and reporting capabilities for statistics, history, alarms, and events
- **IEEE 802.1AB Link Layer Discovery Protocol (LLDP)**  
advertises and receives management information from adjacent devices on a network, facilitating easy mapping by network management applications
- **Command authorization**  
leverages RADIUS to link a custom list of CLI commands to an individual network administrator's login; an audit trail documents activity
- **Friendly port names**  
allow assignment of descriptive names to ports
- **Dual flash images**  
provide independent primary and secondary operating system files for backup while upgrading
- **Multiple configuration files**  
can be stored to the flash image
- **Uni-Directional Link Detection (UDLD)**  
monitors a cable between two switches and shuts down the ports on both ends if the cable is broken, turning the bidirectional link into a unidirectional one; this prevents network problems such as loops
- **Management simplicity**  
provides common software features and CLI implementation across all ProVision-based switches (including the zl and yl switches)
- **NEW Comware-compatible CLI:**
  - **Comware-compatible CLI:** bridges the experience of HP Comware CLI users who are using the HP ProVision software CLI
  - **Display and fundamental Comware CLI commands:** are embedded in the switch CLI as native commands; display output is formatted as on Comware-based switches, and fundamental commands provide a Comware-familiar initial switch setup
  - **Configuration Comware CLI commands:** when Comware commands are entered, CLI help is elicited to formulate the correct ProVision software CLI command

### Connectivity

- **Jumbo frames**  
on Gigabit Ethernet and 10-Gigabit Ethernet ports, jumbo frames allow high-performance remote backup and disaster-recovery services
- **IPv6:**
  - **IPv6 host:** enables switches to be managed in an IPv6 network
  - **Dual stack (IPv4 and IPv6):** transitions from IPv4 to IPv6, supporting connectivity for both protocols
  - **MLD snooping:** forwards IPv6 multicast traffic to the appropriate interface
  - **IPv6 ACL/QoS:** supports ACL and QoS for IPv6 network traffic
  - **IPv6 routing:** supports static and OSPFv3 routing protocols
  - **6in4 tunneling:** supports encapsulation of IPv6 traffic in IPv4 packets

### Performance

### Overview

- **High-speed/capacity architecture**  
105.6 Gbps crossbar switching fabric provides intramodule and intermodule switching with 75.7 million pps throughput on the purpose-built ProVision ASICs
- **Selectable queue configurations**  
allows for increased performance by selecting the number of queues and associated memory buffering that best meet the requirements of the network applications

### Resiliency and high availability

- **Router redundancy**  
VRRP allows groups of two routers to dynamically back each other up to create highly available routed environments
- **IEEE 802.1s Multiple Spanning Tree Protocol**  
provides high link availability in multiple VLAN environments by allowing multiple spanning trees; encompasses IEEE 802.1D Spanning Tree Protocol and IEEE 802.1w Rapid Spanning Tree Protocol
- **IEEE 802.3ad Link Aggregation Control Protocol (LACP) and HP port trunking**  
support up to 144 trunks, each with up to eight links (ports) per trunk
- **Distributed trunking**  
enables loop-free and redundant network topology without using Spanning Tree Protocol; allows a server or switch to connect to two switches using one logical trunk for redundancy and load sharing
- **Uplink Failure Detection**  
provides active-standby network path redundancy for servers that are configured for active-standby NIC teaming

### Layer 2 switching

- **IEEE 802.1ad Q-in-Q**  
increases the scalability of an Ethernet network by providing a hierarchical structure; connects multiple LANs on a high-speed campus or metro network
- **HP switch meshing**  
dynamically load balances across multiple active redundant links to increase available aggregate bandwidth
- **VLAN support and tagging**  
supports complete IEEE 802.1Q standard and 2,048 VLANs simultaneously
- **IEEE 802.1v protocol VLANs**  
isolate select non-IPv4 protocols automatically into their own VLANs
- **GARP VLAN Registration Protocol**  
allows automatic learning and dynamic assignment of VLANs
- **Rapid Per-VLAN Spanning Tree (RPVST+)**  
allows each VLAN to build a separate spanning tree to improve link bandwidth usage; is compatible with PVST+

### Layer 3 services

- **User Datagram Protocol (UDP) helper function**  
allows UDP broadcasts to be directed across router interfaces to specific IP unicast or subnet broadcast addresses and prevents server spoofing for UDP services such as DHCP
- **Loopback interface address**  
defines an address in Routing Information Protocol (RIP) and Open Standard Path First (OSPF), improving diagnostic capability
- **Route map**  
provide more control during route redistribution; allow filtering and altering of route metrics

### Layer 3 routing

- **Static IP routing**

### Overview

- provides manually configured routing for both IPv4 and IPv6 networks
- **Routing Information Protocol (RIP)**  
provides RIPv1 and RIPv2 routing
- **OSPF**  
provides OSPFv2 for IPv4 routing and OSPFv3 for IPv6 routing
- **Border Gateway Protocol (BGP)**  
provides IPv4 Border Gateway Protocol routing, which is scalable, robust, and flexible

### Security

- **Switch CPU protection**  
provides automatic protection against malicious network traffic trying to shut down the switch
- **Virus throttling**  
detects traffic patterns typical of WORM-type viruses and either throttles or entirely prevents the virus from spreading across the routed VLANs without requiring external appliances
- **ICMP throttling**  
defeats ICMP denial-of-service attacks by enabling any switch port to automatically throttle ICMP traffic
- **Multiple user authentication methods:**
  - **IEEE 802.1X users per port:** provides authentication of multiple IEEE 802.1X users per port; prevents user "piggybacking" on another user's IEEE 802.1X authentication
  - **Web-based authentication:** authenticates from Web browser for clients that do not support IEEE 802.1X supplicant; customized remediation can be processed on an external Web server
  - **MAC-based authentication:** client is authenticated with the RADIUS server based on client's MAC address
  - **Concurrent IEEE 802.1X, Web, and MAC authentication schemes per port:** switch port will accept up to 32 sessions of IEEE 802.1X, Web, and MAC authentications
- **Access control lists (ACLs)**  
provide filtering based on the IP field, source/destination IP address/subnet, and source/destination TCP/UDP port number on a per-VLAN or per-port basis
- **Identity-driven ACL**  
enables implementation of a highly granular and flexible access security policy and VLAN assignment specific to each authenticated network user
- **DHCP protection**  
blocks DHCP packets from unauthorized DHCP servers, preventing denial-of-service attacks
- **STP BPDU port protection**  
blocks Bridge Protocol Data Units (BPDUs) on ports that do not require BPDUs, preventing forged BPDU attacks
- **Dynamic IP lockdown**  
works with DHCP protection to block traffic from unauthorized hosts, preventing IP source address spoofing
- **Dynamic ARP protection**  
blocks ARP broadcasts from unauthorized hosts, preventing eavesdropping or theft of network data
- **Detection of malicious attacks**  
monitors 10 types of network traffic and sends a warning when an anomaly that potentially can be caused by malicious attacks is detected
- **Port security**  
allows access only to specified MAC addresses, which can be learned or specified by the administrator
- **MAC address lockout**  
prevents particular configured MAC addresses from connecting to the network
- **Source-port filtering**  
allows only specified ports to communicate with each other
- **RADIUS/TACACS+**  
eases switch management security administration by using a password authentication server

### Overview

- **Secure Shell**  
encrypts all transmitted data for secure remote CLI access over IP networks
- **Secure Sockets Layer (SSL)**  
encrypts all HTTP traffic, allowing secure access to the browser-based management GUI in the switch
- **Secure FTP**  
allows secure file transfer to and from the switch; protects against unwanted file downloads or unauthorized copying of a switch configuration file
- **Management Interface Wizard**  
helps secure management interfaces such as SNMP, telnet, SSH, SSL, Web, and USB at the desired level
- **Secure management access**  
securely encrypts all access methods (CLI, GUI, or MIB) through SSHv2, SSL, and/or SNMPv3
- **Switch management logon security**  
can require either RADIUS or TACACS+ authentication for secure switch CLI logon
- **Security banner:** displays customized security policy when users log in to the switch
- **USB Secure Autorun (requires HP PCM+)**  
deploys, diagnoses, and updates a switch using a USB flash drive; works with a secure credential to prevent tampering
- **STP Root Guard**  
protects the root bridge from malicious attacks or configuration mistakes

### Convergence

- **IP multicast routing**  
includes PIM Sparse and Dense modes to route IP multicast traffic
- **IP multicast snooping (data-driven IGMP)**  
automatically prevents flooding of IP multicast traffic
- **LLDP-MED (Media Endpoint Discovery)**  
is a standard extension of LLDP that stores values for parameters such as QoS and VLAN to automatically configure network devices such as IP phones
- **Auto VLAN configuration for voice:**
  - **RADIUS VLAN:** uses a standard RADIUS attribute and LLDP-MED to automatically configure a VLAN for IP phones
  - **CDPv2:** uses CDPv2 to configure legacy IP phones

### Warranty and support

- **Lifetime warranty**  
for as long as you own the product with advance replacement and next-business-day delivery (available in most countries)†
- **Electronic and telephone support**  
limited electronic and telephone support is available from HP; to reach our support centers, refer to [www.hp.com/networking/contact-support](http://www.hp.com/networking/contact-support); for details on the duration of support provided with your product purchase, refer to [www.hp.com/networking/warrantysummary](http://www.hp.com/networking/warrantysummary)
- **Software releases**  
to find software for your product, refer to [www.hp.com/networking/support](http://www.hp.com/networking/support); for details on the software releases available with your product purchase, refer to [www.hp.com/networking/warrantysummary](http://www.hp.com/networking/warrantysummary)

†HP warranty includes repair or replacement of hardware for as long as you own the product, with next business day advance replacement (available in most countries). The disk drive included with HP AllianceOne Advanced Services and Services zl Modules, HP Threat Management Services zl Module, HP AllianceOne Extended zl Module with Riverbed Steelhead, HP MSM765zl Mobility Controller and HP Survivable Branch Communication zl Module powered by Microsoft Lync has a five-year hardware warranty. For details, refer to the Software license and hardware warranty statements at [www.hp.com/networking/warranty](http://www.hp.com/networking/warranty).

### Technical Specifications

<b>HP 6200-24G-mGBIC yl Switch (J8992A)</b>	<b>Ports</b>	24 open mini-GBIC (SFP) slots Supports a maximum of 4 10-GbE ports, with optional module												
	<b>Physical characteristics</b>	<table border="0"> <tr> <td><b>Dimensions</b></td> <td>17.44(w) x 15.43(d) x 1.73(h) in (44.3 x 39.2 x 4.4 cm) (1U height)</td> </tr> <tr> <td><b>Weight</b></td> <td>14.11 lb (6.4 kg)</td> </tr> </table>	<b>Dimensions</b>	17.44(w) x 15.43(d) x 1.73(h) in (44.3 x 39.2 x 4.4 cm) (1U height)	<b>Weight</b>	14.11 lb (6.4 kg)								
<b>Dimensions</b>	17.44(w) x 15.43(d) x 1.73(h) in (44.3 x 39.2 x 4.4 cm) (1U height)													
<b>Weight</b>	14.11 lb (6.4 kg)													
	<b>Memory and processor</b>	<b>Processor</b> Freescale PowerPC 8540 @ 666 MHz, 4 MB flash, 256 MB DDR SDRAM												
	<b>Mounting</b>	Mounts in an EIA-standard 19 in. telco rack or equipment cabinet (hardware included); horizontal surface mounting only												
	<b>Performance</b>	<table border="0"> <tr> <td><b>1000 Mb Latency</b></td> <td>&lt; 3.7 <math>\mu</math>s (FIFO 64-byte packets)</td> </tr> <tr> <td><b>10 Gbps Latency</b></td> <td>&lt; 2.1 <math>\mu</math>s (FIFO 64-byte packets)</td> </tr> <tr> <td><b>Throughput</b></td> <td>up to 75.7 million pps</td> </tr> <tr> <td><b>Routing/Switching capacity</b></td> <td>101.8 Gbps</td> </tr> <tr> <td><b>Switch fabric speed</b></td> <td>105.6 Gbps</td> </tr> <tr> <td><b>Routing table size</b></td> <td>10000 entries</td> </tr> </table>	<b>1000 Mb Latency</b>	< 3.7 $\mu$ s (FIFO 64-byte packets)	<b>10 Gbps Latency</b>	< 2.1 $\mu$ s (FIFO 64-byte packets)	<b>Throughput</b>	up to 75.7 million pps	<b>Routing/Switching capacity</b>	101.8 Gbps	<b>Switch fabric speed</b>	105.6 Gbps	<b>Routing table size</b>	10000 entries
<b>1000 Mb Latency</b>	< 3.7 $\mu$ s (FIFO 64-byte packets)													
<b>10 Gbps Latency</b>	< 2.1 $\mu$ s (FIFO 64-byte packets)													
<b>Throughput</b>	up to 75.7 million pps													
<b>Routing/Switching capacity</b>	101.8 Gbps													
<b>Switch fabric speed</b>	105.6 Gbps													
<b>Routing table size</b>	10000 entries													
	<b>Environment</b>	<table border="0"> <tr> <td><b>Operating temperature</b></td> <td>32°F to 131°F (0°C to 55°C); 32°F to 104°F (40°C) when used with any X2 10-GbE</td> </tr> <tr> <td><b>Operating relative humidity</b></td> <td>15% to 95% @ 104°F (40°C), noncondensing</td> </tr> <tr> <td><b>Non-operating/Storage temperature</b></td> <td>-40°F to 158°F (-40°C to 70°C)</td> </tr> <tr> <td><b>Non-operating/Storage relative humidity</b></td> <td>15% to 95% at 149°F (65°C), noncondensing</td> </tr> <tr> <td><b>Altitude</b></td> <td>up to 15,000 ft (4.6 km)</td> </tr> <tr> <td><b>Acoustic</b></td> <td>Power: 55.1 dB; DIN 45635T.19 per ISO 7779</td> </tr> </table>	<b>Operating temperature</b>	32°F to 131°F (0°C to 55°C); 32°F to 104°F (40°C) when used with any X2 10-GbE	<b>Operating relative humidity</b>	15% to 95% @ 104°F (40°C), noncondensing	<b>Non-operating/Storage temperature</b>	-40°F to 158°F (-40°C to 70°C)	<b>Non-operating/Storage relative humidity</b>	15% to 95% at 149°F (65°C), noncondensing	<b>Altitude</b>	up to 15,000 ft (4.6 km)	<b>Acoustic</b>	Power: 55.1 dB; DIN 45635T.19 per ISO 7779
<b>Operating temperature</b>	32°F to 131°F (0°C to 55°C); 32°F to 104°F (40°C) when used with any X2 10-GbE													
<b>Operating relative humidity</b>	15% to 95% @ 104°F (40°C), noncondensing													
<b>Non-operating/Storage temperature</b>	-40°F to 158°F (-40°C to 70°C)													
<b>Non-operating/Storage relative humidity</b>	15% to 95% at 149°F (65°C), noncondensing													
<b>Altitude</b>	up to 15,000 ft (4.6 km)													
<b>Acoustic</b>	Power: 55.1 dB; DIN 45635T.19 per ISO 7779													
	<b>Electrical characteristics</b>	<table border="0"> <tr> <td><b>Description</b></td> <td>The switch automatically adjusts to any voltage between 100-127 and 200-240 V with either 50 or 60 Hz.</td> </tr> <tr> <td><b>Maximum heat dissipation</b></td> <td>829 BTU/hr (875 kJ/hr)</td> </tr> <tr> <td><b>Voltage</b></td> <td>100-127/200-240 VAC</td> </tr> <tr> <td><b>Current</b></td> <td>1.8/0.9 A</td> </tr> <tr> <td><b>Power consumption</b></td> <td>243 W</td> </tr> <tr> <td><b>Frequency</b></td> <td>50/60 Hz</td> </tr> </table>	<b>Description</b>	The switch automatically adjusts to any voltage between 100-127 and 200-240 V with either 50 or 60 Hz.	<b>Maximum heat dissipation</b>	829 BTU/hr (875 kJ/hr)	<b>Voltage</b>	100-127/200-240 VAC	<b>Current</b>	1.8/0.9 A	<b>Power consumption</b>	243 W	<b>Frequency</b>	50/60 Hz
<b>Description</b>	The switch automatically adjusts to any voltage between 100-127 and 200-240 V with either 50 or 60 Hz.													
<b>Maximum heat dissipation</b>	829 BTU/hr (875 kJ/hr)													
<b>Voltage</b>	100-127/200-240 VAC													
<b>Current</b>	1.8/0.9 A													
<b>Power consumption</b>	243 W													
<b>Frequency</b>	50/60 Hz													
	<b>Notes</b>	Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.												
	<b>Safety</b>	CSA 22.2 No. 60950; UL 60950; IEC 60950; EN 60950												
	<b>Emissions</b>	FCC Class A; VCCI Class A; EN 55022/CISPR 22 Class A												
	<b>Immunity</b>	<b>EN</b> EN 55024, CISPR 24												

### Technical Specifications

	<b>ESD</b>	IEC 61000-4-2; 4 kV CD, 8 kV AD
	<b>Radiated</b>	IEC 61000-4-3; 3 V/m
	<b>EFT/Burst</b>	IEC 61000-4-4; 1.0 kV (power line), 0.5 kV (signal line)
	<b>Surge</b>	IEC 61000-4-5; 1 kV/2 kV AC
	<b>Conducted</b>	IEC 61000-4-6; 3 V
	<b>Power frequency magnetic field</b>	IEC 61000-4-8; 1 A/m, 50 or 60 Hz
	<b>Voltage dips and interruptions</b>	IEC 61000-4-11; >95% reduction, 0.5 period; 30% reduction, 25 periods
	<b>Harmonics</b>	EN 61000-3-2, IEC 61000-3-2
	<b>Flicker</b>	EN 61000-3-3, IEC 61000-3-3
<b>Management</b>		HP PCM+; HP PCM (included); command-line interface; Web browser; configuration menu; out-of-band management (Serial RS-232C)
<b>Notes</b>		Supported 1G SFP transceivers are revision "B" or later (product number ends with the letter "B" or later; for example, J9142B, J8177C).
<b>Services</b>		3-year, 4-hour onsite, 13x5 coverage for hardware (U2855E) 3-year, 4-hour onsite, 24x7 coverage for hardware (U2856E) 3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 SW phone support and SW updates (U6304E) 3-year, 24x7 SW phone support, software updates (UE262E) 1-year, post-warranty, 4-hour onsite, 13x5 coverage for hardware (HR889E) 1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware (HR890E) 1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (HR891E) Installation with minimum configuration, system-based pricing (U4826E) Installation with HP-provided configuration, system-based pricing (U4830E) 4-year, 4-hour onsite, 13x5 coverage for hardware (UR868E) 4-year, 4-hour onsite, 24x7 coverage for hardware (UR869E) 4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UR870E) 4-year, 24x7 SW phone support, software updates (UR871E) 5-year, 4-hour onsite, 13x5 coverage for hardware (UR872E) 5-year, 4-hour onsite, 24x7 coverage for hardware (UR873E) 5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UR874E) 5-year, 24x7 SW phone support, software updates (UR875E) 3 Yr 6 hr Call-to-Repair Onsite (UW356E) 4 Yr 6 hr Call-to-Repair Onsite (UW357E) 5 Yr 6 hr Call-to-Repair Onsite (UW358E) 1-year, 6 hour Call-To-Repair Onsite for hardware (HR893E) 1-year, 24x7 software phone support, software updates (HR892E) 1-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS610E) 1-year, 24x7 software phone support, software updates + 4 hour hardware exchange (HS611E) 3-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS612E)

### Technical Specifications

- 3-year, 24x7 software phone support, software updates + 4 hour Hardware Exchange (HS613E)
- 4-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS614E)
- 4-year, 24x7 software phone support, software updates + 4 hour Hardware Exchange (HS615E)
- 5-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS616E)
- 5-year, 24x7 software phone support, software updates + 4 hour Hardware Exchange (HS617E)

Refer to the HP website at [www.hp.com/networking/services](http://www.hp.com/networking/services) for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

#### Standards and protocols

##### BGP

- RFC 1997 BGP Communities Attribute
- RFC 2918 Route Refresh Capability
- RFC 4271 A Border Gateway Protocol 4 (BGP-4)
- RFC 4456 BGP Route Reflection: An Alternative to Full Mesh Internal BGP (IBGP)
- RFC 5492 Capabilities Advertisement with BGP-4

##### Device Management

- RFC 1591 DNS (client)
- HTML and telnet management

##### General Protocols

- IEEE 802.1ad Q-in-Q
- IEEE 802.1AX-2008 Link Aggregation
- IEEE 802.1D MAC Bridges
- IEEE 802.1p Priority
- IEEE 802.1Q VLANs
- IEEE 802.1s Multiple Spanning Trees
- IEEE 802.1v VLAN classification by Protocol and Port
- IEEE 802.1w Rapid Reconfiguration of Spanning Tree
- IEEE 802.3ad Link Aggregation Control Protocol (LACP)
- IEEE 802.3x Flow Control
- RFC 768 UDP
- RFC 783 TFTP Protocol (revision 2)
- RFC 792 ICMP
- RFC 793 TCP
- RFC 826 ARP
- RFC 854 TELNET
- RFC 868 Time Protocol
- RFC 951 BOOTP
- RFC 1058 RIPv1
- RFC 1350 TFTP Protocol (revision 2)
- RFC 1519 CIDR
- RFC 1542 BOOTP Extensions
- RFC 2030 Simple Network Time Protocol (SNTP) v4
- RFC 2131 DHCP

### Technical Specifications

#### IP Multicast

RFC 2453 RIPv2  
RFC 2548 (MS-RAS-Vendor only)  
RFC 3046 DHCP Relay Agent Information Option  
RFC 3576 Ext to RADIUS (CoA only)  
RFC 3768 VRRP  
RFC 4675 RADIUS VLAN & Priority  
UDLD (Uni-directional Link Detection)

#### IPv6

RFC 3376 IGMPv3 (host joins only)  
RFC 3973 PIM Dense Mode  
RFC 4601 PIM Sparse Mode  
RFC 1981 IPv6 Path MTU Discovery  
RFC 2375 IPv6 Multicast Address Assignments  
RFC 2460 IPv6 Specification  
RFC 2464 Transmission of IPv6 over Ethernet Networks  
RFC 2710 Multicast Listener Discovery (MLD) for IPv6  
RFC 2925 Definitions of Managed Objects for Remote Ping, Traceroute, and Lookup Operations (Ping only)  
RFC 3019 MLDv1 MIB  
RFC 3315 DHCPv6 (client and relay)  
RFC 3484 Default Address Selection for IPv6  
RFC 3587 IPv6 Global Unicast Address Format  
RFC 3596 DNS Extension for IPv6  
RFC 3810 MLDv2 for IPv6  
RFC 3810 Multicast Listener Discovery Version 2 (MLDv2) for IPv6  
RFC 4022 MIB for TCP  
RFC 4087 IP Tunnel MIB  
RFC 4113 MIB for UDP  
RFC 4213 Basic Transition Mechanisms for IPv6 Hosts and Routers  
RFC 4251 SSHv6 Architecture  
RFC 4252 SSHv6 Authentication  
RFC 4253 SSHv6 Transport Layer  
RFC 4254 SSHv6 Connection  
RFC 4291 IP Version 6 Addressing Architecture  
RFC 4293 MIB for IP  
RFC 4294 IPv6 Node Requirements  
RFC 4419 Key Exchange for SSH  
RFC 4443 ICMPv6  
RFC 4541 IGMP & MLD Snooping Switch  
RFC 4861 IPv6 Neighbor Discovery  
RFC 4862 IPv6 Stateless Address Auto-configuration  
RFC 5095 Deprecation of Type 0 Routing Headers in IPv6  
RFC 5340 OSPF for IPv6

### Technical Specifications

	RFC 5453 Reserved IPv6 Interface Identifiers
	RFC 5519 Multicast Group Membership Discovery MIB (MLDv2 only)
	RFC 5722 Handling of Overlapping IPv6 Fragments
<b>MIBs</b>	IEEE 802.1ap (MSTP and STP MIB's only)
	RFC 1213 MIB II
	RFC 1493 Bridge MIB
	RFC 1724 RIPv2 MIB
	RFC 1850 OSPFv2 MIB
	RFC 2021 RMONv2 MIB
	RFC 2096 IP Forwarding Table MIB
	RFC 2613 SMON MIB
	RFC 2618 RADIUS Client MIB
	RFC 2620 RADIUS Accounting MIB
	RFC 2665 Ethernet-Like-MIB
	RFC 2668 802.3 MAU MIB
	RFC 2674 802.1p and IEEE 802.1Q Bridge MIB
	RFC 2737 Entity MIB (Version 2)
	RFC 2787 VRRP MIB
	RFC 2863 The Interfaces Group MIB
	RFC 2925 Ping MIB
	RFC 2933 IGMP MIB
<b>Network Management</b>	IEEE 802.1AB Link Layer Discovery Protocol (LLDP)
	RFC 2819 Four groups of RMON: 1 (statistics), 2 (history), 3 (alarm) and 9 (events)
	RFC 3176 sFlow
	ANSI/TIA-1057 LLDP Media Endpoint Discovery (LLDP-MED)
	SNMPv1/v2c/v3
	XRMON
<b>OSPF</b>	RFC 2328 OSPFv2
	RFC 3101 OSPF NSSA
	RFC 5340 OSPF for IPv6
<b>QoS/Cos</b>	RFC 2474 DiffServ Precedence, including 8 queues/port
	RFC 2597 DiffServ Assured Forwarding (AF)
	RFC 2598 DiffServ Expedited Forwarding (EF)
<b>Security</b>	IEEE 802.1X Port Based Network Access Control
	RFC 1492 TACACS+
	RFC 2865 RADIUS (client only)
	RFC 2866 RADIUS Accounting
	RFC 3579 RADIUS Support For Extensible Authentication Protocol (EAP)
	Secure Sockets Layer (SSL)
	SSHv2 Secure Shell

### Accessories

#### HP 6200-24G-mGBIC yl Switch accessories

<b>Modules</b>	HP 10GbE 2-port SFP+/2-port CX4 yl Module	J9312A
	HP 10GbE 2-port X2 / 2-port CX4 yl Module	J8694A
<hr/>		
<b>EPS/RPS</b>	HP 620 Redundant/External Power Supply	J8696A
<hr/>		
<b>Transceivers</b>	HP X131 10G X2 SC ER Transceiver	J8438A
	HP X131 10G X2 SC SR Transceiver	J8436A
	HP X131 10G X2 CX4 Transceiver	J8440C
	HP X111 100M SFP LC FX Transceiver	J9054C
	HP X131 10G X2 SC LR Transceiver	J8437A
	HP X131 10G X2 SC LRM Transceiver	J9144A
	HP X112 100M SFP LC BX-D Transceiver	J9099B
	HP X112 100M SFP LC BX-U Transceiver	J9100B
	HP X121 1G SFP LC LH Transceiver	J4860C
	HP X121 1G SFP LC SX Transceiver	J4858C
	HP X121 1G SFP LC LX Transceiver	J4859C
	HP X121 1G SFP RJ45 T Transceiver	J8177C
	HP X122 1G SFP LC BX-D Transceiver	J9142B
HP X122 1G SFP LC BX-U Transceiver	J9143B	
<hr/>		
<b>Cables</b>	HP 0.5 m Multimode OM3 LC/LC Optical Cable	AJ833A
	HP Premier Flex LC/LC Multi-mode OM4 2 fiber 1m Cable	QK732A
	HP Premier Flex LC/LC Multi-mode OM4 2 fiber 2m Cable	QK733A
	HP Premier Flex LC/LC Multi-mode OM4 2 fiber 5m Cable	QK734A
	HP Premier Flex LC/LC Multi-mode OM4 2 fiber 15m Cable	QK735A
	HP Premier Flex LC/LC Multi-mode OM4 2 fiber 30m Cable	QK736A
	HP Premier Flex LC/LC Multi-mode OM4 2 fiber 50m Cable	QK737A

### Accessory Product Details

<b>HP 10GbE 2-port X2/2-port CX4 yl Module</b> (J8694A)	<b>Ports</b>	2 open 10-GbE X2 transceiver slots 2 10-GbE ports (IEEE 802.3ak Type 10GBASE-CX4); Duplex: full only
	<b>Physical characteristics</b>	<b>Dimensions</b> 7.76(d) x 7.52(w) x 14.29(h) in. (19.7 x 19.1 x 36.3 cm) <b>Weight</b> 1.54 lb. (0.7 kg)
	<b>Environment</b>	<b>Operating temperature</b> 32°F to 131°F (0°C to 55°C) <b>Operating relative humidity</b> 15% to 95%, noncondensing <b>Nonoperating/Storage temperature</b> -40°F to 158°F (-40°C to 70°C) <b>Nonoperating/Storage relative humidity</b> 15% to 90%, noncondensing
	<b>Cabling</b>	Maximum distance: • CX4: 15 m using CX4 cable or 300 m using media converter with ribbon MMF
	<b>Notes</b>	Only the two fixed CX4 ports on this module support HP ProCurve 10-GbE CX4 Media Converter (J8439A). Operating temperature is 32°F to 104°F (0°C to 40°C) if any X2 10-GbE optic or transceiver is inserted in any X2 slot. One 0.5 m CX4 cable is included.
	<b>Services</b>	Refer to the HP website at: <a href="http://www.hp.com/networking/services">www.hp.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

<b>HP 10GbE 2-port SFP+/2-port CX4 yl Module</b> (J9312A)	<b>Ports</b>	2 SFP+ 10-GbE ports (IEEE 802.3ae Type 10GBASE-LR); Duplex: full only 2 CX4 10-GbE ports (IEEE 802.3ak Type 10GBASE-CX4); Duplex: full only
	<b>Physical characteristics</b>	<b>Dimensions</b> 7.76(d) x 7.52(w) x 14.29(h) in. (19.7 x 19.1 x 36.3 cm) <b>Weight</b> 1.45 lb. (0.66 kg)
	<b>Environment</b>	<b>Operating temperature</b> 32°F to 131°F (0°C to 55°C) <b>Operating relative humidity</b> 15% to 95%, noncondensing <b>Nonoperating/Storage temperature</b> -40°F to 158°F (-40°C to 70°C) <b>Nonoperating/Storage relative humidity</b> 15% to 90%, noncondensing
	<b>Cabling</b>	Maximum distance: • CX4: 15 m using CX4 cable or 300 m using media converter with ribbon MMF
	<b>Notes</b>	Only the two fixed CX4 ports on this module support HP ProCurve 10-GbE CX4 Media Converter (J8439A). Operating temperature is 32°F to 104°F (0°C to 40°C) if any SFP+ 10-GbE optic or transceiver is inserted in any SFP+ slot. One 0.5 m CX4 cable is included.

### Accessory Product Details

**Services** Refer to the HP website at: [www.hp.com/networking/services](http://www.hp.com/networking/services) for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

<b>HP 620 Redundant/External Power Supply (J8696A)</b>	<b>Ports</b>	2 redundant power supply ports Restrictions: 195 W available per port
		2 external power supply ports Restrictions: 398 W available per port
	<b>Physical characteristics</b>	<b>Dimensions</b> 15.4(d) x 17.4(w) x 1.73(h) in. (39.12 x 44.2 x 4.39 cm) (1U height)
		<b>Weight</b> 15.2 lb. (6.89 kg)
	<b>Mounting</b>	Mounts in an EIA-standard 19 in. telco rack or equipment cabinet (hardware included); horizontal surface mounting only
	<b>Environment</b>	<b>Operating temperature</b> 32°F to 131°F (0°C to 55°C) <b>Operating relative humidity</b> 15% to 95% @ 104°F (40°C), noncondensing <b>Nonoperating/Storage temperature</b> -40°F to 158°F (-40°C to 70°C) <b>Nonoperating/Storage relative humidity</b> 15% to 90% @ 149°F (65°C), noncondensing <b>Altitude</b> up to 10,000 ft. (3 km) <b>Acoustic</b> LwA per ISO 7779: 54.2 dB
	<b>Electrical characteristics</b>	<b>Maximum heat dissipation</b> 400 BTU/hr (422 kJ/hr), for the actual 620 itself. PoE-powered device heat dissipation assumed to be outside the 620. <b>Voltage</b> 100-127/200-240 VAC <b>Current</b> 16/8 A <b>Maximum power rating</b> 1440 W <b>RPS power</b> 390 W <b>PoE power</b> 796 W <b>RPS</b> 12 V <b>PoE</b> -50 V <b>Frequency</b> 50/60 Hz <b>Notes</b> Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated. Above figures are for maximum RPS and PoE power being supplied to two switches simultaneously. 200 - 240 V power cords shipped with the 620 have a wall plug rated as close to 13 A as specific country standards allow.

### Accessory Product Details

<b>Safety</b>	CSA 22.2 No. 60950; EN 60950/IEC 60950; UL 60950
<b>Emissions</b>	FCC Class A; VCCI Class A; EN 55022/CISPR 22 Class A
<b>Immunity</b>	<b>EN</b> EN 55024, CISPR 24
	<b>ESD</b> IEC 61000-4-2
	<b>Radiated</b> IEC 61000-4-3
	<b>EFT/Burst</b> IEC 61000-4-4
	<b>Surge</b> IEC 61000-4-5
	<b>Conducted</b> IEC 61000-4-6
	<b>Power frequency magnetic field</b> IEC 61000-4-8
	<b>Voltage dips and interruptions</b> IEC 61000-4-11
	<b>Harmonics</b> EN 61000-3-2, IEC 61000-3-2
	<b>Flicker</b> EN 61000-3-3, IEC 61000-3-3
<b>Management</b>	Unmanaged power supply; provides information via LEDs (LEDs repeated on front and back panel) or through port interfaces of attached devices
<b>Notes</b>	<p>The 620 supports the HP Switch 2900 Series (RPS) and 3500yl Series (RPS/PoE), as well as 6200yl (RPS) switches. The HP Switch 5400zl Series is not supported.</p> <p>The 620 includes four 2 m RPS/EPs cables. These cables can be used to carry either RPS or PoE power to the switch being powered.</p>
<b>Services</b>	<p>3-year, 4-hour onsite, 13x5 coverage for hardware (U9270E) 3-year, 4-hour onsite, 24x7 coverage for hardware (U9271E) 4-year, 4-hour onsite, 13x5 coverage for hardware (UR854E) 4-year, 4-hour onsite, 24x7 coverage for hardware (UR855E) 5-year, 4-hour onsite, 13x5 coverage for hardware (UR857E) 5-year, 4-hour onsite, 24x7 coverage for hardware (UR858E) 3 Yr 6 hr Call-to-Repair Onsite (UW371E) 4 Yr 6 hr Call-to-Repair Onsite (UW372E) 5 Yr 6 hr Call-to-Repair Onsite (UW373E)</p> <p>Refer to the HP website at: <a href="http://www.hp.com/networking/services">www.hp.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.</p>

### Accessory Product Details

<b>HP X131 10G X2 SC ER Transceiver (J8438A)</b>  HP X131 10G X2 SC ER Transceiver: An X2 format 10-gigabit transceiver with SC connectors using ER technology.	<b>Ports</b> <b>Connectivity</b>	1 SC 10-GbE port (IEEE 802.3ae Type 10GBASE-ER); Duplex: full only <b>Connector type</b> SC
	<b>Physical characteristics</b>	<b>Wavelength</b> 1550 nm <b>Dimensions</b> 3.48(d) x 1.42(w) x 0.43(h) in. (8.84 x 3.61 x 1.09 cm) <b>Weight</b> 0.35 lb. (0.16 kg) <b>Transceiver form factor</b> X2
<b>Environment</b>	<b>Operating temperature</b> 32°F to 104°F (0°C to 40°C) <b>Operating relative humidity</b> 15% to 95%, noncondensing	
	<b>Electrical characteristics</b>	<b>Power consumption typical</b> 3 W <b>Power consumption maximum</b> 4.5 W
<b>Cabling</b>	Cable type:: Low metal content, single-mode fiber-optic, complying with ITU-T G.652 and ISO/IEC 793-2 Type B1; <b>Cable length</b> 2m to 30km (max 40km on engineered links) <b>Fiber type</b> Single Mode	
<b>Notes</b>	Conditioning patch cord cables are not supported For fiber patch cords, use Ultra Physical Contact (UPC) surface termination/polish. Angled Physical Contact (APC) is not recommended.	
<b>Services</b>	Refer to the HP website at <a href="http://www.hp.com/networking/services">www.hp.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.	

<b>HP X131 10G X2 SC SR Transceiver (J8436A)</b>  HP X131 10G X2 SC SR Transceiver: An X2 format 10-gigabit transceiver with SC connectors using SR technology.	<b>Ports</b> <b>Connectivity</b>	1 SC 10-GbE port (IEEE 802.3ae Type 10GBASE-SR); Duplex: full only <b>Connector type</b> SC
	<b>Physical characteristics</b>	<b>Wavelength</b> 850 nm <b>Dimensions</b> 3.48(d) x 1.42(w) x 0.43(h) in. (8.84 x 3.61 x 1.09 cm) <b>Weight</b> 0.35 lb. (0.16 kg) <b>Transceiver form factor</b> X2
<b>Environment</b>	<b>Operating temperature</b> 32°F to 158°F (0°C to 70°C) <b>Operating relative humidity</b> 0% to 95%, noncondensing <b>Nonoperating/Storage temperature</b> -40°F to 185°F (-40°C to 85°C)	
	<b>Nonoperating/Storage relative humidity</b> 0% to 95%, noncondensing <b>Altitude</b> up to 10,000 ft. (3 km)	

### Accessory Product Details

<b>Electrical characteristics</b>	<b>Power consumption typical</b>	1.7 W
	<b>Power consumption maximum</b>	2.4 W
<b>Cabling</b>	Cable type:: 62.5/125 µm or 50/125 µm (core/cladding) graded-index, low metal content, multimode fiber optic, complying with ITU-T G.651 and ISO/IEC 793-2 Type A1b or A1a, respectively;	
	Maximum distance:	
	<ul style="list-style-type: none"> <li>• 2-26m with 62.5 µm multimode cable @ 160 MHz*km</li> <li>• 2-33m with 62.5 µm multimode cable @ 200 MHz*km</li> <li>• 2-66m with 50 µm multimode cable @ 400 MHz*km</li> <li>• 2-82m with 50 µm multimode cable @ 500 MHz*km</li> <li>• 2-300m with 50 µm multimode cable @ 2000 MHz*km</li> </ul>	
	<b>Cable length</b>	2-300m
	<b>Fiber type</b>	Multi Mode
<b>Notes</b>	For fiber patch cords, use Ultra Physical Contact (UPC) surface termination/polish. Angled Physical Contact (APC) is not recommended.	
<b>Services</b>	Refer to the HP website at <a href="http://www.hp.com/networking/services">www.hp.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.	

<b>HP X131 10G X2 CX4 Transceiver (J8440C)</b>	<b>Ports</b>	1 CX4 10-GbE port (IEEE 802.3ak Type 10GBASE-CX4); Duplex: full only
	<b>Connectivity</b>	<b>Connector type</b> CX4
HP X131 10G X2 CX4 Transceiver: An X2 format 10-gigabit CX4 transceiver.	<b>Physical characteristics</b>	<b>Dimensions</b> 3.54(d) x 1.42(w) x 0.53(h) in. (8.99 x 3.61 x 1.35 cm)
		<b>Weight</b> 0.18 lb. (0.08 kg)
		<b>Transceiver form factor</b> X2
	<b>Environment</b>	<b>Operating temperature</b> 32°F to 131°F (0°C to 55°C)
		<b>Operating relative humidity</b> 15% to 95%, noncondensing
		<b>Nonoperating/Storage temperature</b> -40°F to 185°F (-40°C to 85°C)
		<b>Altitude</b> up to 10,000 ft. (3 km)
	<b>Electrical characteristics</b>	<b>Power consumption typical</b> 1.0 W
		<b>Power consumption maximum</b> 3.3 W
	<b>Cabling</b>	Maximum distance: <ul style="list-style-type: none"> <li>• 15m with CX4 cables</li> <li>• 300m with optical media converter and multimode fiber cable</li> </ul>
	<b>Notes</b>	Connector: CX4; Duplex: full Use CX4 10-GbE cable (0.5-15 m) or HP X130 CX4 Optical Media Converter

### Accessory Product Details

(J8439A).

For suggested vendors of CX4 cables, please see the "Cabling" answers on the "HP 10-GbE Transceivers" FAQs Web page.

Optical Media Converter (OMC) J8439A is not supported on the C version as the power supply for the OMC was removed in this design.

#### Services

Refer to the HP website at [www.hp.com/networking/services](http://www.hp.com/networking/services) for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

#### HP X111 100M SFP LC FX Transceiver (J9054C)

#### Ports

1 LC 100BASE-FX port (IEEE 802.3u Type 100BASE-FX); Duplex: half or full

#### Physical characteristics

##### Dimensions

2.7(d) x 0.54(w) x 0.48(h) in. (6.86 x 1.38 x 1.22 cm)

##### Weight

0.06 lb. (0.03 kg)

#### Environment

##### Operating temperature

32°F to 158°F (0°C to 70°C)

##### Operating relative humidity

5% to 95%

##### Nonoperating/Storage temperature

-40°F to 185°F (-40°C to 85°C)

##### Nonoperating/Storage relative humidity

5% to 85%

##### Altitude

up to 10,000 ft. (3 km)

#### Cabling

Cable type:

62.5/125  $\mu$ m or 50/125  $\mu$ m (core/cladding) diameter, graded-index, low metal content, multimode fiber optic, complying with ITU-T G.651 and ISO/IEC 793-2 Type A1b or A1a, respectively;

Maximum distance:

- 2 km (full duplex) or 412 m (half duplex)

#### Notes

Transmitter wavelength: 1310nm

Power consumption is 1.1 watt maximum.

For supported platforms and minimum software requirements to support this product, see the document titled "Support for the J9054B 100-FX SFP-LC Transceiver" on the "ProCurve Mini-GBICs and SFPs" Manuals Web page.

#### Services

Refer to the HP website at: [www.hp.com/networking/services](http://www.hp.com/networking/services) for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

### Accessory Product Details

<b>HP X131 10G X2 SC LR Transceiver (J8437A)</b>  An X2 form-factor transceiver that supports the 10-Gigabit LR standard, providing 10-Gigabit connectivity up to 10 km on single-mode fiber.	<b>Ports</b> 1 SC 10-GbE port (IEEE 802.3ae Type 10GBASE-LR); Duplex: full only
	<b>Connectivity</b> <b>Connector type</b> SC <b>Wavelength</b> 1310 nm
<b>Physical characteristics</b>  <b>Environment</b>	<b>Dimensions</b> 3.48(d) x 1.42(w) x 0.43(h) in. (8.84 x 3.61 x 1.09 cm) <b>Weight</b> 0.35 lb. (0.16 kg) <b>Transceiver form factor</b> X2
	<b>Operating temperature</b> 32°F to 104°F (0°C to 40°C) <b>Operating relative humidity</b> 15% to 95%, noncondensing <b>Nonoperating/Storage temperature</b> -40°F to 185°F (-40°C to 85°C) <b>Altitude</b> up to 10,000 ft. (3 km)
<b>Electrical characteristics</b>	<b>Power consumption typical</b> 2 W <b>Power consumption maximum</b> 3 W
	<b>Cabling</b> Cable type:: Low metal content, single-mode fiber-optic, complying with ITU-T G.652 and ISO/IEC 793-2 Type B1;  Maximum distance: <ul style="list-style-type: none"> <li>• 10 km</li> </ul> <b>Cable length</b> 2m to 10km with 9/125 im single-mode cable <b>Fiber type</b> Single Mode
<b>Notes</b>	Conditioning patch cord cables are not supported For fiber patch cords, use Ultra Physical Contact (UPC) surface termination/polish. Angled Physical Contact (APC) is not recommended
<b>Services</b>	Refer to the HP website at <a href="http://www.hp.com/networking/services">www.hp.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

### Accessory Product Details

#### HP X131 10G X2 SC LRM Transceiver (J9144A)

An X2 form-factor transceiver that supports the 10-Gigabit LRM standard, providing 10-Gigabit connectivity up to 220 m on legacy multimode fiber.

<b>Ports</b>	1 SC 10-GbE port (IEEE 802.3aq Type 10GBASE-LRM); Duplex: full only
<b>Physical characteristics</b>	<p><b>Dimensions</b> 3.54(d) x 1.59(w) x 0.7(h) in. (9.0 x 4.05 x 1.78 cm)</p> <p><b>Weight</b> 0.35 lb. (0.16 kg)</p> <p><b>Transceiver form factor</b> X2</p>
<b>Environment</b>	<p><b>Operating temperature</b> 32°F to 158°F (0°C to 70°C)</p> <p><b>Operating relative humidity</b> 0% to 95%, noncondensing</p> <p><b>Nonoperating/Storage temperature</b> -40°F to 185°F (-40°C to 85°C)</p> <p><b>Altitude</b> up to 10,000 ft. (3 km)</p>
<b>Electrical characteristics</b>	<p><b>Power consumption typical</b> 3.2 W</p> <p><b>Power consumption maximum</b> 4.2 W</p>
<b>Cabling</b>	<p>Cable type: 62.5/125 µm or 50/125 µm (core/cladding) diameter, graded-index, low metal content, multimode fiber optic, complying with ITU-T G.651 and ISO/IEC 793-2 Type A1b or A1a, respectively (a mode conditioning patch cord may be needed in some multimode fiber installations);</p> <p>Maximum distance:</p> <ul style="list-style-type: none"> <li>• 0.5-220m with 62.5 µm multimode cable @ 160/500 MHz*km</li> <li>• 0.5-220m with 62.5 µm multimode cable @ 200/500 MHz*km</li> <li>• 0.5-100m with 50 µm multimode cable @ 400/400 MHz*km</li> <li>• 0.5-220m with 50 µm multimode cable @ 500/500 MHz*km</li> <li>• 0.5-220m with 50 µm multimode cable @ 1500/500 MHz*km</li> </ul> <p><b>Cable length</b> .5m to 220m</p> <p><b>Fiber type</b> Multi Mode</p>
<b>Notes</b>	<p>Wavelength: 1310nm</p> <p>For OM3 cable (50 im multimode @ 1500/500 MHz*km), a mode-conditioning patch cord is not required. Other multimode cables may require mode-conditioning patch cords to achieve the maximum distances listed above.</p> <p>For supported platforms and minimum software requirements to support this product, see the document titled "Support for the J9144A 10-GbE X2-SC LRM Optic" on the "HP 10-GbE Transceivers" Manuals Web page.</p> <p>Power Consumption: 4W Max</p>
<b>Services</b>	Refer to the HP website at <a href="http://www.hp.com/networking/services">www.hp.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

### Accessory Product Details

#### HP X112 100M SFP LC BX-D Ports Transceiver (J9099B)

A small form-factor pluggable (SFP) 100-Megabit BX (bi-directional) "downstream" transceiver that provides 100 Mbps full-duplex connectivity up to 10 km on one strand of singlemode fiber. The J9099B connects to the J9100B "upstream" transceiver, or to any IEEE-standard 100BASE-BX10-U ("upstream") device.

#### Physical characteristics

1 LC 100BASE-BX10 port (IEEE 802.3ah Type 100BASE-BX10-D); Duplex: full only

#### Dimensions

2.7(d) x 0.55(w) x 0.48(h) in. (6.86 x 1.39 x 1.22 cm)

#### Weight

0.04 lb. (0.03 kg)

#### Environment

#### Operating temperature

32°F to 158°F (0°C to 70°C)

#### Operating relative humidity

0% to 95%, noncondensing

#### Cabling

#### Nonoperating/Storage temperature

-40°F to 185°F (-40°C to 85°C)

Type:

Single-mode fiber optic, complying with ITU-T G.652;

Maximum distance:

- 0.5-10,000 m (single-mode fiber)

#### Notes

Transmit wavelength: 1550 nm. Receive wavelength: 1310 nm.

Power consumption is 1.1 watt maximum.

For supported platforms and minimum software requirements to support this product, see the document titled "Support for the HP BX Transceivers" on the "HP Mini-GBICs and SFPs" Manuals Web page.

The J9099B connects to the J9100B "upstream" transceiver, or to any IEEE-standard 100BASE-BX10-U ("upstream") device. (A 100-BX-D transceiver can only connect to a 100-BX-U product. You cannot connect two 100-BX-D transceivers together.)

#### Services

Refer to the HP website at [www.hp.com/networking/services](http://www.hp.com/networking/services) for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

#### HP X112 100M SFP LC BX-U Ports Transceiver (J9100B)

A small form-factor pluggable (SFP) 100-Megabit BX (bi-directional) "upstream" transceiver that provides 100 Mbps full-duplex connectivity up to 10 km on one strand of singlemode fiber. The J9100B connects to the J9099B "downstream" transceiver, or to any IEEE-standard 100BASE-BX10-D ("downstream") device.

#### Physical characteristics

1 LC 100BASE-BX10 port (IEEE 802.3ah Type 100BASE-BX10-U); Duplex: full only

#### Dimensions

2.7(d) x 0.55(w) x 0.48(h) in. (6.86 x 1.39 x 1.22 cm)

#### Weight

0.07 lb. (.03 kg)

#### Environment

#### Operating temperature

32°F to 158°F (0°C to 70°C)

#### Operating relative humidity

0% to 95%, noncondensing

#### Cabling

#### Nonoperating/Storage temperature

-40°F to 185°F (-40°C to 85°C)

Type:

Single-mode fiber optic, complying with ITU-T G.652;

Maximum distance:

- 0.5-10,000 m (single-mode fiber)

### Accessory Product Details

<b>Notes</b>	<p>For supported platforms and minimum software requirements to support this product, see the document titled "Support for the HP BX Transceivers" on the "HP Mini-GBICs and SFPs" Manuals Web page.</p> <p>The J9100B connects to the J9099B "downstream" transceiver, or to any IEEE-standard 100BASE-BX10-D ("downstream") device. (A 100-BX-U transceiver can only connect to a 100-BX-D product. You cannot connect two 100-BX-U transceivers together.)</p> <p>Transmit wavelength: 1310 nm. Receive wavelength: 1550 nm.</p> <p>Power consumption is 1.1 watts maximum.</p>
<b>Services</b>	<p>Refer to the HP website at <a href="http://www.hp.com/networking/services">www.hp.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.</p>

#### HP X121 1G SFP LC LH Transceiver (J4860C)

A small form-factor pluggable (SFP) Gigabit LH transceiver that provides a full-duplex Gigabit solution up to 70 km on single-mode fiber.

<b>Ports</b>	1 LC 1000BASE-LH port (no IEEE standard exists for 1550 nm optics); Duplex: full only
<b>Physical characteristics</b>	Dimensions: 2.17(d) x 0.60(w) x 0.46(h) in. (5.5 x 1.53 x 1.18 cm) Weight: 0.04 lb. (0.02 kg)
<b>Environment</b>	Operating temperature: -40°F to 185°F (-40°C to 85°C) Operating relative humidity: 0% to 95% @ 77°F (25°C), noncondensing Nonoperating/Storage temperature: -40°F to 185°F (-40°C to 85°C) Altitude: up to 10,000 ft. (3 km)
<b>Cabling</b>	Cable type: <ul style="list-style-type: none"><li>• Low metal content, single-mode fiber-optic, complying with ITU-T G.652 and ISO/IEC 793-2 Type B1;</li></ul> Maximum distance: <ul style="list-style-type: none"><li>• 10-70,000 m (single-mode fiber)</li></ul>
<b>Notes</b>	Power consumption is 0.8 watts typical with 1 watt maximum at 100% utilization. For distances less than 20 km, a 10 dB attenuator must be used. For distances between 20 km and 40 km, a 5 dB attenuator must be used. Attenuators can be purchased from most cable vendors.
<b>Services</b>	Refer to the HP website at <a href="http://www.hp.com/networking/services">www.hp.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

### Accessory Product Details

<p><b>HP X121 1G SFP LC SX Transceiver (J4858C)</b></p>	<p><b>Ports</b> <b>Physical characteristics</b></p>	<p>1 LC 1000BASE-SX port; Duplex: full only Dimensions: 2.24(d) x 0.54(w) x 0.48(h) in. (5.69 x 1.37 x 1.22 cm) Weight: 0.04 lb. (0.02 kg) Transceiver form factor: SFP</p>
<p>A small form-factor pluggable (SFP) Gigabit SX transceiver that provides a full-duplex Gigabit solution up to 550 m on multimode fiber.</p>	<p><b>Environment</b></p>	<p>Operating temperature: 32°F to 158°F (0°C to 70°C) Operating relative humidity: 5% to 85%, noncondensing Nonoperating/Storage temperature: -40°F to 203°F (-40°C to 85°C) Altitude: up to 10,000 ft. (3 km)</p>
	<p><b>Electrical characteristics</b></p>	<p>Power consumption typical: 0.4 W Power consumption maximum: 0.7 W</p>
	<p><b>Cabling</b></p>	<p>Type:</p> <ul style="list-style-type: none"> <li>● 62.5/125 µm or 50/125 µm (core/cladding) diameter, graded-index, low metal content, multimode fiber optic, complying with ITU-T G.651 and ISO/IEC 793-2 Type A1b or A1a, respectively;</li> </ul> <p>Maximum distance:</p> <ul style="list-style-type: none"> <li>● 2-220 m (62.5 µm core diameter, 160 MHz*km bandwidth)</li> <li>● 2-275 m (62.5 µm core diameter, 200 MHz*km bandwidth)</li> <li>● 2-500 m (50 µm core diameter, 400 MHz*km bandwidth)</li> <li>● 2-550 m (50 µm core diameter, 500 MHz*km bandwidth)</li> </ul> <p>Cable length: 2-550m Fiber type: Multi Mode</p>
	<p><b>Services</b></p>	<p>Refer to the HP website at <a href="http://www.hp.com/networking/services">www.hp.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.</p>

---

<p><b>HP X121 1G SFP LC LX Transceiver (J4859C)</b></p>	<p><b>Ports</b> <b>Physical characteristics</b></p>	<p>1 LC 1000BASE-LX port (IEEE 802.3z Type 1000BASE-LX); Duplex: full only Dimensions: 2.24(d) x 0.54(w) x 0.486(h) in. (5.69 x 1.37 x 1.23 cm) Weight: 0.04 lb. (0.02 kg)</p>
<p>HP X121 1G SFP LC LX Transceiver: An SFP format gigabit transceiver with LC connectors using LX technology.</p>	<p><b>Environment</b></p>	<p>Operating temperature: 32°F to 158°F (0°C to 70°C) Operating relative humidity: 0% to 85%, noncondensing Nonoperating/Storage temperature: -40°F to 212°F (-40°C to 100°C) Altitude: up to 10,000 ft. (3 km)</p>
	<p><b>Cabling</b></p>	<p>Type:</p> <ul style="list-style-type: none"> <li>● Either single mode or multimode; 62.5/125 µm or 50/125 µm (core/cladding) diameter, graded-index, low metal content, multimode fiber optic, complying with ITU-T G.651 and ISO/IEC 793-2 Type A1b or A1a, respectively; Low metal content, single-mode fiber-optic, complying with ITU-T G.652 and ISO/IEC 793-2 Type B1;</li> </ul> <p>Maximum distance:</p> <ul style="list-style-type: none"> <li>● 2-550 m (multimode 62.5 µm core diameter, 500 MHz*km bandwidth)</li> <li>● 2-550 m (multimode 50 µm core diameter, 400 MHz*km bandwidth)</li> <li>● 2-550 m (multimode 50 µm core diameter, 500 MHz*km bandwidth)</li> <li>● 2-10,000 m (single-mode fiber)</li> </ul>

### Accessory Product Details

<b>Notes</b>	A mode conditioning patch cord may be needed in some multimode fiber installations. Wavelength: 1310nm Power Consumption: < 500mW Typical
<b>Services</b>	Refer to the HP website at <a href="http://www.hp.com/networking/services">www.hp.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

#### HP X122 1G SFP LC BX-D Transceiver (J9142B)

A small form-factor pluggable (SFP) Gigabit-BX (bi-directional) "downstream" transceiver that provides a full-duplex Gigabit solution up to 10 km on one strand of single-mode fiber. The J9142B connects to the J9143B "upstream" transceiver, or to any IEEE-standard 1000BASE-BX10-U ("upstream") device.

<b>Ports</b>	1 LC 1000BASE-BX10 port (IEEE 802.3ah Type 1000BASE-BX10-D); Duplex: full only
<b>Physical characteristics</b>	<b>Dimensions</b> 2.19(d) x 0.54(w) x 0.46(h) in. (5.57 x 1.37 x 1.18 cm)
<b>Environment</b>	<b>Weight</b> 0.04 lb. (0.02 kg) <b>Operating temperature</b> 32°F to 158°F (0°C to 70°C) <b>Operating relative humidity</b> 0% to 95%, non-condensing <b>Non-operating/Storage temperature</b> -40°F to 185°F -40°C to 85°C
<b>Cabling</b>	<b>Type:</b> Single-mode fiber optic, complying with ITU-T G.652;  <b>Maximum distance:</b> <ul style="list-style-type: none"><li>• 0.5-10,000 m (single-mode fiber)</li></ul>
<b>Notes</b>	Transmit wavelength: 1490 nm. Receive wavelength: 1310 nm. Power consumption is 1 watt maximum. For supported platforms and minimum software requirements to support this product, see the document titled "Support for the HP BX Transceivers" on the "HP Mini-GBICs and SFPs" Manuals Web page. The J9142B connects to the J9143B "upstream" transceiver, or to any IEEE-standard 1000BASE-BX10-U ("upstream") device. (A 1000-BX-D transceiver can only connect to a 1000-BX-U product. You cannot connect two 1000-BX-D transceivers together.)
<b>Services</b>	Refer to the HP website at: <a href="http://www.hp.com/networking/services">www.hp.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

### Accessory Product Details

#### HP X122 1G SFP LC BX-U Ports Transceiver (J9143B)

A small form-factor pluggable (SFP) Gigabit-BX (bi-directional) "upstream" transceiver that provides a full-duplex Gigabit solution up to 10 km on one strand of single-mode fiber. The J9143B connects to the J9142B "downstream" transceiver, or to any IEEE-standard 1000BASE-BX10-D ("downstream") device.

<b>Ports</b>	1 LC 1000BASE-BX10 port (IEEE 802.3ah Type 1000BASE-BX10-U); Duplex: full only
<b>Physical characteristics</b>	<b>Dimensions</b> 2.19(d) x 0.54(w) x 0.46(h) in. (5.57 x 1.37 x 1.18 cm)
<b>Environment</b>	<b>Weight</b> 0.04 lb. (0.02 kg)
<b>Cabling</b>	<b>Operating temperature</b> 32°F to 158°F (0°C to 70°C)
<b>Notes</b>	<b>Operating relative humidity</b> 0% to 95%, non-condensing
<b>Services</b>	<b>Non-operating/Storage temperature</b> -40°F to 185°F -40°C to 85°C
	Type: Single-mode fiber optic, complying with ITU-T G.652;
	Maximum distance:
	<ul style="list-style-type: none"> <li>● 0.5-10,000 m (single-mode fiber)</li> </ul>
	Transmit wavelength: 1310 nm. Receive wavelength: 1490 nm. For supported platforms and minimum software requirements to support this product, see the document titled "Support for the HP BX Transceivers" on the "HP Mini-GBICs and SFPs" Manuals Web page. The J9143B connects to the J9142B "downstream" transceiver, or to any IEEE-standard 1000BASE-BX10-D ("downstream") device. (A 1000-BX-U transceiver can only connect to a 1000-BX-D product. You cannot connect two 1000-BX-U transceivers together.) Power consumption is 1 watt maximum.
	Refer to the HP website at: <a href="http://www.hp.com/networking/services">www.hp.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

#### HP 0.5 m Multimode OM3 LC/LC Optical Cable (AJ833A)

<b>Cabling</b>	<b>Cable type:</b> 50/125 µm (core/cladding) diameter, multimode fiber optic, with effective modal bandwidth of 2000 MHz/km as detailed in TIA-492AAAC for distances of up to 300 m
<b>Notes</b>	<b>Maximum distance:</b> 10Gbps Transfer Rate (Ethernet): 300m Cable Specs: Tight buffered duplex fiber optic multimode OM3 50/125 µm fiber optic cable and Ethernet assembly with LC duplex connectors on one end and LC duplex connectors on other end.
	<ul style="list-style-type: none"> <li>● Dimensions: Core diameter: 50 ± 3.0µm Cladding diameter: 125 ± 2.0µm Coating diameter: 245 ± 10µm</li> <li>● Optical glass: Bandwidth: For LED sources: 1500/500 MHz-km @850/1300nm.</li> <li>● Optical glass: Bandwidth: For Laser sources: 2000/500 MHz-km @850/1300nm. VCSEL Laser sources: 600 / 600 meters @850/1300nm for Gigabit Ethernet compliant links.</li> <li>● CABLE: The cable is duplex zipcord graded index 50/125µm multimode</li> </ul>

### Accessory Product Details

optical fiber and designed to work in both the 850 and 1300 nm wavelength windows.

- BULK CABLE & CABLE ASSEMBLY CONFIGURATION:
- Jacket Material: Riser Grade - Low Smoke Zero Halogen thermoplastic.
- Jacket Color: Aqua for OM3 multimode per TIA 598
- Boot Color: White
- Insertion Loss: less than 0.5 dB @ 850 with LED source, 0.003 dB/M added for lengths > 30 meters.
- Maximum Cable attenuation: 3.0 dB/km @ 850 nm, 1.0 dB/Km @ 1310 nm @ 23°C as tested in accordance with EIA 455-46.
- Weight: Air Packed Weight: 1 LB Net Weight: 0.454Kg

#### Services

Refer to the HP website at [www.hp.com/networking/services](http://www.hp.com/networking/services) for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

#### HP Premier Flex LC/LC Multi-mode OM4 2 fiber 1m Cable (QK732A)

#### Notes

Cable Specs: Graded-index, "bendable" fiber optic multimode OM3+ 50/125um duplex cable and Ethernet assembly with LC duplex connectors on each end.

- Core Diameter: 50um ±3um, Cladding diameter: 125um ±2um; Coating diameter: 245 ± 10um
- Bandwidth: 3000 MHz-km @ 850nm (Laser)
- Jacket Color: Blue
- Jacket Material: Riser Grade – Low Smoke Zero Halogen (LSZH) thermoplastic
- Boot Color: White
- Outer Jacket Print: HP PremierFlex OM3+ Fiber Optic Cable, 50/125um, Type OFNR (UL), LSZH, cUL, OFN FT4, ROHS. Cable also has a longitudinal white stripe that runs the entire length of the cable.
- Insertion Loss: Less than 0.5dB @ 850nm with LED source, 0.003dB/m added for lengths >30m
- Maximum Cable Attenuation: 3.0 dB/km @ 850nm, 1.0 dB/km @ 1310nm @ 23°C as tested in accordance with EIA 455-45

#### Services

Refer to the HP website at [www.hp.com/networking/services](http://www.hp.com/networking/services) for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

### Accessory Product Details

**HP Premier Flex LC/LC  
Multi-mode OM4 2 fiber  
2m Cable (QK733A)**

**Notes**

Cable Specs: Graded-index, "bendable" fiber optic multimode OM3+ 50/125um duplex cable and Ethernet assembly with LC duplex connectors on each end.

- Core diameter: 50um  $\pm$ 3um, Cladding diameter: 125um  $\pm$ 2um; Coating diameter: 245  $\pm$  10um
- Bandwidth: 3000 MHz-km @ 850nm (Laser)
- Jacket Color: Blue
- Jacket Material: Riser Grade – Low Smoke Zero Halogen (LSZH) thermoplastic
- Boot Color: White
- Outer Jacket Print: HP PremierFlex OM3+ Fiber Optic Cable, 50/125um, Type OFNR (UL), LSZH, cUL, OFN FT4, ROHS. Cable also has a longitudinal white stripe that runs the entire length of the cable.
- Insertion Loss: Less than 0.5dB @ 850nm with LED source, 0.003dB/m added for lengths >30m
- Maximum Cable Attenuation: 3.0 dB/km @ 850nm, 1.0 dB/km @ 1310nm @ 23°C as tested in accordance with EIA 455-45

**Services**

Refer to the HP website at [www.hp.com/networking/services](http://www.hp.com/networking/services) for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

**HP Premier Flex LC/LC  
Multi-mode OM4 2 fiber  
5m Cable (QK734A)**

**Notes**

Cable Specs: Graded-index, "bendable" fiber optic multimode OM3+ 50/125um duplex cable and Ethernet assembly with LC duplex connectors on each end.

- Core diameter: 50um  $\pm$ 3um, Cladding diameter: 125um  $\pm$ 2um; Coating diameter: 245  $\pm$  10um
- Bandwidth: 3000 MHz-km @ 850nm (Laser)
- Jacket Color: Blue
- Jacket Material: Riser Grade – Low Smoke Zero Halogen (LSZH) thermoplastic
- Boot Color: White
- Outer Jacket Print: HP PremierFlex OM3+ Fiber Optic Cable, 50/125um, Type OFNR (UL), LSZH, cUL, OFN FT4, ROHS. Cable also has a longitudinal white stripe that runs the entire length of the cable.
- Insertion Loss: Less than 0.5dB @ 850nm with LED source, 0.003dB/m added for lengths >30m
- Maximum Cable Attenuation: 3.0 dB/km @ 850nm, 1.0 dB/km @ 1310nm @ 23°C as tested in accordance with EIA 455-45

**Services**

Refer to the HP website at [www.hp.com/networking/services](http://www.hp.com/networking/services) for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

### Accessory Product Details

**HP Premier Flex LC/LC  
Multi-mode OM4 2 fiber  
15m Cable (QK735A)**

**Notes**

Cable Specs: Graded-index, "bendable" fiber optic multimode OM3+ 50/125um duplex cable and Ethernet assembly with LC duplex connectors on each end.

- Core diameter: 50um  $\pm$ 3um, Cladding diameter: 125um  $\pm$ 2um; Coating diameter: 245  $\pm$  10um
- Bandwidth: 3000 MHz-km @ 850nm (Laser)
- Jacket Color: Blue
- Jacket Material: Riser Grade – Low Smoke Zero Halogen (LSZH) thermoplastic
- Boot Color: White
- Outer Jacket Print: HP PremierFlex OM3+ Fiber Optic Cable, 50/125um, Type OFNR (UL), LSZH, cUL, OFN FT4, ROHS. Cable also has a longitudinal white stripe that runs the entire length of the cable.
- Insertion Loss: Less than 0.5dB @ 850nm with LED source, 0.003dB/m added for lengths >30m
- Maximum Cable Attenuation: 3.0 dB/km @ 850nm, 1.0 dB/km @ 1310nm @ 23°C as tested in accordance with EIA 455-45

**Services**

Refer to the HP website at [www.hp.com/networking/services](http://www.hp.com/networking/services) for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

**HP Premier Flex LC/LC  
Multi-mode OM4 2 fiber  
30m Cable (QK736A)**

**Notes**

Cable Specs: Graded-index, "bendable" fiber optic multimode OM3+ 50/125um duplex cable and Ethernet assembly with LC duplex connectors on each end.

- Core diameter: 50um  $\pm$ 3um, Cladding diameter: 125um  $\pm$ 2um; Coating diameter: 245  $\pm$  10um
- Bandwidth: 3000 MHz-km @ 850nm (Laser)
- Jacket Color: Blue
- Jacket Material: Riser Grade – Low Smoke Zero Halogen (LSZH) thermoplastic
- Boot Color: White
- Outer Jacket Print: HP PremierFlex OM3+ Fiber Optic Cable, 50/125um, Type OFNR (UL), LSZH, cUL, OFN FT4, ROHS. Cable also has a longitudinal white stripe that runs the entire length of the cable.
- Insertion Loss: Less than 0.5dB @ 850nm with LED source, 0.003dB/m added for lengths >30m
- Maximum Cable Attenuation: 3.0 dB/km @ 850nm, 1.0 dB/km @ 1310nm @ 23°C as tested in accordance with EIA 455-45

**Services**

Refer to the HP website at [www.hp.com/networking/services](http://www.hp.com/networking/services) for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

### Accessory Product Details

**HP Premier Flex LC/LC  
Multi-mode OM4 2 fiber  
50m Cable (QK737A)**

#### Notes

Cable Specs: Graded-index, "bendable" fiber optic multimode OM3+ 50/125um duplex cable and Ethernet assembly with LC duplex connectors on each end.

- Core diameter: 50um  $\pm$ 3um, Cladding diameter: 125um  $\pm$ 2um; Coating diameter: 245  $\pm$  10um
- Bandwidth: 3000 MHz-km @ 850nm (Laser)
- Jacket Color: Blue
- Jacket Material: Riser Grade – Low Smoke Zero Halogen (LSZH) thermoplastic
- Boot Color: White
- Outer Jacket Print: HP PremierFlex OM3+ Fiber Optic Cable, 50/125um, Type OFNR (UL), LSZH, cUL, OFN FT4, ROHS. Cable also has a longitudinal white stripe that runs the entire length of the cable.
- Insertion Loss: Less than 0.5dB @ 850nm with LED source, 0.003dB/m added for lengths >30m
- Maximum Cable Attenuation: 3.0 dB/km @ 850nm, 1.0 dB/km @ 1310nm @ 23°C as tested in accordance with EIA 455-45

#### Services

Refer to the HP website at [www.hp.com/networking/services](http://www.hp.com/networking/services) for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

---

To learn more, visit [www.hp.com/networking](http://www.hp.com/networking)

© Copyright 2013 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.