

### Overview

#### Models

|                                   |        |
|-----------------------------------|--------|
| HP 5120-48G SI Switch             | JE072A |
| HP 5120-24G SI Switch             | JE074A |
| HP 5120-16G SI Switch             | JE073A |
| HP 5120-24G-PoE+ (370W) SI Switch | JG091A |
| HP 5120-24G-PoE+ (170W) SI Switch | JG092A |

#### Key features

- Full wire-speed, multi-layer switching
- High reliability with redundancy
- Comprehensive security control policies
- Diversified Quality of Service (QoS) policies
- Excellent manageability

#### Product overview

The HP 5120 SI Switch Series comprises intelligent, fully managed Gigabit Ethernet switches that provide high performance, high port density, and simplified installation to improve the value of your network infrastructure investment. The 5120 SI series is enhanced for the access layer in enterprise networks that require Gigabit Ethernet to the desktop or at the distribution layer in metropolitan area networks (MANs). Wire-speed forwarding delivers more effective throughput and the bandwidth necessary for mission-critical data and high-speed communications. As part of their comprehensive security control, 5120 SI switches employ 802.1X authentication to identify users who attempt to access the network. These switches are highly reliable, providing redundancy while eliminating loops in the network. They also offer a range of management protocols to simplify network administration.

#### Features and benefits

##### Quality of Service (QoS)

- **Broadcast control:** allows limitation of broadcast traffic rate to cut down on unwanted network broadcast traffic
- **Powerful QoS feature:** supports the following congestion actions: strict priority (SP) queuing, SDWRR, and SP+SDWRR
- **Advanced classifier-based QoS:** classifies traffic using multiple match criteria based on Layer 2, 3, and 4 information; applies QoS policies such as setting priority level and rate limit to selected traffic on a per-port basis

##### Management

- **Friendly port names:** allow assignment of descriptive names to ports
- **Remote configuration and management:** is available through a secure Web browser or a command-line interface (CLI)
- **Manager and operator privilege levels:** enable read-only (operator) and read/write (manager) access on CLI and Web browser management interfaces
- **Command authorization:** leverages RADIUS to link a custom list of CLI commands to an individual network administrator's login; also provides an audit trail
- **Secure Web GUI:** provides a secure, easy-to-use graphical interface for configuring the module via HTTPS
- **Dual flash images:** provide independent primary and secondary operating system files for backup while upgrading
- **Multiple configuration files:** can be stored to the flash image
- **Complete session logging:** provides detailed information for problem identification and resolution

### Overview

- **SNMPv1, v2c, and v3:** facilitate centralized discovery, monitoring, and secure management of networking devices
- **Remote monitoring (RMON):** uses standard SNMP to monitor essential network functions; supports events, alarm, history, and statistics group plus a private alarm extension group
- **IEEE 802.1AB Link Layer Discovery Protocol (LLDP):** automated device discovery protocol provides easy mapping by network management applications
- **Management VLAN:** segments traffic to and from management interfaces, including CLI/telnet, a Web browser interface, and SNMP
- **Device Link Detection Protocol (DLDP):** monitors a cable between two switches and shuts down the ports on both ends if the cable is broken, this prevents network problems such as loops

### Connectivity

- **Auto-MDIX:** automatically adjusts for straight-through or crossover cables on all 10/100/1000 ports
- **Flow control:** using standard IEEE 802.3x, it provides back pressure to reduce congestion in heavy traffic situations
- **Jumbo packet support:** supports up to 10k byte frame size to improve performance of large data transfers
- **High-density port connectivity:** provides up to 48 fixed 10/100/1000BASE-T ports in an entry-level static Layer 3 switch
- **Ethernet OAM:** provides a Layer 2 link performance and fault detection monitoring tool, which reduces failover and network convergence times
- **Power over Ethernet Plus (PoE+) support:** provides 30 W power for connected devices, simplifies deployment, and dramatically reduces installation costs by helping to eliminate the time and cost involved in supplying local power at each access point location
- **IPv6:**
  - IPv6 Host: enables switches to be managed and deployed at the IPv6 network's edge
  - Dual stack (IPv4 and IPv6 using BIS): allows IPv4 hosts to communicate with IPv6 hosts
  - IPv6 ACL: for filtering IPv6 network traffic

### Performance

- **Nonblocking architecture:** up to 104 Gbps nonblocking switching fabric provides wire-speed switching with up to 77.4 million pps throughput
- **Hardware-based wire-speed access control lists (ACLs):** feature-rich ACL implementation (TCAM-based) helps ensure high levels of security and ease of administration without impacting network performance

### Resiliency and high availability

- **Separate data and control paths:** increases security and performance
- **Spanning Tree/MSTP, RSTP:** provides redundant links while preventing network loops
- **IEEE 802.3ad Link Aggregation Control Protocol (LACP):** supports up to 26 trunks, each with 8 links per trunk; supports static or dynamic groups
- **Smart link:** allows 50 ms failover between links
- **Intelligent Resilient Framework (IRF):** creates virtual resilient switching fabrics, where two or more switches perform as a single Layer 2 switch and Layer 3 router; switches do not have to be co-located and can be part of a disaster-recovery system; servers or switches can be attached using standard LACP for automatic load balancing and high availability; simplifies network operation by eliminating the complexity of Spanning Tree Protocol, Equal-Cost Multipath (ECMP), or VRRP

### Layer 2 switching

- **8K MAC address table:** provides access to many Layer 2 devices
- **VLAN support and tagging:** support IEEE 802.1Q with 4,094 simultaneous VLAN IDs
- **IP multicast snooping:** automatically prevents flooding of IP multicast traffic

### Overview

- **Internet Group Management Protocol (IGMP) and Multicast Listener Discovery (MLD) protocol snooping:** effectively control and manage the flooding of multicast packets in a Layer 2 network

### Layer 3 services

- **Address Resolution Protocol (ARP):** determines the MAC address of another IP host in the same subnet; supports static ARPs; gratuitous ARP allows detection of duplicate IP addresses
- **Dynamic Host Configuration Protocol (DHCP):** simplifies the management of large IP networks; supports client; DHCP Relay enables DHCP operation across subnets
- **Loopback interface address:** defines an address in Routing Information Protocol (RIP) and OSPF that can always be reachable, improving diagnostic capability

### Layer 3 routing

- **Static IP routing:** provides manually configured routing for both IPv4 and IPv6 networks

### Security

- **Access control lists (ACLs):** provides IP Layer 2 to Layer 4 traffic filtering; supports global ACL, VLAN ACL, port ACL, and IPv6 ACL
- **Identity-driven security and access control:**
  - Per-user ACLs: permits or denies user access to specific network resources based on user identity and time of day, allowing multiple types of users on the same network to access specific network services without risk to network security or unauthorized access to sensitive data
  - Automatic VLAN assignment: automatically assigns users to the appropriate VLAN based on their identities
- **Secure management access:** securely encrypts all access methods (CLI, GUI, or MIB) through SSHv2, SSL, and/or SNMPv3
- **Secure FTP:** allows secure file transfer to and from the switch; protects against unwanted file downloads or unauthorized copying of a switch configuration file
- **Guest VLAN:** similar to IEEE 802.1X, it provides a browser-based environment to authenticated clients
- **Port isolation:** secures and adds privacy, and prevents malicious attackers from obtaining user information
- **STP BPDU port protection:** blocks Bridge Protocol Data Units (BPDUs) on ports that do not require BPDUs, preventing forged BPDU attacks
- **STP Root Guard:** protects the root bridge from malicious attacks or configuration mistakes
- **DHCP protection:** blocks DHCP packets from unauthorized DHCP servers, preventing denial-of-service attacks
- **Dynamic ARP protection:** blocks ARP broadcasts from unauthorized hosts, preventing eavesdropping or theft of network data
- **IP Source Guard:** helps prevent IP spoofing attacks
- **Endpoint Admission Defense (EAD):** provides security policies to users accessing a network
- **RADIUS/HWTACACS:** eases switch management security administration by using a password authentication server
- **Port security:** allows access only to specified MAC addresses, which can be learned or specified by the administrator
- **MAC-based authentication:** allows or denies access to the switch based on a client MAC address

### Convergence

- **IEEE 802.1AB Link Layer Discovery Protocol (LLDP):** is an automated device discovery protocol that provides easy mapping of network management applications
- **LLDP-MED:** is a standard extension that automatically configures network devices, including LLDP-capable IP phones
- **LLDP-CDP compatibility:** receives and recognizes CDP packets from Cisco's IP phones for seamless interoperation
- **Voice VLAN:** automatically assigns VLAN and priority for IP phones, simplifying network configuration and maintenance
- **IP multicast snooping (data-driven IGMP):** automatically prevents flooding of IP multicast traffic
- **Multicast VLAN:** reduces network bandwidth demand by eliminating multiple streams to each VLAN

### Overview

#### Additional information

- **Green IT and power:** use the latest advances in silicon development, shut off unused ports, and use variable-speed fans to improve energy efficiency
- **Green initiative support:** provides support for RoHS and WEEE regulations

#### Warranty and support

- **Lifetime warranty:** for as long as you own the product with advance replacement and next-business-day delivery (available in most countries)†
- **Electronic and telephone support:** limited electronic and telephone support is available from HP; to reach our support centers, refer to: [www.hp.com/networking/contact-support](http://www.hp.com/networking/contact-support); for details on the duration of support provided with your product purchase, refer to: [www.hp.com/networking/warrantysummary](http://www.hp.com/networking/warrantysummary)
- **Software releases:** to find software for your product, refer to: [www.hp.com/networking/support](http://www.hp.com/networking/support); for details on the software releases available with your product purchase, refer to [www.hp.com/networking/warrantysummary](http://www.hp.com/networking/warrantysummary)

† HP warranty includes repair or replacement of hardware for as long as you own the product, with next business day advance replacement (available in most countries). The disk drive included with HP AllianceOne Advanced Services and Services z1 Modules, HP Threat Management Services z1 Module, HP AllianceOne Extended z1 Module with Riverbed Steelhead, HP MSM765z1 Mobility Controller and HP Survivable Branch Communication z1 Module powered by Microsoft Lync has a five-year hardware warranty. For details, refer to the Software license and hardware warranty statements at: [www.hp.com/networking/warranty](http://www.hp.com/networking/warranty).

### Configuration

#### Build To Order:

**BTO is a standalone unit with no integration. BTO products ship standalone are not part of a CTO or Rack-Shippable solution.**

##### HP 5120-16G SI Switch

- 16 RJ-45 autosensing 10/100/1000 ports
- 4 fixed Gigabit Ethernet SFP ports
- min=0 \ max=4 SFP Transceivers
- 1U - Height

JE073A  
See Configuration  
Note:1, 2

##### HP 5120-24G SI Switch

- 24 RJ-45 autosensing 10/100/1000 ports
- 4 fixed Gigabit Ethernet SFP ports
- min=0 \ max=4 SFP Transceivers
- 1U - Height

JE074A  
See Configuration  
Note:1, 2

##### HP 5120-24G-HPoE SI Switch

- 24 RJ-45 autosensing 10/100/1000 ports
- 4 fixed Gigabit Ethernet SFP ports
- min=0 \ max=4 SFP Transceivers
- 1U - Height

JG091A  
See Configuration  
Note:1, 2

##### HP 5120-24G-PoE SI Switch

- 24 RJ-45 autosensing 10/100/1000 ports
- 4 fixed Gigabit Ethernet SFP ports
- min=0 \ max=4 SFP Transceivers
- 1U - Height

JG092A  
See Configuration  
Note:1, 2

##### HP 5120-48G SI Switch

- 48 RJ-45 autosensing 10/100/1000 ports
- 4 fixed Gigabit Ethernet SFP ports
- min=0 \ max=4 SFP Transceivers
- 1U - Height

JE072A  
See Configuration  
Note:1, 2

#### Configuration Rules:

Note 1 The following Transceivers install into this Module:

|   |        |
|---|--------|
| HP X125 1G SFP LC LH40 1310nm Transceiver | JD061A |
| HP X120 1G SFP LC LH40 1550nm Transceiver | JD062A |
| HP X120 1G SFP LC SX Transceiver          | JD118B |
| HP X120 1G SFP LC LX Transceiver          | JD119B |
| HP X125 1G SFP LC LH70 Transceiver        | JD063B |
| HP X120 1G SFP LC BX 10-U Transceiver     | JD098B |
| HP X120 1G SFP LC BX 10-D Transceiver     | JD099B |
| HP X120 1G SFP RJ45 T Transceiver         | JD089B |

Note 2 Localization required. (See Localization Menu for list.)

### Configuration

## Transceivers

### SFP Transceivers

|                                       |        |
|---------------------------------------|--------|
| HP X120 1G SFP LC SX Transceiver      | JD118B |
| HP X120 1G SFP LC LX Transceiver      | JD119B |
| HP X125 1G SFP LC LH40 1310nm XCVR    | JD061A |
| HP X120 1G SFP LC LH40 1550nm XCVR    | JD062A |
| HP X125 1G SFP LC LH70 Transceiver    | JD063B |
| HP X120 1G SFP LC BX 10-U Transceiver | JD098B |
| HP X120 1G SFP LC BX 10-D Transceiver | JD099B |
| HP X120 1G SFP RJ45 T Transceiver     | JD089B |

## Cables

### Multi-Mode Cables

|                                      |        |
|--------------------------------------|--------|
| HP .5m Multi-mode OM3 LC/LC FC Cable | AJ833A |
| HP 1m Multi-mode OM3 LC/LC FC Cable  | AJ834A |
| HP 2 m Multimode OM3 LC/LC FC Cable  | AJ835A |
| HP 5 m Multimode OM3 LC/LC FC Cable  | AJ836A |
| HP 15 m Multimode OM3 LC/LC FC Cable | AJ837A |
| HP 30 m Multimode OM3 LC/LC FC Cable | AJ838A |
| HP 50 m Multimode OM3 LC/LC FC Cable | AJ839A |
| HP Premier Flex LC/LC OM4 2f 1m Cbl  | QK732A |
| HP Premier Flex LC/LC OM4 2f 2m Cbl  | QK733A |
| HP Premier Flex LC/LC OM4 2f 5m Cbl  | QK734A |
| HP Premier Flex LC/LC OM4 2f 15m Cbl | QK735A |
| HP Premier Flex LC/LC OM4 2f 30m Cbl | QK736A |
| HP Premier Flex LC/LC OM4 2f 50m Cbl | QK737A |

## Switch Enclosure Options

### External/Redundant Power Supplies

|   |                             |
|---|-----------------------------|
| HP RPS1600 Redundant Power System   | JG136A                      |
| <ul style="list-style-type: none"><li>• Height = 1U</li><li>• includes 1 x c13, 1600w and Power Supply port</li></ul> | See Configuration Note:2, 3 |
| HP RPS1600 1600W AC Power Supply  | JG137A                      |
| <ul style="list-style-type: none"><li>• Installs into JG136A only</li></ul>   | See Configuration Note:1    |

### Configuration

#### Configuration Rules:

- Note 1            If this power supply is selected, The JG136A - HP A-RPS1600 Redundant Power System must be on ordered or onsite.
- Note 2            Localization required. (See Localization Menu for list.)
- Note 3            Only 1 JG136A can be connected per switch.

#### Options for External/Redundant Power Supplies

HP X290 1000 A JD5 2m RPS Cable

JD187A

### Technical Specifications

#### HP 5120-48G SI Switch (JE072A)

|                                   |   |
|-----------------------------------|---|
| <b>Ports</b>                      | 48 RJ-45 autosensing 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only<br>4 fixed Gigabit Ethernet SFP ports<br>1 RJ-45 serial console port   |
| <b>Physical characteristics</b>   | <b>Dimensions</b> 10.24(d) x 17.3(w) x 1.72(h) in. (26.01 x 43.94 x 4.37 cm) (1U height)<br><b>Weight</b> 11.02 lb. (5 kg)  |
| <b>Memory and processor</b>       | 128 MB flash, 128 MB SDRAM; packet buffer size: 1 MB  |
| <b>Mounting</b>                   | Mounts in an EIA-standard 19 in. telco rack or equipment cabinet (hardware included)  |
| <b>Performance</b>                | <b>1000 Mb Latency</b> < 3 $\mu$ s<br><b>Throughput</b> 77.4 million pps<br><b>Routing/Switching capacity</b> 104 Gbps<br><b>Routing table size</b> 32 entries  |
| <b>Environment</b>                | <b>Operating temperature</b> 32°F to 113°F (0°C to 45°C)<br><b>Operating relative humidity</b> 10% to 90%, noncondensing<br><b>Nonoperating/Storage temperature</b> -40°F to 158°F (-40°C to 70°C)<br><b>Nonoperating/Storage relative humidity</b> 5% to 95%, noncondensing  |
| <b>Electrical characteristics</b> | <b>Maximum heat dissipation</b> 189 BTU/hr (199.4 kJ/hr)<br><b>Voltage</b> 100-240 VAC<br><b>Maximum power rating</b> 55.4 W<br><b>Frequency</b> 50/60 Hz<br><b>Notes</b> Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated. |
| <b>Safety</b>                     | UL 60950-1; EN 60825-1 Safety of Laser Products-Part 1; EN 60825-2 Safety of Laser Products-Part 2; IEC 60950-1; CAN/CSA-C22.2 No. 60950-1; Anatel; ULAR; GOST; EN 60950-1/A11; FDA 21 CFR Subchapter J; NOM; ROHS Compliance   |
| <b>Emissions</b>                  | FCC part 15 Class A; VCCI Class A; EN 55022 Class A; CISPR 22 Class A; ICES-003 Class A; ANSI C63.4 2003; ETSI EN 300 386 V1.3.3; AS/NZS CISPR22 Class A; EN 61000-3-2; EN 61000-3-3; EN 61000-4-2; EN 61000-4-3; EN 61000-4-4; EN 61000-4-5; EN 61000-4-6; EN 61000-4-11; EN 61000-3-2:2006; EN 61000-3-3:1995 +A1:2001 +A2:2005; EMC Directive 2004/108/EC; FCC (CFR 47, Part 15) Class A                             |
| <b>Management</b>                 | IMC - Intelligent Management Center; command-line interface; Web browser; SNMP Manager  |
| <b>Services</b>                   | 3-year, 4-hour onsite, 13x5 coverage for hardware (UV858E)<br>3-year, 4-hour onsite, 24x7 coverage for hardware (UV861E)<br>3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (UV864E)<br>3-year, 24x7 SW phone support, software updates (UV867E)<br>1-year, post-warranty, 4-hour onsite, 13x5 coverage for hardware (HR584E)  |

### Technical Specifications

- 1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware (HR585E)
- 1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (HR586E)
- Installation with minimum configuration, system-based pricing (UX116E)
- Installation with HP-provided configuration, system-based pricing (UX117E)
- 4-year, 4-hour onsite, 13x5 coverage for hardware (UV859E)
- 4-year, 4-hour onsite, 24x7 coverage for hardware (UV862E)
- 4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UV865E)
- 4-year, 24x7 SW phone support, software updates (UV868E)
- 5-year, 4-hour onsite, 13x5 coverage for hardware (UV860E)
- 5-year, 4-hour onsite, 24x7 coverage for hardware (UV863E)
- 5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UV866E)
- 5-year, 24x7 SW phone support, software updates (UV869E)
- 3 Yr 6 hr Call-to-Repair Onsite (UW963E)
- 4 Yr 6 hr Call-to-Repair Onsite (UW964E)
- 5 Yr 6 hr Call-to-Repair Onsite (UW965E)
- 1-year, 6 hour Call-To-Repair Onsite for hardware (HR588E)
- 1-year, 24x7 software phone support, software updates (HR587E)
- 1-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS682E)
- 1-year, 24x7 software phone support, software updates + 4 hour hardware exchange (HS683E)
- 4-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS686E)
- 4-year, 24x7 software phone support, software updates + 4 hour Hardware Exchange (HS687E)
- 5-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS688E)

Refer to the HP website at: [www.hp.com/networking/services](http://www.hp.com/networking/services) for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

#### HP 5120-24G SI Switch (JE074A)

|                                 |  |   |
|---------------------------------|--|---|
| <b>Ports</b>                    | 24 RJ-45 autosensing 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only |   |
|                                 | 4 fixed Gigabit Ethernet SFP ports   |   |
|                                 | 1 RJ-45 serial console port  |   |
| <b>Physical characteristics</b> | <b>Dimensions</b>  | 6.3(d) x 17.3(w) x 1.72(h) in. (16 x 43.94 x 4.37 cm) (1U height) |
|                                 | <b>Weight</b>  | 6.61 lb. (3 kg)   |
| <b>Memory and processor</b>     | 128 MB flash, 128 MB SDRAM; packet buffer size: 0.5 MB   |   |
| <b>Mounting</b>                 | Mounts in an EIA-standard 19 in. telco rack or equipment cabinet (hardware included)   |   |
| <b>Performance</b>              | <b>1000 Mb Latency</b>   | < 3 $\mu$ s   |
|                                 | <b>Throughput</b>  | 41.7 million pps  |
|                                 | <b>Routing/Switching capacity</b>  | 56 Gbps   |
|                                 | <b>Routing table size</b>  | 32 entries  |
| <b>Environment</b>              | <b>Operating temperature</b>   | 32°F to 113°F (0°C to 45°C)                                       |

### Technical Specifications

|                                   |   |   |
|-----------------------------------|---|---|
|                                   | <b>Operating relative humidity</b>  | 10% to 90%, noncondensing   |
|                                   | <b>Nonoperating/Storage temperature</b>   | -40°F to 158°F (-40°C to 70°C)  |
|                                   | <b>Nonoperating/Storage relative humidity</b>   | 5% to 95%, noncondensing  |
| <b>Electrical characteristics</b> | <b>Maximum heat dissipation</b>   | 108 BTU/hr (113.94 kJ/hr)   |
|                                   | <b>Voltage</b>  | 100-240 VAC   |
|                                   | <b>Maximum power rating</b>   | 31.5 W  |
|                                   | <b>Frequency</b>  | 50/60 Hz  |
|                                   | <b>Notes</b>  | Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated. |
| <b>Safety</b>                     | UL 60950-1; EN 60825-1 Safety of Laser Products-Part 1; EN 60825-2 Safety of Laser Products-Part 2; IEC 60950-1; CAN/CSA-C22.2 No. 60950-1; Anatel; ULAR; GOST; EN 60950-1/A11; FDA 21 CFR Subchapter J; NOM; ROHS Compliance   |   |
| <b>Emissions</b>                  | FCC part 15 Class A; VCCI Class A; EN 55022 Class A; CISPR 22 Class A; ICES-003 Class A; ANSI C63.4 2003; ETSI EN 300 386 V1.3.3; AS/NZS CISPR22 Class A; EN 61000-3-2; EN 61000-3-3; EN 61000-4-2; EN 61000-4-3; EN 61000-4-4; EN 61000-4-5; EN 61000-4-6; EN 61000-4-11; EN 61000-3-2:2006; EN 61000-3-3:1995 +A1:2001 +A2:2005; EMC Directive 2004/108/EC; FCC (CFR 47, Part 15) Class A |   |
| <b>Management Services</b>        | IMC - Intelligent Management Center; command-line interface; Web browser; SNMP Manager  |   |
|                                   | 3-year, 4-hour onsite, 13x5 coverage for hardware (UV858E)  |   |
|                                   | 3-year, 4-hour onsite, 24x7 coverage for hardware (UV861E)  |   |
|                                   | 3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (UV864E)   |   |
|                                   | 3-year, 24x7 SW phone support, software updates (UV867E)  |   |
|                                   | 1-year, post-warranty, 4-hour onsite, 13x5 coverage for hardware (HR584E)   |   |
|                                   | 1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware (HR585E)   |   |
|                                   | 1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (HR586E)  |   |
|                                   | Installation with minimum configuration, system-based pricing (UX116E)  |   |
|                                   | Installation with HP-provided configuration, system-based pricing (UX117E)  |   |
|                                   | 4-year, 4-hour onsite, 13x5 coverage for hardware (UV859E)  |   |
|                                   | 4-year, 4-hour onsite, 24x7 coverage for hardware (UV862E)  |   |
|                                   | 4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UV865E)   |   |
|                                   | 4-year, 24x7 SW phone support, software updates (UV868E)  |   |
|                                   | 5-year, 4-hour onsite, 13x5 coverage for hardware (UV860E)  |   |
|                                   | 5-year, 4-hour onsite, 24x7 coverage for hardware (UV863E)  |   |
|                                   | 5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UV866E)   |   |
|                                   | 5-year, 24x7 SW phone support, software updates (UV869E)  |   |
|                                   | 3 Yr 6 hr Call-to-Repair Onsite (UW963E)  |   |
|                                   | 4 Yr 6 hr Call-to-Repair Onsite (UW964E)  |   |
|                                   | 5 Yr 6 hr Call-to-Repair Onsite (UW965E)  |   |
|                                   | 1-year, 6 hour Call-To-Repair Onsite for hardware (HR588E)  |   |
|                                   | 1-year, 24x7 software phone support, software updates (HR587E)  |   |
|                                   | 1-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange   |   |

### Technical Specifications

(HS682E)  
 1-year, 24x7 software phone support, software updates + 4 hour hardware exchange (HS683E)  
 4-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS686E)  
 4-year, 24x7 software phone support, software updates + 4 hour Hardware Exchange (HS687E)  
 5-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS688E)

Refer to the HP website at: [www.hp.com/networking/services](http://www.hp.com/networking/services) for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

#### HP 5120-16G SI Switch (JE073A)

|                                   |  |   |
|-----------------------------------|--|---|
| <b>Ports</b>                      | 16 RJ-45 autosensing 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only |   |
|                                   | 4 fixed Gigabit Ethernet SFP ports   |   |
|                                   | 1 RJ-45 serial console port  |   |
| <b>Physical characteristics</b>   | <b>Dimensions</b>  | 6.3(d) x 17.3(w) x 1.72(h) in. (16 x 43.94 x 4.37 cm) (1U height)   |
|                                   | <b>Weight</b>  | 6.61 lb. (3 kg)   |
| <b>Memory and processor</b>       | 128 MB flash, 128 MB SDRAM; packet buffer size: 0.5 MB   |   |
| <b>Mounting</b>                   | Mounts in an EIA-standard 19 in. telco rack or equipment cabinet (hardware included)   |   |
| <b>Performance</b>                | <b>1000 Mb Latency</b>   | < 3 $\mu$ s   |
|                                   | <b>Throughput</b>  | 29.8 million pps  |
|                                   | <b>Routing/Switching capacity</b>  | 40 Gbps   |
|                                   | <b>Routing table size</b>  | 32 entries  |
| <b>Environment</b>                | <b>Operating temperature</b>   | 32°F to 113°F (0°C to 45°C)   |
|                                   | <b>Operating relative humidity</b>   | 10% to 90%, noncondensing   |
|                                   | <b>Nonoperating/Storage temperature</b>  | -40°F to 158°F (-40°C to 70°C)  |
|                                   | <b>Nonoperating/Storage relative humidity</b>  | 5% to 95%, noncondensing  |
| <b>Electrical characteristics</b> | <b>Maximum heat dissipation</b>  | 76 BTU/hr (80.18 kJ/hr)   |
|                                   | <b>Voltage</b>   | 100-240 VAC   |
|                                   | <b>Maximum power rating</b>  | 22.4 W  |
|                                   | <b>Frequency</b>   | 50/60 Hz  |
|                                   | <b>Notes</b>   | Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated. |

### Technical Specifications

|                   |   |
|-------------------|---|
| <b>Safety</b>     | UL 60950-1; EN 60825-1 Safety of Laser Products-Part 1; EN 60825-2 Safety of Laser Products-Part 2; IEC 60950-1; CAN/CSA-C22.2 No. 60950-1; Anatel; ULAR; GOST; EN 60950-1/A11; FDA 21 CFR Subchapter J; NOM; ROHS Compliance   |
| <b>Emissions</b>  | FCC part 15 Class A; VCCI Class A; EN 55022 Class A; CISPR 22 Class A; ICES-003 Class A; ANSI C63.4 2003; ETSI EN 300 386 V1.3.3; AS/NZS CISPR22 Class A; EN 61000-3-2; EN 61000-3-3; EN 61000-4-2; EN 61000-4-3; EN 61000-4-4; EN 61000-4-5; EN 61000-4-6; EN 61000-4-11; EN 61000-3-2:2006; EN 61000-3-3:1995 +A1:2001 +A2:2005; EMC Directive 2004/108/EC; FCC (CFR 47, Part 15) Class A   |
| <b>Management</b> | IMC - Intelligent Management Center; command-line interface; Web browser; SNMP Manager  |
| <b>Services</b>   | 3-year, 4-hour onsite, 13x5 coverage for hardware (UV858E)<br>3-year, 4-hour onsite, 24x7 coverage for hardware (UV861E)<br>3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (UV864E)<br>3-year, 24x7 SW phone support, software updates (UV867E)<br>1-year, post-warranty, 4-hour onsite, 13x5 coverage for hardware (HR584E)<br>1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware (HR585E)<br>1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (HR586E)<br>Installation with minimum configuration, system-based pricing (UX116E)<br>Installation with HP-provided configuration, system-based pricing (UX117E)<br>4-year, 4-hour onsite, 13x5 coverage for hardware (UV859E)<br>4-year, 4-hour onsite, 24x7 coverage for hardware (UV862E)<br>4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UV865E)<br>4-year, 24x7 SW phone support, software updates (UV868E)<br>5-year, 4-hour onsite, 13x5 coverage for hardware (UV860E)<br>5-year, 4-hour onsite, 24x7 coverage for hardware (UV863E)<br>5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UV866E)<br>5-year, 24x7 SW phone support, software updates (UV869E)<br>3 Yr 6 hr Call-to-Repair Onsite (UW963E)<br>4 Yr 6 hr Call-to-Repair Onsite (UW964E)<br>5 Yr 6 hr Call-to-Repair Onsite (UW965E)<br>1-year, 6 hour Call-To-Repair Onsite for hardware (HR588E)<br>1-year, 24x7 software phone support, software updates (HR587E)<br>1-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS682E)<br>1-year, 24x7 software phone support, software updates + 4 hour hardware exchange (HS683E)<br>4-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS686E)<br>4-year, 24x7 software phone support, software updates + 4 hour Hardware Exchange (HS687E)<br>5-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS688E) |

Refer to the HP website at: [www.hp.com/networking/services](http://www.hp.com/networking/services) for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

---

#### HP 5120-24G-PoE+ (370W) SI Switch (JG091A)

### Technical Specifications

|                                   |   |
|-----------------------------------|---|
| <b>Ports</b>                      | 24 RJ-45 autosensing 10/100/1000 PoE+ ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T, IEEE 802.3at PoE+); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only<br>4 fixed Gigabit Ethernet SFP ports<br>1 RJ-45 serial console port   |
| <b>Physical characteristics</b>   | <b>Dimensions</b> 16.54(d) x 17.32(w) x 1.72(h) in. (42 x 44.0 x 4.36 cm) (1U height)<br><b>Weight</b> 15.43 lb. (7 kg)   |
| <b>Memory and processor</b>       | 128 MB flash, 128 MB SDRAM; packet buffer size: 0.5 MB  |
| <b>Mounting</b>                   | Mounts in an EIA-standard 19 in. telco rack or equipment cabinet (hardware included)  |
| <b>Performance</b>                | <b>1000 Mb Latency</b> < 3 $\mu$ s<br><b>Throughput</b> 41.7 million pps<br><b>Routing/Switching capacity</b> 56 Gbps<br><b>Routing table size</b> 32 entries   |
| <b>Environment</b>                | <b>Operating temperature</b> 32°F to 113°F (0°C to 45°C)<br><b>Operating relative humidity</b> 10% to 90%, noncondensing<br><b>Nonoperating/Storage temperature</b> -40°F to 158°F (-40°C to 70°C)<br><b>Nonoperating/Storage relative humidity</b> 5% to 95%, noncondensing  |
| <b>Electrical characteristics</b> | <b>Maximum heat dissipation</b> 539 BTU/hr (568.65 kJ/hr)<br><b>Voltage</b> 100-240 VAC<br><b>DC Voltage</b> -52 to -55 VDC<br><b>Maximum power rating</b> 832 W<br><b>PoE power</b> 720 W<br><b>Frequency</b> 50/60 Hz<br><b>Notes</b> Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.<br>PoE Power is the power supplied by the internal power supply, it is dependent on the type and quantity of power supplies and may be supplemented with the use of a External Power Supply (EPS).<br>With AC input, the Max power consumption is 523W (370W for PoE) |
| <b>Safety</b>                     | UL 60950-1; EN 60825-1 Safety of Laser Products-Part 1; EN 60825-2 Safety of Laser Products-Part 2; IEC 60950-1; CAN/CSA-C22.2 No. 60950-1; Anatel; ULAR; GOST; EN 60950-1/A11; FDA 21 CFR Subchapter J; NOM; ROHS Compliance   |
| <b>Emissions</b>                  | FCC part 15 Class A; VCCI Class A; EN 55022 Class A; CISPR 22 Class A; ICES-003 Class A; ANSI C63.4 2003; ETSI EN 300 386 V1.3.3; AS/NZS CISPR22 Class A; EN 61000-3-2; EN 61000-3-3; EN 61000-4-2; EN 61000-4-3; EN 61000-4-4; EN 61000-4-5; EN 61000-4-6; EN 61000-4-11; EN 61000-3-2:2006; EN 61000-3-3:1995 +A1:2001 +A2:2005; EMC Directive 2004/108/EC; FCC (CFR 47, Part 15) Class A   |

### Technical Specifications

**Management** IMC - Intelligent Management Center; command-line interface; Web browser; SNMP Manager

**Services**

- 3-year, 4-hour onsite, 13x5 coverage for hardware (UV858E)
- 3-year, 4-hour onsite, 24x7 coverage for hardware (UV861E)
- 3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (UV864E)
- 3-year, 24x7 SW phone support, software updates (UV867E)
- 4-year, 4-hour onsite, 13x5 coverage for hardware (UV859E)
- 4-year, 4-hour onsite, 24x7 coverage for hardware (UV862E)
- 4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UV865E)
- 4-year, 24x7 SW phone support, software updates (UV868E)
- 5-year, 4-hour onsite, 13x5 coverage for hardware (UV860E)
- 5-year, 4-hour onsite, 24x7 coverage for hardware (UV863E)
- 5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UV866E)
- 5-year, 24x7 SW phone support, software updates (UV869E)
- 3 Yr 6 hr Call-to-Repair Onsite (UW963E)
- 4 Yr 6 hr Call-to-Repair Onsite (UW964E)
- 5 Yr 6 hr Call-to-Repair Onsite (UW965E)

Refer to the HP website at: [www.hp.com/networking/services](http://www.hp.com/networking/services) for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

#### HP 5120-24G-PoE+ (170W) SI Switch (JG092A)

|                                   |  |   |
|-----------------------------------|--|---|
| <b>Ports</b>                      | 24 RJ-45 autosensing 10/100/1000 PoE+ ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T, IEEE 802.3at PoE+); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only |   |
|                                   | 4 fixed Gigabit Ethernet SFP ports   |   |
|                                   | 1 RJ-45 serial console port  |   |
| <b>Physical characteristics</b>   | <b>Dimensions</b>  | 16.54(d) x 17.32(w) x 1.72(h) in. (42 x 44.0 x 4.36 cm) (1U height) |
|                                   | <b>Weight</b>  | 15.43 lb. (7 kg)  |
| <b>Memory and processor</b>       | 128 MB flash, 128 MB SDRAM; packet buffer size: 0.5 MB   |   |
| <b>Mounting</b>                   | Mounts in an EIA-standard 19 in. telco rack or equipment cabinet (hardware included)   |   |
| <b>Performance</b>                | <b>1000 Mb Latency</b>   | < 3 $\mu$ s   |
|                                   | <b>Throughput</b>  | 41.7 million pps  |
|                                   | <b>Routing/Switching capacity</b>  | 56 Gbps   |
|                                   | <b>Routing table size</b>  | 32 entries  |
| <b>Environment</b>                | <b>Operating temperature</b>   | 32°F to 113°F (0°C to 45°C)   |
|                                   | <b>Operating relative humidity</b>   | 10% to 90%, noncondensing   |
|                                   | <b>Nonoperating/Storage temperature</b>  | -40°F to 158°F (-40°C to 70°C)                                      |
|                                   | <b>Nonoperating/Storage relative humidity</b>  | 5% to 95%, noncondensing  |
| <b>Electrical characteristics</b> | <b>Maximum heat</b>  | 290 BTU/hr (305.95 kJ/hr)   |

### Technical Specifications

#### dissipation

**Voltage** 100-240 VAC

**Maximum power rating** 255 W

**PoE power** 170 W

**Frequency** 50/60 Hz

**Notes** Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.  
PoE Power is the power supplied by the internal power supply, it is dependent on the type and quantity of power supplies and may be supplemented with the use of a External Power Supply (EPS).

**Safety** UL 60950-1; EN 60825-1 Safety of Laser Products-Part 1; EN 60825-2 Safety of Laser Products-Part 2; IEC 60950-1; CAN/CSA-C22.2 No. 60950-1; Anatel; ULAR; GOST; EN 60950-1/A11; FDA 21 CFR Subchapter J; NOM; ROHS Compliance

**Emissions** FCC part 15 Class A; VCCI Class A; EN 55022 Class A; CISPR 22 Class A; ICES-003 Class A; ANSI C63.4 2003; ETSI EN 300 386 V1.3.3; AS/NZS CISPR22 Class A; EN 61000-3-2; EN 61000-3-3; EN 61000-4-2; EN 61000-4-3; EN 61000-4-4; EN 61000-4-5; EN 61000-4-6; EN 61000-4-11; EN 61000-3-2:2006; EN 61000-3-3:1995 +A1:2001 +A2:2005; EMC Directive 2004/108/EC; FCC (CFR 47, Part 15) Class A

**Management** IMC - Intelligent Management Center; command-line interface; Web browser; SNMP Manager

**Services**  
3-year, 4-hour onsite, 13x5 coverage for hardware (UV858E)  
3-year, 4-hour onsite, 24x7 coverage for hardware (UV861E)  
3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (UV864E)  
3-year, 24x7 SW phone support, software updates (UV867E)  
4-year, 4-hour onsite, 13x5 coverage for hardware (UV859E)  
4-year, 4-hour onsite, 24x7 coverage for hardware (UV862E)  
4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UV865E)  
4-year, 24x7 SW phone support, software updates (UV868E)  
5-year, 4-hour onsite, 13x5 coverage for hardware (UV860E)  
5-year, 4-hour onsite, 24x7 coverage for hardware (UV863E)  
5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UV866E)  
5-year, 24x7 SW phone support, software updates (UV869E)  
3 Yr 6 hr Call-to-Repair Onsite (UW963E)  
4 Yr 6 hr Call-to-Repair Onsite (UW964E)  
5 Yr 6 hr Call-to-Repair Onsite (UW965E)

Refer to the HP website at: [www.hp.com/networking/services](http://www.hp.com/networking/services) for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

**Standards and protocols**  
(applies to all products in series)

#### General protocols

IEEE 802.1D MAC Bridges  
IEEE 802.1p Priority  
IEEE 802.1Q VLANs  
IEEE 802.1s Multiple Spanning Trees  
IEEE 802.1w Rapid Reconfiguration of Spanning Tree  
IEEE 802.1X PAE  
IEEE 802.3ad Link Aggregation Control Protocol

RFC 3513 IPv6 Addressing Architecture  
RFC 3542 Advanced Sockets API for IPv6  
RFC 3587 IPv6 Global Unicast Address Format  
RFC 3596 DNS Extension for IPv6  
RFC 3736 Stateless Dynamic Host Configuration Protocol (DHCP) Service for IPv6  
RFC 4007 IPv6 Scoped Address Architecture  
RFC 4022 MIB for TCP  
RFC 4113 MIB for UDP

### Technical Specifications

(LACP)  
IEEE 802.3x Flow Control  
IEEE 802.3z 1000BASE-X Gigabit Ethernet over fiber  
RFC 768 UDP  
RFC 792 ICMP  
RFC 793 TCP  
RFC 826 ARP  
RFC 854 TELNET  
RFC 951 BOOTP  
RFC 1350 TFTP Protocol (revision 2)  
RFC 2131 DHCP  
RFC 2865 Remote Authentication Dial In User Service (RADIUS)  
RFC 2866 RADIUS Accounting

#### IPv6

RFC 1350 TFTP  
RFC 1886 DNS Extension for IPv6  
RFC 1887 IPv6 Unicast Address Allocation Architecture  
RFC 1981 IPv6 Path MTU Discovery  
RFC 2292 Advanced Sockets API for IPv6  
RFC 2373 IPv6 Addressing Architecture  
RFC 2460 IPv6 Specification  
RFC 2461 IPv6 Neighbor Discovery  
RFC 2462 IPv6 Stateless Address Auto-configuration  
RFC 2463 ICMPv6  
RFC 2464 Transmission of IPv6 over Ethernet Networks  
RFC 2465 Management Information Base for IP Version 6: Textual Conventions and General Group (partially support, only "IPv6 Interface Statistics table")  
RFC 2475 IPv6 DiffServ Architecture  
RFC 2553 Basic Socket Interface Extensions for IPv6  
RFC 2711 IPv6 Router Alert Option  
RFC 2893 Transition Mechanisms for IPv6 Hosts and Routers  
RFC 2925 Definitions of Managed Objects for Remote Ping, Traceroute, and Lookup Operations (Ping only)  
RFC 2925 Remote Operations MIB (Ping only)  
RFC 3056 Connection of IPv6 Domains via IPv4 Clouds  
RFC 3162 RADIUS and IPv6  
RFC 3363 DNS support  
RFC 3484 Default Address Selection for IPv6  
RFC 3493 Basic Socket Interface Extensions for IPv6

RFC 4251 SSHv6 Architecture  
RFC 4252 SSHv6 Authentication  
RFC 4253 SSHv6 Transport Layer  
RFC 4254 SSHv6 Connection  
RFC 4291 IP Version 6 Addressing Architecture  
RFC 4293 MIB for IP  
RFC 4419 Key Exchange for SSH  
RFC 4443 ICMPv6  
RFC 4541 IGMP & MLD Snooping Switch  
RFC 4861 IPv6 Neighbor Discovery  
RFC 4862 IPv6 Stateless Address Auto-configuration  
RFC 5095 Deprecation of Type 0 Routing Headers in IPv6  
RFC 5722 Handling of Overlapping IPv6 Fragments

#### MIBs

IEEE8021-PAE-MIB  
IEEE8023-LAG-MIB  
RFC 1213 MIB II  
RFC 1493 Bridge MIB  
RFC 2011 SNMPv2 MIB for IP  
RFC 2013 SNMPv2 MIB for UDP  
RFC 2233 Interface MIB  
RFC 2571 SNMP Framework MIB  
RFC 2572 SNMP-MPD MIB  
RFC 2573 SNMP-Target MIB  
RFC 2618 RADIUS Authentication Client MIB  
RFC 2620 RADIUS Accounting Client MIB  
RFC 2665 Ethernet-Like-MIB  
RFC 2668 802.3 MAU MIB  
RFC 2674 802.1p and IEEE 802.1Q Bridge MIB  
RFC 2819 RMON MIB  
RFC 2925 Ping MIB  
RFC 3414 SNMP-User based-SM MIB  
RFC 3415 SNMP-View based-ACM MIB  
RFC 3418 MIB for SNMPv3  
RFC 4133 Entity MIB (Version 3)  
LLDP-EXT-DOT1-MIB  
LLDP-EXT-DOT3-MIB  
LLDP-MIB

#### Network management

IEEE 802.1AB Link Layer Discovery Protocol (LLDP)  
ANSI/TIA-1057 LLDP Media Endpoint Discovery (LLDP-MED)  
SNMPv1/v2c/v3

### Accessories

|   |  |        |
|---|--|--------|
| <b>HP 5120 SI Switch Series accessories</b> | <b>Transceivers</b>  |        |
|   | <a href="#">HP X120 1G SFP LC SX Transceiver</a>                       | JD118B |
|   | <a href="#">HP X120 1G SFP LC LX Transceiver</a>                       | JD119B |
|   | <a href="#">HP X125 1G SFP LC LH40 1310nm Transceiver</a>              | JD061A |
|   | <a href="#">HP X120 1G SFP LC LH40 1550nm Transceiver</a>              | JD062A |
|   | <a href="#">HP X125 1G SFP LC LH70 Transceiver</a>                     | JD063B |
|   | <a href="#">HP X120 1G SFP LC BX 10-U Transceiver</a>                  | JD098B |
|   | <a href="#">HP X120 1G SFP LC BX 10-D Transceiver</a>                  | JD099B |
|   | <a href="#">HP X120 1G SFP RJ45 T Transceiver</a>                      | JD089B |
|   | <b>Cables</b>  |        |
|   | <a href="#">HP 0.5 m Multimode OM3 LC/LC Optical Cable</a>             | AJ833A |
|   | <a href="#">HP 1 m Multimode OM3 LC/LC Optical Cable</a>               | AJ834A |
|   | <a href="#">HP 2 m Multimode OM3 LC/LC Optical Cable</a>               | AJ835A |
|   | <a href="#">HP 5 m Multimode OM3 LC/LC Optical Cable</a>               | AJ836A |
|   | <a href="#">HP 15 m Multimode OM3 LC/LC Optical Cable</a>              | AJ837A |
|   | <a href="#">HP 30 m Multimode OM3 LC/LC Optical Cable</a>              | AJ838A |
|   | <a href="#">HP 50 m Multimode OM3 LC/LC Optical Cable</a>              | AJ839A |
|   | <a href="#">HP Premier Flex LC/LC Multi-mode OM4 2 fiber 1m Cable</a>  | QK732A |
|   | <a href="#">HP Premier Flex LC/LC Multi-mode OM4 2 fiber 2m Cable</a>  | QK733A |
|   | <a href="#">HP Premier Flex LC/LC Multi-mode OM4 2 fiber 5m Cable</a>  | QK734A |
|   | <a href="#">HP Premier Flex LC/LC Multi-mode OM4 2 fiber 15m Cable</a> | QK735A |
|   | <a href="#">HP Premier Flex LC/LC Multi-mode OM4 2 fiber 30m Cable</a> | QK736A |
|   | <a href="#">HP Premier Flex LC/LC Multi-mode OM4 2 fiber 50m Cable</a> | QK737A |
|   | <a href="#">HP 3600 Switch SFP Stacking Kit</a>                        | JD324B |
|   | <b>Power Supply</b>  |        |
|   | <a href="#">HP RPS1600 Redundant Power System</a>                      | JG136A |
|   | <a href="#">HP RPS1600 1600W AC Power Supply</a>                       | JG137A |
|   | <b>Power cords</b>   |        |
|   | <a href="#">HP X290 1000 A JD5 2m RPS Cable</a>                        | JD187A |

### Accessory Product Details

**NOTE:** Details are not available for all accessories. The following specifications were available at the time of publication.

|  |                                   |   |  |
|--|-----------------------------------|---|--|
| <b>HP X120 1G SFP LC SX Transceiver (JD118B)</b><br><br>A small form-factor pluggable (SFP) Gigabit Ethernet LX transceiver that provides a full duplex Gigabit solution up to 550m on MMF or 10Km on SMF. | <b>Ports</b>                      | 1 LC 1000BASE-SX port (IEEE 802.3z Type 1000BASE-SX)  |  |
|  | <b>Connectivity</b>               | <b>Connector type</b> LC  |  |
|  | <b>Physical characteristics</b>   | <b>Wavelength</b>   | 850 nm   |
|  |                                   | <b>Dimensions</b>   | 2.17(d) x 0.6(w) x 0.46(h) in. (5.51 x 1.52 x 1.17 cm) |
|  |                                   | <b>Full configuration weight</b>  | 0.04 lb. (0.02 kg)                                     |
|  | <b>Electrical characteristics</b> | <b>Power consumption typical</b>  | 0.8 W  |
|  |                                   | <b>Power consumption maximum</b>  | 1.0 W  |
|  | <b>Cabling</b>                    | Maximum distance:   |  |
|  |                                   | • FDDI Grade distance = 220m  |  |
|  |                                   | • OM1 = 275m  |  |
|  | • OM2 = 500m                      |   |  |
|  | • OM3 = Not Specified by standard |   |  |
| <b>Services</b>  | Cable length                      | up to 550m  |  |
|  | Fiber type                        | Multi Mode  |  |
|  |                                   | Refer to the HP website at <a href="http://www.hp.com/networking/services">www.hp.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office. |  |

|  |                                   |   |  |
|--|-----------------------------------|---|--|
| <b>HP X120 1G SFP LC LX Transceiver (JD119B)</b><br><br>A small form-factor pluggable (SFP) Gigabit LX transceiver that provides a full duplex Gigabit solution up to 550m on MMF or 10Km on SMF | <b>Ports</b>                      | 1 SFP 1000BASE-LX port (IEEE 802.3z Type 1000BASE-LX) |  |
|  | <b>Connectivity</b>               | <b>Connector type</b> LC                              |  |
|  | <b>Physical characteristics</b>   | <b>Wavelength</b>                                     | 1300 nm  |
|  |                                   | <b>Dimensions</b>                                     | 2.17(d) x 0.6(w) x 0.46(h) in. (5.51 x 1.52 x 1.17 cm) |
|  |                                   | <b>Full configuration weight</b>                      | 0.04 lb. (0.02 kg)                                     |
|  | <b>Electrical characteristics</b> | <b>Power consumption typical</b>                      | 0.8 W  |
|  |                                   | <b>Power consumption maximum</b>                      | 1.0 W  |
|  | <b>Cabling</b>                    | Cable type:   | Either single mode or multimode;                       |
|  |                                   | Maximum distance:                                     |  |
|  |                                   | • 550m for Multimode                                  |  |
|  | • 10km for Singlemode             |   |  |
|  | Fiber type                        | Both  |  |

### Accessory Product Details

**Services** Refer to the HP website at [www.hp.com/networking/services](http://www.hp.com/networking/services) for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

**HP X125 1G SFP LC LH40  
1310nm Transceiver  
(JD061A)**

A small form-factor pluggable SFP Gigabit LH40 transceiver that provides a full duplex Gigabit solution up to 40km on a single-mode fiber.

**Ports** 1 LC 1000Base-LH port (no IEEE standard exists for 1550 nm optics)

**Connectivity** Connector type LC  
Wavelength 1310 nm

**Physical characteristics** Dimensions 2.17(d) x 0.6(w) x 0.46(h) in. (5.51 x 1.52 x 1.17 cm)  
Full configuration weight 0.04 lb. (0.02 kg)

**Electrical characteristics** Power consumption typical 0.8 W  
Power consumption maximum 1.0 W

**Cabling** Cable type: Single-mode fiber optic, complying with ITU-T G.652;  
Maximum distance:  

- 40km distance

Fiber type Single Mode

**Services** Refer to the HP website at [www.hp.com/networking/services](http://www.hp.com/networking/services) for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

**HP X120 1G SFP LC LH40  
1550nm Transceiver  
(JD062A)**

A small form-factor pluggable (SFP) Gigabit LH40 transceiver that provides a full-duplex Gigabit solution up to 40 km on a single mode fiber.

**Ports** 1 LC 1000BASE-LH port (no IEEE standard exists for 1550 nm optics)

**Connectivity** Connector type LC  
Wavelength 1550 nm

**Physical characteristics** Dimensions 2.17(d) x 0.6(w) x 0.46(h) in. (5.51 x 1.52 x 1.17 cm)  
Full configuration weight 0.04 lb. (0.02 kg)

**Electrical characteristics** Power consumption typical 0.8 W  
Power consumption maximum 1.0 W

**Cabling** Cable type: Single-mode fiber optic, complying with ITU-T G.652;  
Maximum distance:  

- 40km distance

Fiber type Single Mode

**Services** Refer to the HP website at [www.hp.com/networking/services](http://www.hp.com/networking/services) for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

### Accessory Product Details

#### HP X125 1G SFP LC LH70 Transceiver (JD063B)

A small form-factor pluggable (SFP) Gigabit LH70 transceiver that provides a full-duplex Gigabit solution up to 70km on a single-mode fiber.

|                                   |   |
|-----------------------------------|---|
| <b>Ports</b>                      | 1 LC 1000BASE-LH port (no IEEE standard exists for 1550 nm optics)  |
| <b>Connectivity</b>               | <b>Connector type</b> LC  |
| <b>Physical characteristics</b>   | <b>Wavelength</b> 1550 nm   |
| <b>Electrical characteristics</b> | <b>Dimensions</b> 2.17(d) x 0.6(w) x 0.46(h) in. (5.51 x 1.52 x 1.17 cm)  |
| <b>Cabling</b>                    | <b>Full configuration weight</b> 0.04 lb. (0.02 kg)   |
| <b>Services</b>                   | <b>Power consumption typical</b> 0.8 W  |
|                                   | <b>Power consumption maximum</b> 1.0 W  |
|                                   | <b>Cable type:</b><br>Single-mode fiber optic, complying with ITU-T G.652;  |
|                                   | <b>Maximum distance:</b><br>• 70km  |
|                                   | <b>Fiber type</b> Single Mode   |
|                                   | Refer to the HP website at <a href="http://www.hp.com/networking/services">www.hp.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office. |

#### HP X120 1G SFP LC BX 10-U Transceiver (JD098B)

A small form-factor pluggable (SFP) Gigabit LX-BX10-U transceiver that provides a full duplex Gigabit solution up to 10km on a single mode cable.

|                                   |  |
|-----------------------------------|--|
| <b>Ports</b>                      | 1 LC 1000BASE-BX10 port (IEEE 802.3ah Type 1000BASE-BX10-U); Duplex: full only   |
| <b>Connectivity</b>               | <b>Connector type</b> LC   |
| <b>Physical characteristics</b>   | <b>Dimensions</b> 2.17(d) x 0.6(w) x 0.46(h) in. (5.51 x 1.52 x 1.17 cm)   |
| <b>Electrical characteristics</b> | <b>Full configuration weight</b> 0.04 lb. (0.02 kg)  |
| <b>Cabling</b>                    | <b>Power consumption typical</b> 0.8 W   |
| <b>Notes</b>                      | <b>Power consumption maximum</b> 1.0 W   |
| <b>Services</b>                   | <b>Maximum distance:</b><br>• 10km   |
|                                   | <b>Fiber type</b> Single Mode  |
|                                   | TX 1310nm RX 1490nm  |
|                                   | Refer to the HP website at: <a href="http://www.hp.com/networking/services">www.hp.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office. |

### Accessory Product Details

|  |  |
|--|--|
| <p><b>HP X120 1G SFP LC BX10-D Transceiver (JD099B)</b></p> <p>A small form-factor pluggable (SFP) Gigabit LX-BX10-D transceiver that provides a full duplex Gigabit solution up to 10km on a single mode cable.</p> | <p><b>Ports</b></p> <p>1 LC 1000BASE-BX10 port (IEEE 802.3ah Type 1000BASE-BX10-D); Duplex: full only</p>  |
| <p><b>Connectivity</b></p>   | <p><b>Connector type</b></p> <p>LC</p>   |
| <p><b>Physical characteristics</b></p>   | <p><b>Dimensions</b></p> <p>2.17(d) x 0.6(w) x 0.46(h) in. (5.51 x 1.52 x 1.17 cm)</p> <p><b>Full configuration weight</b></p> <p>0.04 lb. (0.02 kg)</p>   |
| <p><b>Electrical characteristics</b></p>   | <p><b>Power consumption typical</b></p> <p>0.8 W</p> <p><b>Power consumption maximum</b></p> <p>1.0 W</p>  |
| <p><b>Cabling</b></p>  | <p>Maximum distance:</p> <ul style="list-style-type: none"> <li>• Up to 10km</li> </ul> <p>Fiber type</p> <p>Single Mode</p>   |
| <p><b>Notes</b></p>  | <p>TX 1490nm RX 1310nm</p>   |
| <p><b>Services</b></p>   | <p>Refer to the HP website at <a href="http://www.hp.com/networking/services">www.hp.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.</p> |

|   |   |
|---|---|
| <p><b>HP X120 1G SFP RJ45 T Transceiver (JD089B)</b></p> <p>A small form factor pluggable (SFP) Gigabit 1000Base-T transceiver that provides a full duplex Gigabit solution up to 100m on a Cat-5+ cable.</p> | <p><b>Ports</b></p> <p>1 RJ-45 1000BASE-T port (IEEE 802.3ab Type 1000BASE-T)</p>   |
| <p><b>Connectivity</b></p>  | <p><b>Connector type</b></p> <p>RJ-45</p>   |
| <p><b>Physical characteristics</b></p>  | <p><b>Dimensions</b></p> <p>2.71(d) x 0.54(w) x 0.55(h) in. (6.88 x 1.37 x 1.4 cm)</p> <p><b>Full configuration weight</b></p> <p>0.07 lb. (0.03 kg)</p>  |
| <p><b>Electrical characteristics</b></p>  | <p><b>Power consumption typical</b></p> <p>0.8 W</p> <p><b>Power consumption maximum</b></p> <p>1.0 W</p>   |
| <p><b>Cabling</b></p>   | <p>Cable type:</p> <p>1000BASE-T: Category 5 (5E or better recommended), 100 Ω differential 4-pair unshielded twisted pair (UTP) or shielded twisted pair (STP) balanced, complying with IEEE 802.3ab 1000BASE-T;</p> <p>Maximum distance:</p> <ul style="list-style-type: none"> <li>• 100m</li> </ul> |
| <p><b>Services</b></p>  | <p>Refer to the HP website at <a href="http://www.hp.com/networking/services">www.hp.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.</p>          |

### Accessory Product Details

**HP 0.5 m Multimode OM3 Cabling  
LC/LC Optical Cable  
(AJ833A)**

**Cable type:**

50/125  $\mu\text{m}$  (core/cladding) diameter, multimode fiber optic, with effective modal bandwidth of 2000 MHz/km as detailed in TIA-492AAAC for distances of up to 300 m

**Maximum distance:**

10Gbps Transfer Rate (Ethernet): 300m

**Notes**

Cable Specs: Tight buffered duplex fiber optic multimode OM3 50/125  $\mu\text{m}$  fiber optic cable and Ethernet assembly with LC duplex connectors on one end and LC duplex connectors on other end.

- Dimensions: Core diameter:  $50 \pm 3.0\mu\text{m}$  Cladding diameter:  $125 \pm 2.0\mu\text{m}$  Coating diameter:  $245 \pm 10\mu\text{m}$
- Optical glass: Bandwidth: For LED sources: 1500/500 MHz-km @850/1300nm.
- Optical glass: Bandwidth: For Laser sources: 2000/500 MHz-km @850/1300nm. VCSEL Laser sources: 600 / 600 meters @850/1300nm for Gigabit Ethernet compliant links.
- CABLE: The cable is duplex zipcord graded index 50/125 $\mu\text{m}$  multimode optical fiber and designed to work in both the 850 and 1300 nm wavelength windows.
- BULK CABLE & CABLE ASSEMBLY CONFIGURATION:
- Jacket Material: Riser Grade - Low Smoke Zero Halogen thermoplastic.
- Jacket Color: Aqua for OM3 multimode per TIA 598
- Boot Color: White
- Insertion Loss: less than 0.5 dB @ 850 with LED source, 0.003 dB/M added for lengths > 30 meters.
- Maximum Cable attenuation: 3.0 dB/km @ 850 nm, 1.0 dB/Km @ 1310 nm @ 23°C as tested in accordance with EIA 455-46.
- Weight: Air Packed Weight: 1 LB Net Weight: 0.454Kg

**Services**

Refer to the HP website at [www.hp.com/networking/services](http://www.hp.com/networking/services) for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

### Accessory Product Details

**HP 1 m Multimode OM3 LC/LC Optical Cable**  
(AJ834A)

**Cabling**

**Cable type:**

50/125  $\mu\text{m}$  (core/cladding) diameter, multimode fiber optic, with effective modal bandwidth of 2000 MHz/km as detailed in TIA-492AAAC for distances of up to 300 m

**Maximum distance:**

10Gbps Transfer Rate (Ethernet): 300m

**Notes**

Cable Specs: Tight buffered duplex fiber optic multimode OM3 50/125  $\mu\text{m}$  fiber optic cable and Ethernet assembly with LC duplex connectors on one end and LC duplex connectors on other end.

- Dimensions: Core diameter:  $50 \pm 3.0\mu\text{m}$  Cladding diameter:  $125 \pm 2.0\mu\text{m}$  Coating diameter:  $245 \pm 10\mu\text{m}$
- Optical Glass Bandwidth: For LED sources: 1500/500 MHz-km @850/1300nm.
- Optical Glass: For Laser sources: 2000/500 MHz-km @850/1300nm. VCSEL Laser sources: Shall achieve 600 / 600 meters @850/1300nm for Gigabit Ethernet compliant links.
- CABLE: The cable is duplex zipcord graded index 50/125 $\mu\text{m}$  multimode optical fiber. The cable is designed to work in both the 850 and 1300 nm wavelength windows.
- BULK CABLE & CABLE ASSEMBLY CONFIGURATION:
- Jacket Material: Riser Grade - Low Smoke Zero Halogen thermoplastic.
- Jacket Color: Aqua for OM3 multimode per TIA 598
- Boot Color: White
- Insertion Loss: less than 0.5 dB @ 850 with LED source, 0.003 dB/M added for lengths > 30 meters.
- Maximum Cable attenuation: 3.0 dB/km @ 850 nm, 1.0 dB/Km @ 1310 nm @ 23°C as tested in accordance with EIA 455-46.
- Weight: Air Packed Weight: 1 LB Net Weight: 0.454Kg

**Services**

Refer to the HP website at [www.hp.com/networking/services](http://www.hp.com/networking/services) for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

### Accessory Product Details

**HP 2 m Multimode OM3 LC/LC Optical Cable**  
(AJ835A)

**Cabling**

**Cable type:**

50/125 µm (core/cladding) diameter, multimode fiber optic, with effective modal bandwidth of 2000 MHz/km as detailed in TIA-492AAAC for distances of up to 300 m;

**Maximum distance:**

10Gbps Transfer Rate (Ethernet): 300m

**Notes**

Cable Specs: Tight buffered duplex fiber optic multimode OM3 50/125 µm fiber optic cable and Ethernet assembly with LC duplex connectors on one end and LC duplex connectors on other end.

- Dimensions: Core diameter: 50 ± 3.0µm Cladding diameter: 125 ± 2.0µm Coating diameter: 245 ± 10µm
- Optical Glass Bandwidth: For LED sources: 1500/500 MHz-km @850/1300nm.
- Optical Glass: For Laser sources: 2000/500 MHz-km @850/1300nm. VCSEL Laser sources: Shall achieve 600 / 600 meters @850/1300nm for Gigabit Ethernet compliant links.
- CABLE: The cable is duplex zipcord graded index 50/125µm multimode optical fiber. The cable is designed to work in both the 850 and 1300 nm wavelength windows.
- BULK CABLE & CABLE ASSEMBLY CONFIGURATION:
- Jacket Material: Riser Grade - Low Smoke Zero Halogen thermoplastic.
- Jacket Color: Aqua for OM3 multimode per TIA 598
- Boot Color: White
- Insertion Loss: less than 0.5 dB @ 850 with LED source, 0.003 dB/M added for lengths > 30 meters.
- Maximum Cable attenuation: 3.0 dB/km @ 850 nm, 1.0 dB/Km @ 1310 nm @ 23°C as tested in accordance with EIA 455-46.
- Weight: Air Packed Weight: 1 LB Net Weight: 0.454Kg

**Services**

Refer to the HP website at [www.hp.com/networking/services](http://www.hp.com/networking/services) for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

### Accessory Product Details

**HP 5 m Multimode OM3 LC/LC Optical Cable**    **Cabling**  
(AJ836A)

**Cable type:**

50/125 µm core/cladding) diameter, multimode fiber optic, with effective modal bandwidth of 2000 MHz/km as detailed in TIA-492AAAC for distances of up to 300 m;

**Maximum distance:**

10Gbps Transfer Rate (Ethernet): 300m

**Notes**

Cable Specs: This specification defines the detail requirements for a tight buffered duplex fiber optic multimode OM3 50/125 um fiber optic cable and Ethernet assembly with LC duplex connectors on one end and LC duplex connectors on other end.

- Dimensions: Core diameter: 50 ± 3.0um Cladding diameter: 125 ± 2.0um Coating diameter: 245 ± 10um
- Optical Glass Bandwidth: For LED sources: 1500/500 MHz-km @850/1300nm.
- Optical Glass: For Laser sources: 2000/500 MHz-km @850/1300nm. VCSEL Laser sources: Shall achieve 600 / 600 meters @850/1300nm for Gigabit Ethernet compliant links.
- CABLE: The cable is duplex zipcord graded index 50/125um multimode optical fiber. The cable is designed to work in both the 850 and 1300 nm wavelength windows.
- BULK CABLE & CABLE ASSEMBLY CONFIGURATION:
- Jacket Material: Riser Grade - Low Smoke Zero Halogen thermoplastic.
- Jacket Color: Aqua for OM3 multimode per TIA 598
- Boot Color: White
- Insertion Loss: less than 0.5 dB @ 850 with LED source, 0.003 dB/M added for lengths > 30 meters.
- Maximum Cable attenuation: 3.0 dB/km @ 850 nm, 1.0 dB/Km @ 1310 nm @ 23°C as tested in accordance with EIA 455-46.
- Weight: Air Packed Weight: 1 LB Net Weight: 0.454Kg

**Services**

Refer to the HP website at [www.hp.com/networking/services](http://www.hp.com/networking/services) for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

### Accessory Product Details

**HP 15 m Multimode OM3 Cabling**  
**LC/LC Optical Cable**  
(AJ837A)

**Cable type:**

50/125  $\mu\text{m}$  (core/cladding) diameter, multimode fiber optic, with effective modal bandwidth of 2000 MHz/km as detailed in TIA-492AAAC for distances of up to 300 m;

**Maximum distance:**

10Gbps Transfer Rate (Ethernet): 300m

**Notes**

Cable Specs: Tight buffered duplex fiber optic multimode OM3 50/125  $\mu\text{m}$  fiber optic cable and Ethernet assembly with LC duplex connectors on one end and LC duplex connectors on other end.

- Dimensions: Core diameter:  $50 \pm 3.0\mu\text{m}$  Cladding diameter:  $125 \pm 2.0\mu\text{m}$  Coating diameter:  $245 \pm 10\mu\text{m}$
- Optical Glass Bandwidth: For LED sources: 1500/500 MHz-km @850/1300nm.
- Optical Glass: For Laser sources: 2000/500 MHz-km @850/1300nm. VCSEL Laser sources: Shall achieve 600 / 600 meters @850/1300nm for Gigabit Ethernet compliant links.
- CABLE: The cable is duplex zipcord graded index 50/125 $\mu\text{m}$  multimode optical fiber. The cable is designed to work in both the 850 and 1300 nm wavelength windows.
- BULK CABLE & CABLE ASSEMBLY CONFIGURATION:
- Jacket Material: Riser Grade - Low Smoke Zero Halogen thermoplastic.
- Jacket Color: Aqua for OM3 multimode per TIA 598
- Boot Color: White
- Insertion Loss: less than 0.5 dB @ 850 with LED source, 0.003 dB/M added for lengths > 30 meters.
- Maximum Cable attenuation: 3.0 dB/km @ 850 nm, 1.0 dB/Km @ 1310 nm @ 23°C as tested in accordance with EIA 455-46.
- Weight: Air Packed Weight: 1 LB Net Weight: 0.454Kg

**Services**

Refer to the HP website at [www.hp.com/networking/services](http://www.hp.com/networking/services) for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

### Accessory Product Details

**HP 30 m Multimode OM3 Cabling  
LC/LC Optical Cable  
(AJ838A)**

**Cable type:**

50/125 µm (core/cladding) diameter, multimode fiber optic, with effective modal bandwidth of 2000 MHz/km as detailed in TIA-492AAAC for distances of up to 300 m;

**Maximum distance:**

10Gbps Transfer Rate (Ethernet): 300m

**Notes**

Cable Specs: Tight buffered duplex fiber optic multimode OM3 50/125 um fiber optic cable and Ethernet assembly with LC duplex connectors on one end and LC duplex connectors on other end.

- Dimensions: Core diameter: 50 ± 3.0um Cladding diameter: 125 ± 2.0um Coating diameter: 245 ± 10um
- Optical Glass Bandwidth: For LED sources: 1500/500 MHz-km @850/1300nm.
- Optical Glass: For Laser sources: 2000/500 MHz-km @850/1300nm. VCSEL Laser sources: Shall achieve 600 / 600 meters @850/1300nm for Gigabit Ethernet compliant links.
- CABLE: The cable is duplex zipcord graded index 50/125um multimode optical fiber. The cable is designed to work in both the 850 and 1300 nm wavelength windows.
- BULK CABLE & CABLE ASSEMBLY CONFIGURATION:
- Jacket Material: Riser Grade - Low Smoke Zero Halogen thermoplastic.
- Jacket Color: Aqua for OM3 multimode per TIA 598
- Boot Color: White
- Insertion Loss: less than 0.5 dB @ 850 with LED source, 0.003 dB/M added for lengths > 30 meters.
- Maximum Cable attenuation: 3.0 dB/km @ 850 nm, 1.0 dB/Km @ 1310 nm @ 23°C as tested in accordance with EIA 455-46.
- Weight: Air Packed Weight: 1 LB Net Weight: 0.454Kg

**Services**

Refer to the HP website at [www.hp.com/networking/services](http://www.hp.com/networking/services) for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

### Accessory Product Details

**HP 50 m Multimode OM3 Cabling**  
**LC/LC Optical Cable**  
(AJ839A)

**Cable type:**

50/125  $\mu\text{m}$  (core/cladding) diameter, multimode fiber optic, with effective modal bandwidth of 2000 MHz/km as detailed in TIA-492AAAC for distances of up to 300 m;

**Maximum distance:**

10Gbps Transfer Rate (Ethernet): 300m

**Notes**

Cable Specs: Tight buffered duplex fiber optic multimode OM3 50/125  $\mu\text{m}$  fiber optic cable and Ethernet assembly with LC duplex connectors on one end and LC duplex connectors on other end.

- Dimensions: Core diameter:  $50 \pm 3.0\mu\text{m}$  Cladding diameter:  $125 \pm 2.0\mu\text{m}$  Coating diameter:  $245 \pm 10\mu\text{m}$
- Optical Glass Bandwidth: For LED sources: 1500/500 MHz-km @850/1300nm.
- Optical Glass: For Laser sources: 2000/500 MHz-km @850/1300nm. VCSEL Laser sources: Shall achieve 600 / 600 meters @850/1300nm for Gigabit Ethernet compliant links.
- CABLE: The cable is duplex zipcord graded index 50/125 $\mu\text{m}$  multimode optical fiber. The cable is designed to work in both the 850 and 1300 nm wavelength windows.
- BULK CABLE & CABLE ASSEMBLY CONFIGURATION:
- Jacket Material: Riser Grade - Low Smoke Zero Halogen thermoplastic.
- Jacket Color: Aqua for OM3 multimode per TIA 598
- Boot Color: White
- Insertion Loss: less than 0.5 dB @ 850 with LED source, 0.003 dB/M added for lengths > 30 meters.
- Maximum Cable attenuation: 3.0 dB/km @ 850 nm, 1.0 dB/Km @ 1310 nm @ 23°C as tested in accordance with EIA 455-46.
- Weight: Air Packed Weight: 1 LB Net Weight: 0.454Kg

**Services**

Refer to the HP website at [www.hp.com/networking/services](http://www.hp.com/networking/services) for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

### Accessory Product Details

**HP Premier Flex LC/LC  
Multi-mode OM4 2 fiber  
1m Cable (QK732A)**

**Notes**

Cable Specs: Graded-index, "bendable" fiber optic multimode OM3+ 50/125um duplex cable and Ethernet assembly with LC duplex connectors on each end.

- Core Diameter: 50um ±3um, Cladding diameter: 125um ±2um; Coating diameter: 245 ± 10um
- Bandwidth: 3000 MHz-km @ 850nm (Laser)
- Jacket Color: Blue
- Jacket Material: Riser Grade – Low Smoke Zero Halogen (LSZH) thermoplastic
- Boot Color: White
- Outer Jacket Print: HP PremierFlex OM3+ Fiber Optic Cable, 50/125um, Type OFNR (UL), LSZH, cUL, OFN FT4, ROHS. Cable also has a longitudinal white stripe that runs the entire length of the cable.
- Insertion Loss: Less than 0.5dB @ 850nm with LED source, 0.003dB/m added for lengths >30m
- Maximum Cable Attenuation: 3.0 dB/km @ 850nm, 1.0 dB/km @ 1310nm @ 23°C as tested in accordance with EIA 455-45

**Services**

Refer to the HP website at [www.hp.com/networking/services](http://www.hp.com/networking/services) for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

**HP Premier Flex LC/LC  
Multi-mode OM4 2 fiber  
2m Cable (QK733A)**

**Notes**

Cable Specs: Graded-index, "bendable" fiber optic multimode OM3+ 50/125um duplex cable and Ethernet assembly with LC duplex connectors on each end.

- Core diameter: 50um ±3um, Cladding diameter: 125um ±2um; Coating diameter: 245 ± 10um
- Bandwidth: 3000 MHz-km @ 850nm (Laser)
- Jacket Color: Blue
- Jacket Material: Riser Grade – Low Smoke Zero Halogen (LSZH) thermoplastic
- Boot Color: White
- Outer Jacket Print: HP PremierFlex OM3+ Fiber Optic Cable, 50/125um, Type OFNR (UL), LSZH, cUL, OFN FT4, ROHS. Cable also has a longitudinal white stripe that runs the entire length of the cable.
- Insertion Loss: Less than 0.5dB @ 850nm with LED source, 0.003dB/m added for lengths >30m
- Maximum Cable Attenuation: 3.0 dB/km @ 850nm, 1.0 dB/km @ 1310nm @ 23°C as tested in accordance with EIA 455-45

**Services**

Refer to the HP website at [www.hp.com/networking/services](http://www.hp.com/networking/services) for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

### Accessory Product Details

**HP Premier Flex LC/LC  
Multi-mode OM4 2 fiber  
5m Cable (QK734A)**

**Notes**

Cable Specs: Graded-index, "bendable" fiber optic multimode OM3+ 50/125um duplex cable and Ethernet assembly with LC duplex connectors on each end.

- Core diameter: 50um  $\pm$ 3um, Cladding diameter: 125um  $\pm$ 2um; Coating diameter: 245  $\pm$  10um
- Bandwidth: 3000 MHz-km @ 850nm (Laser)
- Jacket Color: Blue
- Jacket Material: Riser Grade – Low Smoke Zero Halogen (LSZH) thermoplastic
- Boot Color: White
- Outer Jacket Print: HP PremierFlex OM3+ Fiber Optic Cable, 50/125um, Type OFNR (UL), LSZH, cUL, OFN FT4, ROHS. Cable also has a longitudinal white stripe that runs the entire length of the cable.
- Insertion Loss: Less than 0.5dB @ 850nm with LED source, 0.003dB/m added for lengths >30m
- Maximum Cable Attenuation: 3.0 dB/km @ 850nm, 1.0 dB/km @ 1310nm @ 23°C as tested in accordance with EIA 455-45

**Services**

Refer to the HP website at [www.hp.com/networking/services](http://www.hp.com/networking/services) for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

**HP Premier Flex LC/LC  
Multi-mode OM4 2 fiber  
15m Cable (QK735A)**

**Notes**

Cable Specs: Graded-index, "bendable" fiber optic multimode OM3+ 50/125um duplex cable and Ethernet assembly with LC duplex connectors on each end.

- Core diameter: 50um  $\pm$ 3um, Cladding diameter: 125um  $\pm$ 2um; Coating diameter: 245  $\pm$  10um
- Bandwidth: 3000 MHz-km @ 850nm (Laser)
- Jacket Color: Blue
- Jacket Material: Riser Grade – Low Smoke Zero Halogen (LSZH) thermoplastic
- Boot Color: White
- Outer Jacket Print: HP PremierFlex OM3+ Fiber Optic Cable, 50/125um, Type OFNR (UL), LSZH, cUL, OFN FT4, ROHS. Cable also has a longitudinal white stripe that runs the entire length of the cable.
- Insertion Loss: Less than 0.5dB @ 850nm with LED source, 0.003dB/m added for lengths >30m
- Maximum Cable Attenuation: 3.0 dB/km @ 850nm, 1.0 dB/km @ 1310nm @ 23°C as tested in accordance with EIA 455-45

**Services**

Refer to the HP website at [www.hp.com/networking/services](http://www.hp.com/networking/services) for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

### Accessory Product Details

**HP Premier Flex LC/LC  
Multi-mode OM4 2 fiber  
30m Cable (QK736A)**

**Notes**

Cable Specs: Graded-index, "bendable" fiber optic multimode OM3+ 50/125um duplex cable and Ethernet assembly with LC duplex connectors on each end.

- Core diameter: 50um  $\pm$ 3um, Cladding diameter: 125um  $\pm$ 2um; Coating diameter: 245  $\pm$  10um
- Bandwidth: 3000 MHz-km @ 850nm (Laser)
- Jacket Color: Blue
- Jacket Material: Riser Grade – Low Smoke Zero Halogen (LSZH) thermoplastic
- Boot Color: White
- Outer Jacket Print: HP PremierFlex OM3+ Fiber Optic Cable, 50/125um, Type OFNR (UL), LSZH, cUL, OFN FT4, ROHS. Cable also has a longitudinal white stripe that runs the entire length of the cable.
- Insertion Loss: Less than 0.5dB @ 850nm with LED source, 0.003dB/m added for lengths >30m
- Maximum Cable Attenuation: 3.0 dB/km @ 850nm, 1.0 dB/km @ 1310nm @ 23°C as tested in accordance with EIA 455-45

**Services**

Refer to the HP website at [www.hp.com/networking/services](http://www.hp.com/networking/services) for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

**HP Premier Flex LC/LC  
Multi-mode OM4 2 fiber  
50m Cable (QK737A)**

**Notes**

Cable Specs: Graded-index, "bendable" fiber optic multimode OM3+ 50/125um duplex cable and Ethernet assembly with LC duplex connectors on each end.

- Core diameter: 50um  $\pm$ 3um, Cladding diameter: 125um  $\pm$ 2um; Coating diameter: 245  $\pm$  10um
- Bandwidth: 3000 MHz-km @ 850nm (Laser)
- Jacket Color: Blue
- Jacket Material: Riser Grade – Low Smoke Zero Halogen (LSZH) thermoplastic
- Boot Color: White
- Outer Jacket Print: HP PremierFlex OM3+ Fiber Optic Cable, 50/125um, Type OFNR (UL), LSZH, cUL, OFN FT4, ROHS. Cable also has a longitudinal white stripe that runs the entire length of the cable.
- Insertion Loss: Less than 0.5dB @ 850nm with LED source, 0.003dB/m added for lengths >30m
- Maximum Cable Attenuation: 3.0 dB/km @ 850nm, 1.0 dB/km @ 1310nm @ 23°C as tested in accordance with EIA 455-45

**Services**

Refer to the HP website at [www.hp.com/networking/services](http://www.hp.com/networking/services) for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

### Accessory Product Details

|   |                                   |  |
|---|-----------------------------------|--|
| <b>HP RPS1600 Redundant Power System (JG136A)</b> | <b>Ports</b>                      | 8 redundant power supply ports<br>Restrictions: two -56V/25A DC(PoE); six -56V/8A DC(non-PoE)  |
|   | <b>Physical characteristics</b>   | <p><b>Dimensions</b> 15.63(d) x 17.32(w) x 1.74(h) in. (39.7 x 44 x 4.42 cm)</p> <p><b>Weight</b> 14.11 lb. (6.4 kg)</p> <p><b>Full configuration weight</b> 16.75 lb. (7.6 kg)</p>  |
|   | <b>Environment</b>                | <p><b>Operating temperature</b> 14°F to 122°F (-10°C to 50°C)</p> <p><b>Operating relative humidity</b> 5% to 95%</p> <p><b>Nonoperating/Storage temperature</b> -40°F to 158°F (-40°C to 70°C)</p> <p><b>Nonoperating/Storage relative humidity</b> 5% to 95%</p> <p><b>Altitude</b> up to 13,123 ft. (4 km)</p> <p><b>Acoustic</b> Pressure: 53 dB; ISO 7779, ISO 9296</p>   |
|   | <b>Electrical characteristics</b> | <p><b>Voltage</b> 100-120/200-240 VAC</p> <p><b>Current</b> 30/60 A</p> <p><b>Idle power</b> 38 W</p> <p><b>Maximum power rating</b> 3550 W</p> <p><b>RPS power</b> 3200 W</p> <p><b>PoE power</b> 2800 W</p> <p><b>RPS</b> -55 V</p> <p><b>PoE</b> -55 V</p> <p><b>Frequency</b> 50/60 Hz</p> <p><b>Notes</b> Idle power is the actual power consumption of the device with no ports connected. Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated. With one RPS1600 Power Supply, the PRS1600 Redundant Power System can provide 1600W power output; With two PRS1600 Power Supplies, the output power is 3200W.</p> |
|   | <b>Safety</b>                     | CE Labeled; UL 60950-1; IEC 60950-1; ICES-003; FCC Part 15, Subpart B; EU RoHS Compliant; EN 60950-1/A11; C-Tick; VCCI Class A; ROHS Compliance; EN 300386   |
|   | <b>Services</b>                   | Refer to the HP website at: <a href="http://www.hp.com/networking/services">www.hp.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.   |

### Accessory Product Details

|  |  |   |   |
|--|--|---|---|
| <b>HP RPS1600 1600W AC Power Supply</b> (JG137A) | <b>Physical characteristics</b>  | <b>Dimensions</b>                             | 8.19(d) x 4.96(w) x 1.63(h) in. (20.8 x 12.6 x 4.15 cm)   |
|  |  | <b>Weight</b>                                 | 3.02 lb. (1.37 kg)  |
|  | <b>Environment</b>   | <b>Operating temperature</b>                  | 14°F to 122°F (-10°C to 50°C)   |
|  |  | <b>Operating relative humidity</b>            | 5% to 95%   |
|  |  | <b>Nonoperating/Storage temperature</b>       | -40°F to 158°F (-40°C to 70°C)  |
|  |  | <b>Nonoperating/Storage relative humidity</b> | 5% to 95%   |
|  | <b>Electrical characteristics</b>  | <b>Voltage</b>                                | 100-120/200-240 VAC   |
|  |  | <b>Current</b>                                | 15/30 A   |
|  |  | <b>Maximum power rating</b>                   | 1600 W  |
|  |  | <b>Frequency</b>                              | 50/60 Hz  |
|  |  | <b>Notes</b>                                  | Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated. |
| <b>Services</b>                                  | Refer to the HP website at: <a href="http://www.hp.com/networking/services">www.hp.com/networking/services</a> for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office. |   |   |

To learn more, visit: [www.hp.com/networking](http://www.hp.com/networking)

© Copyright 2010-2013 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.