

Xerox[®] Phaser[®] 7100 Color Printer



Phaser 7100 A full-featured color printer with optional automatic 2-sided printing and standard 400-sheet paper capacity.



Phaser 7100 Shown with additional 550sheet feeder (950-sheet paper capacity).



Phaser 7100 Shown with 3 additional 550-sheet feeders (2,050sheet paper capacity).



Phaser 7100 Shown with 3 additional 550-sheet feeders and System Cart with Storage Drawer (2,050-sheet paper capacity).

	7100N	7100DN		
Output Speed - Color and	Output Speed - Color and Black and White			
One-sided	Up to 30 ppm 8.5 x 11 in. / A4 (210 x 297 mm) Up to 20 ppm 8.5 x 14 in. Up to 17 ppm 11 x 17 in. / A3 (297 x 432 mm)			
Automatic Two-sided	N/A	Up to 22 ppm 8.5 x 11 in. / A4 (210 x 297 mm) Up to 12 ppm 8.5 x 14 in. Up to 11 ppm 11 x 17 in. / A3 (297 x 432 mm)		
Paper Handling - Input				
Bypass Tray	Bypass Tray			
Capacity ¹	150 sheets			
Sizes	Custom Sizes: 3 x 3.9 in. to 11.7 x 17 in., 8.5 x 35.4 in. and 11.7 x 47.2 in. banners / 75 x 98 mm to A3, 210 x 900 mm and 297 x 1200 mm banners			
Weights	16 lb. bond to 80 lb. cover / 60 to 216 gsm			
Media Types	Plain paper Recycled Heavyweight Card Stock Heavy Card Stock Glossy Glossy Card Stock Hole Punched Letterhead Pre-printed Custom Labels Envelopes			

Tray 1			
Capacity ¹	250 sheets		
Sizes	Sizes: 5.8 x 8.3 in. to 11.7 x 17 in. / 148 x 210 mm to 297 x	Sizes: 5.8 x 8.3 in. to 11.7 x 17 in. / 148 x 210 mm to 297 x 432 mm	
Weights	16 lb. bond to 80 lb. cover / 60 to 216 gsm		
Media Types	Plain paper Recycled Heavyweight Card Stock Heavy Card Stock Hole Punched Letterhead Pre-printed Custom Labels		
Trays 2, 3, 4 (Optional)	1		
Capacity ¹	550 sheets each		
Sizes	Sizes: 5.8 x 8.3 in. to 11.7 x 17 in. / 148 x 210 mm to 297 x	432 mm	
Weights	16 lb. bond to 80 lb. cover / 60 to 216 gsm	16 lb. bond to 80 lb. cover / 60 to 216 gsm	
Media Types	Plain paper Recycled Heavyweight Card Stock Heavy Card Stock Hole Punched Letterhead Pre-printed Custom Labels		
Paper Capacity			
Standard Capacity ¹	400 sheets		
Maximum Capacity ¹	2,050 sheets		
Paper Output	7100N	7100DN	
Output Tray (Standard)			
Output Capacity	250 sheets		
Automatic Two-sided Printing	N/A	Standard	
Print			
First-Page-Out Time	As fast as 11 seconds color / 9 seconds black-and-white		
Print Resolution	Up to 1200 x 1200 dpi ; 600 x 600 x 8 bit		
Maximum Print Area	11.5 x 16.7 in. / 291 x 424 mm		
Memory (Std/max)	1 GB / 2 GB		
Hard Drive (Optional)	40 GB		
Processor	667 MHz		

Language Support	Adobe® Postscript® 3™ PCL® 5c PCL® 6 Adobe PDF-Direct XPS	
Connectivity	10/100Base-T Ethernet USB 2.0 Optional external wireless 802.11 b, g, n	
Printing Features (Standard)	Earth Smart driver settings Collation Bi-directional driver Smart Duplex Layout / watermark	
Printing Features (Optional)	Productivity Kit (with 40 GB Hard Drive) Font Storage Network Accounting / Xerox® Standard Accounting 128-bit Hard Disk Encryption Hard Disk Overwrite Increased Secure Print capacity and Security Certificate protection	
Supported Operating Systems	Windows® XP, Server 2003, Server 2008, Vista, 7 Mac OS® 10.5 and higher Red Hat Fedora Core 12-15 HP-UX® 11iv2 IBM® AIX 5, SUSE® 11.x	
Print Drivers	Windows® XP and later Mac OS® 10.5 and later Various Linux® and Unix distributions Xerox® Global Print Driver® Xerox® Mobile Express Driver®	
Font Capability	136 PostScript [®] fonts 82 PCL [®] fonts	
Xerox® Mobile Express Driver® (X-MED)	 Makes it easy for mobile users to find, use and manage Xerox[®] and non-Xerox devices in every new location. Plug into a new network, and X-MED automatically discovers available printers and provides status and capability information. Save a list of "favorite" printers for each location, store application print settings for use on any printer in any network, and greatly reduce mobile support calls to IT. Printers are automatically discovered Printer list can be managed based on location Gives Bi-directional feedback device status, supplies, queue management 	
Xerox® Global Print Driver® (X-GPD)	A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non-Xerox devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management. • Printers are automatically discovered • Printer list can be managed based on location • Gives Bi-directional feedback device status, supplies, queue management	
Accounting		
Xerox Standard Accountin	ng (Requires Productivity Kit)	
Tracking	Print usage	
Accounting	Up to 9,999 User accounts (User ID); Up to 9,999 Group accounts (Department)	
Features	Enable/disable via the web UI or the front panel interface. Admin can manage the feature remotely via the web UI, Data can be exported via a CSV file, user required to enter XSA ID into the print driver when submitting a print job, similar to secure print.	

Security		
Security Features	IPsec 802.1X authentication Secure HTTPS (SSL) IPv6 compatibility SNMPv3 IP Filtering Secure Print Removable hard drive Image Overwrite Port Control	
Device Management		
Xerox CentreWare® Web		
	 A Web-based server application for network administrators that permits web browser-based device management from any workstation, whether running Windows or UNIX or any other operating system Works with any SNMP-managed printer from any manufacturer Provides help with device discovery and installations, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management 	
Xerox [®] CentreWare [®] Inte	rnet Services - Integrated Device Web Page	
Device Status	Web server embedded • Tray status/contents • Consumables status	
Print Queue Viewing	Complete job print queue management—hold, release, promote and delete	
Job Submission	Print-ready files (PS, PCL, TIFF, PDF) Output feature selection (requires Productivity Kit)	
Device Administration	Allows simple, remote installation setting of configuration options and management of the device	
Browsers	Microsoft® Internet Explorer 7 Firefox® version 4 and above	
Xerox [®] Mobile Solutions		
Xerox® PrintBack	PrintBack takes the capabilities of the printer you already use, and extends them beyond your computer and out to your Apple iOS- or Android-based mobile device. When you're working offsite or away from your desk and receive an important document via your mobile device, simply use PrintBack to print it with your default printer back at your office or desk. Plus, it supports the most common office file types (Microsoft® Office documents, PDF, etc.) with uncompromised print quality. Download from iTunes or Android Marketplace.	
Xerox® Mobile Express Driver	The Xerox® Mobile Express Driver is a single, universal printer driver that can be downloaded to a PC and used to print to virtually any PostScript device on the network, including printers made by other manufacturers. Instead of downloading individual printer drivers for each product in each office, users can download the single, simple, Mobile Express Driver.	
Device Specifications		
Duty Cycle		
	Up to 52,000 pages per month ²	
Recommended Monthly F	Recommended Monthly Print Volume	
	Up to 8,000 pages per month ³	

² Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

³ Range reflects the number of pages per month the product can regularly print while maintaining optimal

performance (considering factors including supplies replenishment and reliability over the expected product life).

Power Consumption					
	110-127 VAC ±10%, 50/	60 Hz ± 3 % , 9.7A or less	220-240 VAC ±10%, 50	/60 Hz ± 3 % , 4.7A or less	
Printing (average operations)	<600 watts		<600 watts		
Standby	<75 watts		<75 watts		
Power save	<55 watts		<55 watts	<55 watts	
Sleep	<0.9 watts		<0.9 watts		
Warm up (from sleep)	<5 seconds				
Warm up (from power on)	As fast as 45 seconds				
Operating Temperature Range	41 to 89.6° F (5° to 32° C)				
Storage Temperature Range	32 to 95° F (0° to 35° C)				
Operating Humidity	15% to 85%				
Storage Humidity	15% to 80%				
Operating Altitude	Up to 3,100 meters				
Sound Pressure Levels					
Printing	<54 dB(A)				
Standby	<25 dB(A)				
Sound Power Levels					
Printing	<7.0 B(A)				
Standby	<4.3 B(A)				
Dimensions and Weights (Unpackaged)	Width	Depth	Height	Weight	
Base Unit	19.7 in. / 499.5 mm	21.2 in. / 538 mm	16 in. / 406 mm	97 lbs. / 44 kg	
550-sheet Feeder	19.7 in. / 499.5 mm	21.2 in. / 538 mm	6.4 in. / 163 mm	21.2 lbs. / 9.6 kg	
Dimensions and Weights (Packaged)	Width	Depth	Height	Weight	
Base Unit	25.9 in. / 659 mm	29.7 in. / 755 mm	26.9 in. / 683 mm	128.5 lbs. / 58.3 kg	
550-sheet Feeder	25.2 in. / 639 mm	26.1 in. / 663 mm	11.5 in. / 293 mm	29.1 lbs. / 13.2 kg	
Duplex Kit	11.6 in. / 295 mm	21.9 in. / 558 mm	9.9 in. / 251.5 mm	4.2 lbs. / 1.9 kg	
Certifications		·			
	EN 60950-1, 2nd Edition FCC Part 15, Class A	CSA 60950-1-07, 2nd Edition w Voltage Directive 2006/95/E /EC	C		

What Comes in the Box			
	Phaser 7100 Starter Toner Cartridges – One of each (Cyan, Magenta, Yellow: 3,000 print capacity; Black: 5,000 print capacity) ⁴ Imaging Drum – One of each (Cyan, Magenta, Yellow, Black: 24,000 print capacity) ⁵ Quick Use Guide Quick Install Guide Software and Documentation CD (with Drivers, User Manual, System Admin. Guide and Warranty Statement) Power cord		
Supplies and Options	Description	Order Number	
Standard-Capacity Toner	Cyan: 4,500 pages ⁴	106R02599	
Cartridges	Magenta: 4,500 pages ⁴	106R02600	
	Yellow: 4,500 pages ⁴	106R02601	
High-Capacity Toner	Black: 10,000 pages ⁴	106R02605	
Cartridges (Dual Pack)	Cyan: 9,000 pages ⁴	106R02602	
	Magenta: 9,000 pages ⁴	106R02603	
	Yellow: 9,000 pages ⁴	106R02604	
Routine Maintenance	Imaging Drum - CMY: Up to 24,000 pages⁵	108R01148	
Items	Imaging Drum: Up to 24,000 pages ⁵	108R01151	
	Waste Cartridge: Up to 24,000 pages ⁵	106R02624	
Options	550-sheet Feeder, Phaser 7100	097504485	
	Automatic 2-sided Printing Upgrade, Phaser 7100	097504486	
	System Cart with Storage Drawer	097S04245	
	1 GB Memory Upgrade	097504488	
	Productivity Kit wtih 40 GB Hard Disk Drive, Phaser 7100	097S04487	
	Wireless Network Adapter North American power converter Euro power converter UK power converter	097S03740 097S03741 097S03742	

⁴ Average standard pages. Declared Yield in accordance with ISO/IEC 19798. Yield will vary based on image, area coverage and print mode.

⁵ Average standard pages. Yield will vary depending on job run length, media size. orientation, area coverage and print mode.



©2012 Xerox Corporation. All rights reserved. Contents of this publication may not be reproduced in any form without permission of Xerox Corporation. XEROX®, XEROX and Design®, CentreWare® and Phaser® are trademarks of Xerox Corporation in the United States and/or other countries. Adobe® and PostScript® 3^{red} are registered trademarks or trademarks of Adobe Systems, Incorporated. PCL® is a registered trademark of Hewlett-Packard. As an ENERGY STAR® partner, Xerox Corporation has determined that this product meets the ENERGY STAR guidelines for energy efficiency. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. All other trademarks are the property of their respective manufacturers. The information in this brochure is subject to change without notice. 9/12