Overview

The HP Ethernet 1Gb 2-port 361FLB Adapter is a ProLiant c-Class BladeSystem FlexibleLOM network adapter with PCIe Gen 2.1 compliance providing two Gigabit Ethernet ports that utilizes only a maximum of 2.8 watts of power. The HP 361FLB is a 1Gb FlexibleLOM that has been designed for use with select HP BladeSystem c-Class Gen8 servers, featuring bridgeless Intel® Ethernet I350 Controller. 361FLB has performance enhancing features and new power management technologies. With the introduction of the 361FLB FlexibleLOM, ProLiant c-Class customers now have the choice and flexibility of choosing 1GbE solution that could pave the way for a future 10GbE upgrade. The 361FLB is ideal for virtualization, security, network segmentation, and other BladeSystem applications requiring 1GbE bandwidth.

Tested and proven to meet demanding BladeSystem standards, the 361FLB ships with the advanced server features that ProLiant customers have come to expect, such as support for failover and load balancing, TCP/IP checksum offloading, large send offloading, Wake-on-LAN, jumbo frames, PXE, VLAN tagging, Virtualization, advanced power management features, new I/O technologies, IEEE 1588 and much more.



HP Ethernet 1Gb 2-port 361FLB Adapter

Models

HP Ethernet 1Gb 2-port 361FLB Adapter

Kit contents

- HP Ethernet 1Gb 2-port 361FLB Adapter
- Quick install card
- Product warranty statement
- Drivers, user guide, and utilities via http://www.hp.com



652500-B21

Compatibility

HP ProLiant Server Support

- HP ProLiant BL420c Gen8
- HP ProLiant BL460c Gen8
- HP ProLiant BL465c Gen8
- BL ProLiant BL660c Gen8



HP Ethernet 1Gb 2-port 361FLB Adapter

QuickSpecs

Standard Features

Product Features	 Dual Gigabit Ethernet ports Maximum 2.8 watts power usage Supported on Select Gen8 ProLiant c-Class servers in FlexibleLOM slot Intel® Ethernet I350 controller Designed with server needs in mind: IEEE 802.1p, 802.1Q, 802.3, 802.3ad, and 802.3x, 1588, 802.1AS ProLiant Teaming including Network Fault Tolerance, Transmit Load Balancing, and Switch-Assisted Load Balancing Jumbo frames TCP/IP checksum offload (TCO) and large send offload (LSO) Interrupt/DMA coalescing PXE Wake-on-LAN (WOL) IPv6 packet transmit and receive (excluding all offload capabilities); IPv6 aware SNMPv1 agent for Windows 			
	Intel $^{\circ}$ Integrated I/O and Data Direct I/O for increased performance and reduced latency			
Performance				
Dual-port Gigabit Ethernet Throughput	Up to 1000 Mbps full duplex Ethernet transfer rate per port (2000 Mbps combined) delivers outstanding network performance that improves response time and removes bottlenecks across the entire network.			
Jumbo Frames	Jumbo frames (also known as extended frames) permit a 9.5K byte transmission unit (MTU), which is six times the size of standard 1500 byte Ethernet frame. The 361FLB supports jumbo frames as a way to achieve higher throughput and better CPU utilization. Jumbo frames are particularly useful for database transfers and tape backups.			
802.1Q VLANs with 802.1p QoS Tagging	IEEE 802.1Q virtual local area network (VLAN) protocol allows each physical port of the 361FLB to be separated into multiple virtual NICs for added network segmentation and enhanced security and performance. VLANs increase security by isolating traffic between users. Limiting the broadcast traffic to within the same VLAN domain also improves performance. IEEE quality of service (QoS) 802.1p tagging allows the adapter to mark or tag frames with a priority level across a QoS-aware network for improved traffic flow.			
TCP/IP Stateless	For overall improved system response, the 366M supports standard TCP/IP offloading techniques including:			
Offloading	 TCP/IP checksum offload (TCO) moves the TCP and IP checksum offloading from the CPU to the network adapter. Large send offload (LSO) or TCP segmentation offload (TSO) allows the TCP segmentation to be handled by the adapter rather than the CPU. 			
Interrupt Coalescence	Interrupt coalescing (interrupt moderation) groups multiple packets, thereby reducing the number of interrupts sent to the host. This process optimizes host efficiency, leaving the CPU available for other duties.			
DMA Coalescing	Supports DMA Coalescing, the incoming data packets and interrupts associated with these DMA calls are intelligently batched to keep the system devices in lower power states.			
Intel® Integrated I/O with Data Direct I/O	New on HP ProLiant Gen8 servers, Intel® Integrated I/O features reduces memory access from I/O on local socket which speeds up CPU data transfer and accelerates inbound and outbound traffic flows. Together, Integrated I/O and Data Direct I/O technologies reduce system power, increases I/O performance and reduced I/O latency.			



I/O Virtualization support for VMware NetQueue, Microsoft VMQ and Intel's Virtualization Machine Device Queues(VMDq) help meet the performance demands of consolidated virtual workloads.			
Compliant with Single-Root I/O Virtualization (SR-IOV), accommodating multiple Virtual Machines (VMs) to share single PCIe resources. The device is capable of SR-IOV, and requires Firmware, Software and OS support			
Support hardware-enabled IEEE 1588, a standard that defines PTP (Precision Time Protocol), a high- precision time protocol for clock synchronization used in measurement and control systems.			
Support for HP Sea of Sensors 3D Technology which is a collection of 32 sensors that automatically track thermal activity - heat - across the server. When temperatures get too high, sensors can kick on fans and make other adjustments to reduce energy usage. What makes it better is the upgrade from all six fans kicking on at one time to a new system where only one kicks on - the one in proximity of the area that started heating up - thus reducing the amount of energy used for cooling.			
Support for pre-boot execution environment (PXE) enables automatic deployment of computing resources remotely from anywhere. It allows a new or existing server to boot over the network and download software, including the operating system, from a management/ deployment server at another location on the network. Additionally, PXE enables decentralized software distribution and remote troubleshooting and repairs.			
With multiple quad port adapters supported per server connected to up to two redundant pairs of interconnect modules per enclosure, a very wide variety of high availability I/O configurations are possible.			
ProLiant Network Adapter Teaming provides fault tolerance and load balancing across a team of two or more network adapters. The team of adapters works together as a single virtual adapter. Support for several different types of teaming is included. Teaming offers IT professionals an easy, efficient, and co effective way to provide network fault tolerance and increased network bandwidth. For more information refer to the ProLiant Network Adapter Teaming Whitepaper available at: ftp://ftp.compaq.com/pub/products/servers/networking/TeamingWP.pdf			
HP branded hardware options qualified for BladeSystem c-Class and p-Class servers are covered by a global limited warranty and supported by HP Services and a worldwide network of HP Authorized Channel Partners. The HP branded hardware option diagnostic support and repair is available for one year from date of purchase, or the length of the server they are attached to, whichever is greater. Support for software and initial setup is available for 90 days from date of purchase. Additional support may be covered under the warranty or available for an additional fee. Enhancements to warranty services are available through HP Care Pack services or customized service agreements.			



Service and Support

Service and Support

HP Care Pack Services: Packaged server and storage services for increased uptime, productivity and ROI

When you buy HP server and storage products and solutions, it's also a good time to think about what levels of support you may need. Our portfolio of service options reduce deployment and management worries while helping you get the most out of your server and storage investments. We take a holistic approach to your environment, bridging servers, blades, storage, software and network infrastructures with our packaged HP Care Pack Services for servers and storage.

Protect your business beyond warranty

When it comes to robustness and reliability, standard computing equipment warranties have matured along with technology. Good news that can also create problems stemming from depending on standard warranties designed to only protect against product defects and some downtime causes. Using a standard approach to warranty uplifts, such as HP Care Pack Services, helps reduce downtime risks and provides operational consistency for mission-critical and standard business computing.

HP Care Pack Services: Upgrading or extending standard server and storage warranties cost effectively

HP Care Pack Services offer a standard reactive hardware and software support services suite sold separately, or combined with our Support Plus and Support Plus 24 services. The portfolio also provides a combination of integrated proactive and reactive services, such as Proactive 24 Service and Critical Service. In addition with HP Proactive Select, you can acquire the specific proactive constancy and technical services. HP Proactive Select menu offers a broad set of service options that you can mix and match depending on your specific requirements. Proactive service options include offers for server, storage, network, SAN device, software, environment, and education services.

HP server and storage lifecycle support services offer a full spectrum of customer care-from technology support to complex migrations to complete managed services. HP Factory Express provides customization, integration and deployment services for turnkey solutions. HP Education Services offer flexible, comprehensive training on to help your IT staff get the most out of your server and storage investments. HP Financial solutions extend innovative financing and cost-effective asset management programs-from purchase to equipment retirement.

Learn more: www.hp.com/services/servers and www.hp.com/services/storage

NOTE: Care Pack Services availability may vary by product and country.

HP Care Pack Services are sold by HP and HP Authorized Service Partners:

- Services for customers purchasing from HP or an enterprise reseller are quoted using HP order configuration tools.
- Customers purchasing from a commercial reseller can find HP Care Pack Services at http://www.hp.com/go/lookuptool



Service and Support

Recommended HP Care Pack Services for optimal satisfaction with your HP product

Recommended Services Hardware Options Support

HP Care Packs provide support for all HP-branded hardware options qualified for inclusion in your server or storage solution. Any additional HP-qualified options installed within the server are covered at the same service level and for the same period as the server and no additional cost.

- Help improve or maintain system uptime
- Convenient onsite support
- Committed response time

http://h20195.www2.hp.com/V2/GetPDF.aspx/5982-6547EEE.pdf

3-Year HP Hardware Support Onsite Service, 4-hour response, 24x7

Provides you with rapid remote support and if required an HP authorized representative who will arrive on site any time and day of the year to begin hardware maintenance service within 4 hours of the service request being logged.

This service provides a trained HP service specialist to perform an installation that meets HP quality standards, for:

- Help improve or maintain system uptime
- Convenient onsite support
- Committed response time

http://h20195.www2.hp.com/V2/GetPDF.aspx/5982-6547EEE.pdf

HP Installation and Startup of HP ProLiant Servers

Provides for the installation of your new HP ProLiant server and operating system to assist you in bringing your new HP ProLiant server and operating system into operation in a timely and professional manner.

This service provides a trained HP service specialist to perform an installation that meets HP quality standards, for:

- Delivery of the service at a mutually scheduled time convenient to your organization
- Availability of an HP service specialist to answer basic questions during the onsite delivery of this service
- Custom installation as detailed in "Delivery specifications" or in a Statement of Work (SOW)
- Verification prior to installation that all service prerequisites are met

http://h20195.www2.hp.com/V2/GetPDF.aspx/5982-7572ENN.pdf



Service and Support

Optional HP Care Pack Services that will enhance your HP product experience

Optional Services

3-Year HP Hardware Support Onsite Call-to-Repair (CTR) Service, 6- or 24-hour

As an alternative to our recommended support level, for customers who need committed call-to-repair for server hardware.

Provides your IT manager with a team of support specialists who will quickly begin troubleshooting the system to help return the hardware to operating condition within 6 or 24 hours of the initial service request to the HP Global Solution Center.

http://h20195.www2.hp.com/V2/GetPDF.aspx/5982-6547EN.pdf

3-Year HP Support Plus 24

As an alternative to our recommended support level, for customers who need access to responsive 24x7 hardware and software support plus software updates on HP and selected third party products:

For a higher return on your server and storage technology, our 3-year combined reactive support service delivers integrated onsite hardware/software support services available 24x7x365, including access to HP technical resources, 4-hour response onsite hardware support and software updates.

http://h20195.www2.hp.com/V2/GetPDF.aspx/5981-6638EEE

HP Proactive Select Service

Customer needs on demand access to consulting, technical proactive services and education courses

Provides a flexible way to purchase HP best-in-class consultancy and technical services. You can buy Proactive Select Service Credits when you purchase your hardware and then use the credits over the next 12 months.

http://h20195.www2.hp.com/V2/GetPDF.aspx/4AA2-3842ENN.pdf

eSupport

HP eSupport is a portfolio of technology-based services that assist you with managing your business environment - from the desktop to the data center.

Support Portal

The HP support portal provides one-stop access to the information, tools and services you need to manage the daily operations of your IT environment.

Features include:

- Access to self-solve tools (including search technical knowledge base)
- Efficient logging and tracking of support cases
- Collaboration with other business and IT professionals
- Download of patches and drivers
- Access to diagnostic tools
- Proactive notification of relevant information

Access to certain features of the support portal requires an HP service agreement. To access the support portal, visit: http://www.hp.com/support



Service and Support		
	HP Insight Remote Support software delivers secure remote support for your HP Servers and Storage, 24 X 7, so you can spend less time solving problems and more time focused on your business. You can have your systems remotely monitored for hardware failure using secure technology that's been proven at thousands of companies around the world. In many cases, you can avoid problems before they occur.	
Customer Technical Training	In today's cost-conscious business environment, IT professionals, developers, consultants and users face an interesting challenge: how to keep up with the latest technologies and expand important skills while delivering profitable results on current projects. To help address this challenge, HP offers innovative training solutions that help keep you up-to-date on virtualization, server, storage, Insight Control, Citrix, Microsoft [®] and open source/Linux-related topics-while spending less time away from business-critical activities.	
HP Services Awards	HP Technology Services continues to be recognized for service and support excellence by customers partners, industry organizations and publications around the world. Recent honors and award reflect services team's dedications, technical expertise, professionalism and uncompromising commitment customer satisfaction.	
Additional Services Information	To learn more on HP ProLiant servers, HP BladeSystem servers and HP storage products, please contact your HP sales representative or HP Authorized Channel Partner. Or visit: www.hp.com/services/proliant or www.hp.com/services/bladesystem or http://www.hp.com/services/storage	

Related Options

c-Class BladeSystem	NOTE: This is a list of supported options. Some may be discontinued.			
Interconnect Modules	HP 6125XLG Ethernet Blade Switch	711307-B21		
	HP Virtual Connect Flex-10 10Gb Ethernet Module for c-Class BladeSystem	455880-B21		
	HP 1:10Gb Ethernet Blade Switch for c-Class BladeSystem	438031-B21		
	HP 1/10Gb-F Virtual Connect Ethernet Module for c-Class BladeSystem	447047-B21		
	Cisco Catalyst Blade Switch 3020 for HP c-Class BladeSystem	410916-B21		
	Cisco Catalyst 1GbE 3120G Blade Switch	451438-B21		
	Cisco Catalyst 1/10GbE 3120X Blade Switch	451439-B21		
	HP GbE2c Layer 2/3 Ethernet Blade Switch	438030-B21		
	HP 1GB Ethernet Pass-Thru Module for c-Class BladeSystem	406740-B21		
	HP 6120XG Blade Switch	516733-B21		
	HP 6120G/XG Ethernet Blade Switch	498358-B21		
	HP Cisco B22HP Fabric Extender for BladeSystem c-Class	641146-B21		
	HP Cisco B22HP Fabric Extender with 16 FET for BladeSystem c-Class	657787-B21		



Technical Specifications

General Specifications	Network controller	Intel® Ethernet I350 Con	troller	
	Data rate	Two ports, each at 1000 Mbps full duplex (theoretical maximum) NOTE: The 361FLB adapter transmits from the server at only 1 Gbps full duplex per port.		
	Bus type	x4 PCI Express 2.1		
	Form factor	·	ompatible with all Gen8 ProLiant c-Class server slots	
	IEEE Compliance	802.1p, 802.1Q, 802.3, 802.3ad, and 802.3x, IEEE1588, 802.1AS		
Power and Environmental	Operating	Temperature	50° - 95° F (10° - 35° C)	
Specifications		Humidity	10% to 90% non-condensing	
	Non-operating	Temperature	-40° to 158° F (-40° to 70° C)	
		Humidity	5% to 95% non-condensing	
	Power requirement	Maximum Watts	2.7W typical / 2.8W maximum 1.2W for Wake on LAN support	
	Emissions	FCC Class A		
	Agency Approvals	USA	FCC (CFR 47 part 15) and UL 60950	
		Canada	CSA60950	
		Japan	VCCI	
		Korea	MIC (RRL), EMC Registration	
		Australia	ACA, AS/NZS3548/EN55022:1998, EN55024:1998	
		European Union	EN55022:1998 (CISPR 22), EN55024:1998, and IEC60950:1999 (EN60950:2000)	
	RoHS Compliance	6 of 6		
	Safety	UL Mark (USA and Canada)		
		CE Mark		
		EN 60590		
Operating System Support	 Microsoft Windows Server 2008 Microsoft Windows HPC Server 2008 Red Hat Enterprise Linux 5.7, 6.1 SUSE Linux Enterprise Server Solaris 10 VMware ESX/ESXi 4.1u2 and ESXi 5.0u1 Citrix Xenserver 6.0 Microsoft Windows Hyper-V NOTE: For more operating system support & certification information, please visit http://h10018.www1.hp.com/wwsolutions/index.html.			



Technical Specifications

Environment-friendly Products and Approach	End-of-life Management and Recycling	Hewlett-Packard offers end-of-life HP product return, trade-in, and recycling programs in many geographic areas. For trade-in information, please go to: http://www.hp.com/go/green. To recycle your product, please go to: http://www.hp.com/go/green or contact your nearest HP sales office. Products returned to HP will be recycled, recovered or disposed of in a responsible manner.
		The EU WEEE directive (2002/95/EC) requires manufacturers to provide treatment information for each product type for use by treatment facilities. This information (product disassembly instructions) is posted on the Hewlett Packard web site at: http://www.hp.com/go/green. These instructions may be used by recyclers and other WEEE treatment facilities as well as HP OEM customers who integrate and re-sell HP equipment.

© Copyright 2014 Hewlett-Packard Development Company, L.P.

The information contained herein is subject to change without notice.

Windows is a US registered trademark of Microsoft Corporation.

The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

