

## **Direct LED**

Super Narrow Bezel Display

Bezel Width : 3.2mm (left/top), 1.7mm (right/bottom)

▶ 47WV50BR-B

47" class (46.96" measured diagonally)



# Superb Picture Quality

#### NO BLACKENING DEFECT

Display has a built-in temperature control that adjusts to light and heat eliminating dark or blackened areas.



## TRUE WIDE VIEWING

AUTO CALIBRATION

Color changes and distortion are eliminated from any viewing angle.



WV Series provide Automatic Calibration solution

by adjusting the white balance on videowall easily.

which enables to save time and labor on installation

#### PANEL STABILITY

Minimized image distortion when external pressure is applied.



Normal

#### AUTO HIGHER RESOLUTION

IPS

WV50 supports Full HD. You can enjoy super fine image from each and every displays composing videowall.



### SLIMMER BEZEL

4.9mm, the slimmest bezels create powerful and impactful video walls.



Bezel to Bezel 4.9mm



≻∥⊲ Bezel to Bezel 6.3mm







Life's Good LGsolutions.com

# Direct LED

Super Narrow Bezel Display

Bezel Width : 3.2mm (left/top), 1.7mm (right/bottom)

41.1"



<u>₩∕</u>/Ψ ∎\_



47WV50BR-B

47" class (46.96" measured diagonally)

Model

			FEATURES	Temperature Sensor	Yes	
		1	Tile Mode	Yes		
				Tile Mode @ Natural Mode	Yes, Up to 15x15	
				Source Selection	Digital(HDMI/DVI) / DVI / Analog(RGB) / Component/USB	
			Brightness/Contrast /Backlight	Yes		
L			·	Position/Size	Yes	
D	k Pack Panel			Auto Config/Phrase	Yes	
				Language (OSD/USB Playback)	Korean, Chinese(Traditional), Chinese(Simplified), Japanese, Gerr English, French, Portuguese(Brazil), Portuguese(Europe), Spanis Italian, Russian, Swedish(Sweden), Finnish(Finland), Norwegian(Norway), Danish(Denmark), Dutch(Netherlands), Cheskey(Czech), Greek	
PANEL	Model		ENVIRONMENT CONDITIONS CABINET POWER	Language (CD Manual)	Korean, Chinese(Traditional), Chinese(Simplified), Japanese, Gerr English, French, Portuguese(Brazil), Portuguese(Europe), Spanis Italian, Russian, Swedish(Sweden), Finnish(Finland), Norwegian(Norway), Danish(Denmark), Dutch(Netherlands), Cheskey(Czech), Greek	
	Panel Size	47" class (46.96" measured diagonally)		ISM Method	Normal, Orbiter, Inversion, White Wash	
	Panel Technology Aspect Ratio	IPS 16:9		Advanced	Clear White, Dynamic Contrast, Dynamic Color, Noise Reduct Gamma, Black Level, Skin color, Digital Noise Reduction	
	Native Resolution	1920 x 1080 (FHD)		Time	Clock, On/off Time, Sleep Timer, Power on Delay	
	Pixels (H x V x 3)	6,220,800		Information Display	Model/Type, Serial Number, S/W Version, IP Address, Homepag	
	Brightness	500 cd/m <sup>2</sup>		Input Label	Yes	
	Contrast Ratio (Typ.)	1,400:1		Auto Power/Source Memory	Yes	
	Dynamic CR (DCR)	500,000 : 1		DPM Select	Yes (Installation Menu)	
	Color Gamut	68%		Energy Saving	Yes, Off /Minumum/Medium/Maximum/Screen Off	
	Viewing Angle	178°/178°		Smart Energy	Yes	
	Color Depth	1.06 Billion (10-bit)		Saving		
	Response Time	12ms (Typical)		File Play with USB	Yes	
	Surface Treatment	Hard coating(3H), Anti-reflection treatment of the front polarizer (Reflectance (2%)		Operation Tempature Operation Humidity	0°C ~ 40°C 10% ~ 90%	
	Orientation	Portrait and Landscape		Color	Black	
VIDEO	Max Input Resolution	1920 X 1080@ 60Hz(RGB, HDMI, DVI-D, Display Port)		Bezel Width	3.2mm (left/top), 1.7mm (right/bottom)	
	Rec. Resolution	1920 X 1080@ 60Hz(RGB, HDMI, DVI-D, Display Port)		Monitor Dimension	41.1" x 23.2" x 3.5"	
	H-Scanning Freq.	30 ~ 83kHz(RGB, HDMI, DVI-D, Display Port)		Monitor Weight	40.8 lbs.	
	V-Scanning Freq.	56~75Hz(RGB) / 56~60 Hz(HDMI, DVI-D, Display Port)		Carton Dimensions	46.5" x 30.3" x 6.5"	
	Pixel Frequency	148.5MHz(RGB, HDMI, DVI-D, Display Port)		Packed Weight	51.8 lbs.	
	Sync Compatability	Separate, Composite, Digital		Handle	Yes	
	Video Input	RGB, HDMI, DVI-D, AV, Component, Display Port		VESA <sup>™</sup> Standard Mount Interface	600mm x 400mm	
	Picture mode	Vivid, Standard, Cinema, Sports, Game		Power Supply	100-240V~, 50/60Hz	
	Color temperature	Warm/Medium/Cool		Power Type	Built-in Power	
INPUT (Rear) OUTPUT	Digital	DVI-D(1), HDMI(1) with HDCP for all input, Display Port(1)		Power Consumption		
	Analog	RGB(1), Component(RGB Shared), AV(BNC, 1)		Typical	150W	
	Audio	PC Audio In(1), AV/Component Audio In(RCA, 1)	STANDARD CERTIFICATIONS	Smart Energy Saving	80W	
	External Control	RS232C(1), RJ45(1), IR Receiver(1)		DPM	0.7W	
	USB	USB(1)		Power Off	0.5W	
(Rear)	Digital	DVI-D(1)		Safety	UL / cUL / CB / TUV / KC	
	Analog Audio	RGB(1)		EMC	FCC Class "B" / CE / KCC	
	External Control	External speaker(1) RS232C(1)		Erp/Energy Star 6.0	Yes / Yes	
AUDIO	Balance	KSZ3ZC(1) Yes				
	Audio Power	tes 20W (10W × 2)	MEDIA PLAYER COMPATIBLITY		External Media player Attatchable	
	Speaker On/off	2000 (1000 x 2) Yes	SOFTWARE		Supersign Compatibility: Elite-s	
	Clear Voice II	Yes				
	Sound Mode	Standard, Music, Cinema, Sports, Game	WARRANTY UPC		3-Year Limited Warranty (Parts/Labor/Backlight) 7 19192 19268 3	
				Domoto Controllo		

┛╹♥҈╲᠁

Remote Controller, Power cable, DVI Cable, Manual, IR Receiver, RS-232C Cable, Guide Bracket, Screw





LG Electronics U.S.A., Inc. HE B2B Division 2000 Millbrook Drive Lincolnshire, IL 60069

Customer Service: 888.865.3026 www.LGsolutions.com/support

Contact your LG Regional Sales Representative Channel: 800.897.8871 Hospitality: 800.228.1236 E-mail: info@LGsolutions.com

All screen images are simulated. Dimensions and weights are approximate. Design, specifications, and features subject to change without notice.

**NIPS** 

© Copyright 2014 LG Electronics USA, Inc. All Rights Reserved. "LG Life's Good" is a registered trademark of LG Corp.

ENERGY STAR is a registered trademark of the U.S. Environmental Protection Agency. In Plane Switching is a trademark of LG Philips LCD Ltd. VESA is a trademark of Video Electronics Standards Association. HDMI, the HDMI logo and High-Definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing LLC.

All other product and brand names are trademarks or registered trademarks of their respective companies

SPEC\_47WV50BR\_B\_111310\_PR

Printed in the USA. February 2014

нат

ULLHD