A4

🔇 КУОСЕRа

Compact, Yet Powerful

The ECOSYS PA4500x is a powerful printer embedded with high-level security features. The rapid speed of up to 45 pages per minute contributes to the enhanced productivity of smaller workgroups. Thanks to long-life components and low energy consumption, it leaves a smaller environmental footprint.

+ + + + + +	· · · · · · ·	+ + +
		+ Pady to print. PL_A4 *bajA4 Status Torser 3 +
		ECOSYS PA4500x
+		
ECOSYS PA4500x		
A4 Monochrome printer		
Up to 45 pages A4 per minute		
1200 x 1200 dpi resolution		

GENERAL

KYOCERA ECOSYS Laser Monochrome Printer Operation panel: LCD 21 characters, 5 lines Type: Desktop Engine speed: Up to 45 pages A4 per minute;

Duplex print speed: 22.5 page per minute, A4 Resolution: 1,200 x 1,200 dpi Recommended Print Volume': 20,000 pages per month.

Maximum Print Volume1: 150,000 pages per month. Maximum Life¹: 900,000 pages or 5 years. Warm-up time: Approx. 16 seconds or less. Time to first print: Approx. 5.3 seconds or less. CPU: ARM Cortex-A53 Dual core 1.4GHz Memory: Standard 512MB; Max. 2.5GB (optional) **Standard interfaces:** Standard interface: USB 2.0 (Hi-Speed), 2 x USB Host Interface, Gigabit Ethernet (10BaseT/100BaseTX/1000BaseT), optional Wireless LAN (IEEE 802.11b/g/n), 2 eKUIO slots for optional internal print server or SSD hard disc, Slot for optional SD/SDHC Card. Integrated accounting: 100 department codes. Dimensions (W x D x H): Without packaging: 380 x 410 x 285 mm (without protrusions); 390 x 416 x 308 mm (with protrusions); With packaging: 549 x 494 x 420 mm Weight: Without packaging: Approx. 14.6kg with bundled toner. With packaging: 18.5 kg Power source: AC 220 ~ 240 V, 50/60 Hz Power consumption: Printing: 605.5 W Ready mode: 8.4 W Sleep-mode: 0.5 W Noise (sound pressure level: ISO 7779/ISO 9296): Printing: 54 dB (A) Stand-by: 30 dB (A) Safety standards: TÜV/GS. CE This unit is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard.

PAPER HANDLING

All paper capacities quoted are based on paper thickness of max. 0.11 mm. Please use paper recommended by KYOCERA under normal environmental conditions. **Input capacity:** Multi-purpose tray: 100 sheets, 60 to 220 g/m², A4, A5, B5, Letter, Legal, Folio, Custom (140 x 210 to 216 x 326 mm). Banner paper up to 915 mm. Standard universal paper cassette: 500 sheet, 60–120 g/m², A4, A5, B5, Letter, Legal, Folio, Custom (140 x 210 to 216 x 336 mm). Max. input capacity with options: 2,600 sheets. **Duplex:** Standard duplex unit, 60 to 120 g/m², A4, A5, B5, Letter, Legal, Custom (140x 210 mm - 216 x 356 mm). **Output capacity:** 250-sheet-face-down with paper full sensor.

PRINT FUNCTIONS

Controller language: PRESCRIBE Emulations: PCL6 (5e/XL), KPDL3 (PostScript 3 compatible), PDF Direct Print, XPS Direct Print and Open XPS, PPML, TIFF/IPEG Direct Print Support, URF, PWG Raster, PCLm, IBM Proprinter, Line Printer, Epson LO-850. Operating systems: All current Windows operating systems, MAC OS X Version 10.9 or higher, Chrome OS, Linux, as well as other operating systems on request. Fonts/barcodes: 93 outline fonts (PCL6, KPDL3), 4 fonts (Calibri), 4 fonts (Cambria), 1 Bitmap font, 45 types of one-dimensional barcodes, 1 type of two-dimensional barcode (PDF417). Print features: PDF Direct Print, Internet printing IPP 1.0, E-mail printing, WSD print, secure printing IPP over TLS, Local and network authentication, Network data encryption IPsec, HTTPS, LDAP over TLS, SNMP3, SMTP over TLS, POP over TLS, Encrypted PDF Direct Print, Universal Print, Printing for Chrome OS. Mobile printing support: KYOCERA Mobile Print app for iOS and Android, AirPrint, Mopria, Wi-Fi Direct.

CONSUMABLES

Average continuous toner yield in accordance with ISO/IEC 19752. **TK-3400 Toner Kit:** Microfine toner black for 12,500 pages A4. Capacity of starter toner is 6,000 pages A4.

OPTIONS

PF-3110 Paper feeder (max. 4 units): Max. 500 sheets, 60 - 120 g/m²; A4, A5, B5, Letter, Legal, Curter (02 + 142 mm - 216 + 256 mm)

Custom (92 x 162 mm - 216 x 356 mm) **PF-3100 Bulk paper feeder and PB-325 Printer base:** Max. 2,000 sheets, 60 - 220 g/m²; A4, A5, B5, Letter, Custom (76 x 148 to 216 x 305 mm); not to be combined with PF-3110 **CB-360W-B Cabinet:** Wooden desk with storage

capacity, Approx. 380 x 411 x 508 mm (WxDxH) CB-365W-B Cabinet: Wooden desk with storage capacity, Approx. 380 x 411 x 254 mm (WxDxH) CA-3100 Caster Unit: for increased stability. Mandatory when installing 4 optional paper feeders. Memory upgrade: MM-21(2GB)/MM-20(1GB), DP3 144-in DMM.

DDR3-144pin DIMM Storage Devices for easy document management: HD-17 SSD hard disk: 64GB HD-18 SSD hard disk: 256GB HD-19 SSD bard disk: 517GB

SECURITY

UG-33: ThinPrint support UG-50: TPM (Trusted Platform Module) USB IC Card Reader + Card Authentication Kit (B): Support for various authentication keys available. The card holder is standard. Optional interface: IB-32 B: IEEE1284 interface

IB-37: Wireless LAN (802.11b/g/n, 2.4-GHz and 5-GHz) with Wi-Fi Direct IB-38: Wireless LAN (802.11b/g/n, 2.4-GHz)

with Wi-Fi Direct **IB-50:** Gigabit-Ethernet board 10 BaseT/100 BaseTX/1,000 BaseT

IB-51: Wireless LAN Interface (802.11b/g/n)

WARRANTY

1-year warranty as standard **. KYOCERA guarantees the drum and developer for 3 years or 300,000 pages (whichever occurs sooner), provided each device is used and cleaned in accordance with the service instructions.

KYOCERA LIFE

Up to 5-year on-site warranty extensions available for product and options.

WHAT'S IN THE BOX:

Main unit, pre-installed starter toner, waste toner box, user documents, power supply cord.

¹The device is not designed to achieve the specified volumes in continuous operation.

ECOSYS stands for ECOlogy, ECOnomy and SYStem printing. With their long-life components, ECOSYS devices are designed to maximise durability and minimise the total cost of ownership with regard to maintenance, administration and consumables. The cartridge-free system means that only the toner has to be replaced regularly. The modular design concept allows you to add workflowenhancing functions as required. Integrated system software provides long-term crossnetwork compatibility. KYOCERA's long-life components cost you and the environment less.





KYOCERA Document Solutions Europe B.V. Beechavenue 27, 1119 RA, Schiphol-Rijk Tel +31 (0) 20-654-0000 — Fax +31 (0) 20-653-1256 www.kyoceradocumentsolutions.eu — info@deu.kyocera.com



moorio

* KYOCERA Document Solutions does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press.

All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged. ** Depending on the country kyoceradocumentsolutions.eu

KYOCERA Document Solutions Partner

NOV2022ECOSYSPA4500x/VER1.0