

IPS Edge LED

Full HD Open Frame Monitor

▶ 47WX50MF-B

47" class (46.9" measured diagonally)



Features

Rental & Staging Systems Awards showcase the most innovative commercial AV products. LG's 47-inch class Outdoor Display (47WX50MF-B) was named the winner for the "Best Flat Panel Display" category. With LG's In-Plane Switching (IPS) technology, blacking defect free up to 230 degrees Fahrenheit and Shine Out™ technology, which is designed to deflect ambient light, making it a well-suited solution for delivering messages in outdoor spaces. It also equipped with Circular Polarization which means that it will not appear black when viewed with polarized sunglasses when the unit is in portrait mode.

Specifications

Native Display Resolution 1,920 × 1,080 (FHD)

High Brightness 2000 cd/m²

Contrast Ratio 1,300: 1 (Typical) 500,000:1 (DCR)

178° Viewing Angle

Viewing Angle and Life Expectancy Portrait and Landscape Mode

RJ-45 LAN Control

Display Port, HDMI and DVI Connection

RS-232C Control

Convenient External Speaker-Out

Split Zoom (self video wall) Up to 15 x 15 matrix - adjusts for bezel width

Bezel Width (11mm)

USB Playback

Auto Brightness Sensor

Temperature Sensor

PIP/PBP

*Conditional 3-Year Limited Warranty Parts/Labor/Backlight



IPS Edge LED

Full HD Open Frame Monitor





47" class (46.9" measured diagonally)

• • •	42.2"		AUDIO	Model	47WX50MF-B	
	· · · ·			Balance	Yes	
				Audio Power	20W (10W x 2)	
				Speaker On/off	Yes	
				Clear Voice II	Yes	
				Sound mode	Standard, Music, Cinema, Sports, Game	
			CABINET	Bezel Width	11 mm	
Rear Jack Panel				Monitor Dimensions	42.2" x 26.2" x 6.2" (W x H x D)	
				Monitor Weight	52.7 lbs	
				Carton Dimensions	46.5" x 29.2" x 10.6" (W x H x D)	
				Packed Weight	64.2 lbs (Head Only)	
				Handle	Yes	
PANEL	Model	47WX50MF-B		VESA™ Standard Mount Interface	N/A	
	Panel Size	47" (46.9" measured diagonally)	SPECIAL FEATURES	Shine-Out Film	Yes	
	Panel Type	IPS				
	Aspect Ratio	16:9		Circular Polarization	Yes	
	Native Resolution	1,920 × 1,080 (FHD)		Temperature Sensor	Yes	
	Brightness (Typ)	2000 cd/m ²		Auto Brightness	Yes	
	Contrast Ratio	1,300:1 (Typ.), 500,000 (DCR)		sensor Cooling FAN	Yes	
	Color gamut	72%		Multi-media		
	Tni	110°C		playback	Yes	
		178°/178°		PIP/PBP	Yes	
	Viewing Angle	,		Tile mode	Yes (Up to 15 x15)	
	Color Depth	1.07 Billion		Image Zoom	Yes	
	Response Time	10ms (G to G), 8ms (G to G, WOT)		Source Selection	Yes (AV, Component, RGB, Display Port, DVI, HDMI, US	
	Surface Treatment	Hard coating(3H), Anti-Reflection treatment (Reflectance <2%)		Auto Power/Source Memory	Yes	
	Lifetime	50,000 Hrs		ISM Method	Yes	
	Orientation	Portrait & Landscape		Key Lock	Yes	
VIDEO (PC)	Max Input Resolution	1920 x 1080@ 60Hz (RGB,HDMI/DVI-D)		Smart Energy Saving	Yes	
	Recommended Resolution	1920 x 1080@ 60Hz (RGB,HDMI/DVI-D)				
	H-Scanning	30~68 kHz (RGB, HDMI/DVI-D)		File Play with USB	Yes	
	Frequency V-Scanning				0°C ~ 40°C	
	Frequency	56Hz~75Hz (RGB), 56Hz~63Hz (HDMI/DVI-D)		Operation Humidity	10% ~ 80%	
	Pixel Frequency	148.5 MHz (RGB, HDMI/DVI-D)	POWER	Power Supply	100 -240V~, 50/60Hz	
	Video Input	RGB, HDMI, DVI, Display Port		Power Consumption Typical/Smart		
	Picture mode	Vivid, Standard , Cinema, Sports, Game		Energy Saving on	240W(Max), 120W(SES)	
	Color temperature	Warm, Medium , Cool		DPMS	1.0W(Set Only)	
INPUT (REAR)	Digital	HDMI (1), DVI-D (1), Display Port (1) with HDCP for all input		Power Off	0.7W	
	Analog	Component (1), AV (1), RGB (1) (Shared with D-Sub)	STANDARD (CERTIFICATIONS)	Safety	UR / cUR / CB scheme / TUV-Type	
	Audio	PC/AV/Component Audio In (1)	MEDIA PLAYER COMPATIBILITY SOFTWARE COMPATIBILITY	EMC	FCC Class "A" / CE / KCC	
	External Control	RS232C (1), RJ45 (1)		Slot PC Compatible (optional)	No	
	USB	Yes (1)		Supersign	Elite-W / Elite-W lite	
	HDTV Formats	Component: 720p / 1080i / 1080p HDMI: 720P / 1080i / 1080p		Compatibility	Editing, Scheduling, Distribution & Play, Control	
(REAR)	Digital	DVI-D (1)	WARRANTY		Conditional 3 Year (parts/labor/backlight)	
	-		UPC Code		7 19192 19067 2	
	Analog	Component(1), Composite(1), RGB(1) (Shared with D-Sub)	ACCESSORIES	ACCESSORIES Remote Controller, Power Cable, VGA Cable, Manual * Conditional Warranty is covered when product is installed/used between 0 degree to 104 degree Fahrenheit		
	Audio	External speaker	* Conditional War			
	External Control	RS232C (1)				







LG Electronics U.S.A., Inc. HE B2B Division 2000 Millbrook Drive Lincolnshire, IL 60069

Customer Service: 888.865.3026 www.LGsolutions.com/support

Contact your LG Regional Sales Representative: Channel: 800.897.8871 Hospitality: 800.228.1236 E-mail: info@LGsolutions.com All screen images are simulated. Dimensions and weights are approximate. Design, specifications, and features subject to change without notice.

© Copyright 2013 LG Electronics USA, Inc. All Rights Reserved. "LG Life's Good" is a registered trademark of LG Corp.

ENERGY STAR is a registered trademark of the U.S. Environmental Protection Agency. In Plane Switching is a trademark of LG Philips LCD Ltd. VESA is a trademark of Video Electronics Standards Association. HDML the HDML log and High-Definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing LLC.

All other product and brand names are trademarks or registered trademarks of their respective companies

SPEC_47WX50MF_B_111305_PR