Technical Specifications

HP Z24n G3 WUXGA Display



1. Power button

Technical Specifications

HP Z24n G3 WUXGA Display



- 1. OSD control
- 2. Security cable slot
- 3. Master power switch
- 4. Power connector
- 5. HDMI port
- **6.** DisplayPort[™] connector

Back

- 7. DisplayPort[™] connector (out)
- 8. USB Type-B port (upstream)
- 9. USB port
- **10.** USB port (Battery charging 1.2, 7.5W)
- 11. USB Port
- 12. USB port (Battery charging 1.2, 7.5W)



Technical Specifications

(hp)

| | On Screen Controls | Brightness +, Color, Image, Input, Power, Menu, Management, Information, Exit |
|------------------------|--|--|
| | Display Management Software On Screen Display | HP Display Center Joystick |
| | Display Management Software | certified) HP Dicplay Contor |
| | Low Blue Light Mode | Yes, HP Eye Ease (TÜV Low Blue Light Hardware Solution |
| | Warranty (Number of Years) | 3/3/0 for LA, NA, EMEA, APJ; (3/3/3 in select APJ Countries) |
| | Detachable Stand | Yes |
| | Security Lock Ready | Standard Security Lock Slot |
| | VESA Mounting | 100 mm x 100 mm (bracket included) |
| | Height Adjust Range | 150mm |
| | Pivot | ±45 ±90 |
| | Swivel | ±45° |
| | Tilt | -5 to $+20^{\circ}$ |
| Monitor Specifications | Bezel Color | 4-sided Micro Edge (Head) Turbo Silver ; (Stand) Turbo Silver |
| | P3 D65 | 85% |
| Color | sRGB | 99 % |
| | Default Color Temperature | sRGB |
| | RGB Channel Adjust | Yes, Gain |
| Color Management | Factory Color Calibrated Calibrated Color Presets | Yes (Delta E <=2) sRGB, BT.709, (Color Match) |
| | Manufacturers; Actual Performance May Vary B | |
| | | The Typical Specifications Provided By HP's Component |
| | Panel Active Area (W X H) | 518.4(H)*324.0(V) |
| | Vertical Viewing Angle (Typical Cr>10) | 178° |
| | Cr>10) | 178° |
| | Horizontal Viewing Angle (Typical | 170° |
| | Response Time (Typical) | 5ms GtG (with overdrive) |
| | Haze | 25% |
| | Hardness | ЗН |
| | Screen Treatment | Anti-glare |
| | Backlight Type | Edge-lit |
| | Brightness - In Hours) | 30k |
| | Backlight Lamp Life Minimum (To Half | |
| | Pixel Pitch Pixels Per Inch (Ppi) | 96 PPI |
| | Pixel Pitch | 0.270mm |
| | Dynamic Contrast Ratio Flicker Free | Yes |
| | Contrast Ratio (Static) | 1000:1 10M:1 |
| | Brightness (Typical) | 350 nits |
| | Aspect Ratio | 16:10 |
| | Panel Bit Depth | 8 bit (6bit + FRC) |
| | Refresh Rate | 60 Hz |
| | Display Size (Diagonal) Panel Technology | IPS |

HP Z24n G3 WUXGA Display

QuickSpecs

Technical Specifications

| | Preset Graphic Modes/Suppored | 640 × 480@60Hz |
|-----------------------------|--|---|
| | Resolutions | 800 × 600@60Hz |
| | | 1024 × 768@60Hz |
| | | 1280 × 720@60Hz |
| | | 1280 × 800@60Hz |
| | | 1280 × 1024@60Hz |
| | | 1440 × 900@60Hz |
| | | 1600 × 900@60Hz |
| | | 1600 × 1200@60Hz |
| | | 1680 × 1050@60Hz |
| | | 1920 × 1080@60Hz |
| | | 1920 × 1200@60Hz |
| | High Definition Video Formats | 720 × 480p@60Hz |
| | | 720 × 576p@50Hz |
| | | 1280 × 720p@50Hz |
| | | 1280 × 720p@60Hz |
| | | 1920 × 1080p@50Hz |
| | | 1920 × 1080p@60Hz |
| | Minimum Vertical Scan Rate | 50 Hz |
| | Maximum Vertical Scan Rate | 60 Hz |
| | Minimum Horizontal Scan Rate | 30.0 kHz |
| | Maximum Horizontal Scan Rate | 75.0 kHz |
| | Maximum Pixel Clock | 170 MHz |
| | | 10 (English, Spanish, German, French, Italian, Netherlands, |
| | Languages | Portuguese, Japanese, T-Chinese and S-Chinese) |
| | | |
| Connector Types | DisplayPort™ | 1 DisplayPort™ 1.2 |
| | DisplayPort™ Out | 1 DisplayPort™ 1.2-out |
| | HDMI | 1 HDMI 1.4 |
| | USB- A | 4 USB-A 3.2 Gen1 (2 for battery charging 1.2, 7.5W) |
| | USB-B (Hub enablement) | 1 USB-B |
| | | |
| Special Features | DaisyChain/DisplayPort Multi stream | Yes |
| Specialicatales | Transport (MST) | |
| | User Updateable Firmware | Yes |
| | osci oputtuote i minute | |
| Power & Operating | Power Supply | Internal |
| Specs | Power Source | 100 – 240 VAC 50/60 Hz |
| | Power Consumption- MAX | 63 W |
| | Energy Saving/Stand By Mode | 0.5 W |
| | Power Consumption- Typical | 28 W |
| | Power Cable Length | 1.9m |
| | ···· J | |
| ENERGY STAR Data | Operational Mode at 100 VAC | 14.92 W |
| | Operational Mode at 115 VAC | 14.85 W |
| | Operational Mode at 230 VAC | 14.84 W |
| | • | |
| EU Energy Efficiency | On-mode Power Consumption (EC | 16.6 W |
| Class (Ec1062) | 1062/2010) | |
| • | Annual Power Consumption (EC | 25 kWh |
| | 1062/2010) | |
| | Energy Efficiency Class (EC 1062/2010) | A+ |
| | | |
| Operating Conditions | Operating Temperature - Celsius | 5° – 35°C |
| | Operating Temperature - Fahrenheit | 41° – 95°F |
| | Non-Operating Temperature - Celsius | –34° – 60°C |
| | | |



HP Z24n G3 WUXGA Display

QuickSpecs

Technical Specifications

| | Non-Operating Temperature - | 29° – 140°F | |
|---|---|--|---|
| | Fahrenheit Operating Humidity Non-Operating Humidity Operating Altitude Non-operating Altitude | 20 – 80% Relative Humidity 5 – 95% 0 – 5,000 m (16,400 ft.) 0 – 12.192 m (40,000 ft.) | (non-condensing) |
| Environmental Features and Certifications | Mercury-free LED display backlighting Arsenic-Free Display Glass Low Halogen | Yes, Mercury-free LED back Yes Yes WW application CE CB KC/KCC/NOM/PSB/EA | lighting C/GS/TUV-S/ISO 9241-307/ |
| | Agency Approvals And Certifications | | /CCC/CEL/CECP/SEPA/Energy |
| | Microsoft WHQL Certification | Yes | |
| | ENERGY STAR [®] Certified | Yes | |
| | EPEAT® Registered Regions need to verify by country | Yes | |
| | China Energy Label | CEL Grade 1 | |
| | TCO Certified Edge | Yes | |
| | TCO Certified | Yes | |
| | SmartWay Transport Partnership - NA only | Yes (NA sku) | |
| Contains Recycled Plastics | Contains Recycled Plastics | 81.07% | |
| | Recyclable Packaging (Box, packing materials) | 100% recyclable packaging | |
| Unit Product/Package Specifications | Product Dimensions (Unpacked with stand) (W x D x H) | 53.17 x 19.5 x 52.14 cm | 20.93 x 7.68 x 20.53 in |
| | Product Dimensions (Packed) (W x D x H) | 62.5 x 41.5 x 14.2 cm | 24.61 x 16.34 x 5.59 in |
| | Display Head Dimensions (Unpacked without stand) (W x D x H) Base Area Footprint | 53.17 x 3.85 x 34.29 cm | 20.93 x 1.52 x 13.5 in |
| | (w x d mm) | 232 X 195 mm | 9.13 X 7.7 in |
| | Bezel Measurements - Metric | Bottom Cover :521.33 mm | Bottom Cover :20.52 in |
| | Product Weight (Unpacked with stand) | 4.9 kg | 10.8 lb |
| | Product Weight (Packed) | 7.6 kg | 16.7 lb |
| | Product Weight (Head Only) | 3.7 kg | 8.2 lb |
| What's in the box? | Documentation kit DP1.4 Cable (1.8m) USB3.0 Type A to B (1.8m) Power cable VESA Adapter Cable Holder | | |
| User Guide and Warranty Languages | User Guide Languages | | T. Chinese, Czech, Danish, nan, Greek, Hungarian, Italian, Norwegian, Polish, Brazilian |





HP Z24n G3 WUXGA Display

Technical Specifications

Warranty Languages

Portuguese, Russian, Slovenian, Spanish, Swedish and Turkish.

English, Arabic, S. Chinese, T. Chinese, Czech, Danish, Dutch, Finnish, French, German, Greek, Hungarian, Italian, Japanese, Kazakh, Korean, Norwegian, Polish, Brazilian Portuguese, Russian, Slovenian, Spanish, Swedish and Turkish.



Technical Specifications

Copyright © 2021 HP Development Company, L.P.

The information contained herein is subject to change without notice. The only warranties for HP products are set forth in the express limited warranty statements accompanying such products. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein. Microsoft and Windows are registered trademarks or trademarks of Microsoft Corporation in the U.S. and/or other countries. ENERGY STAR is a registered trademark owned by the U.S. Environmental Protection Agency.



Summary

| Change Log | | | | | |
|------------------|----------|---------|--------------------------|--|--|
| | | | | | |
| January 12, 2021 | V1 to V2 | Updated | Technical Specifications | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |

