Overview



NOTE: To activate the OSD menu, touch the lower front bezel to the left of the power icon. The OSD icons will become illuminated and the OSD functions become active. The OSD icons will extinguish upon exit from the OSD or OSD timeout.

| 1. | Menu | Opens the On-Screen Display (OSD) main 4. OK menu. | | If the OSD menu is on, tap to select a menu item. If the OSD menu is inactive and the icons are illuminated, tap to activate the auto adjustment feature to optimize the screen image. |
|----|---------|--|--------------|--|
| 2. | - Minus | If the OSD menu is on, tap to navigate 5. backward through the OSD menu and decrease adjustment levels. If the OSD menu is inactive and the icons are illuminated, tap to open the OSD volume control menu and adjust the volume level. | Power LED | Green = Fully powered. Amber = Sleep mode. Flashing Amber = Sleep Timer mode. Off = Power is off or the LED has been suppressed in the OSD |
| 3. | + Plus | If the OSD menu is on, tap to navigate forward through the OSD menu and increase adjustment levels. If the OSD menu is inactive and the icons are illuminated, tap to activate the Source button that chooses the video signal input. | | Stand is not included and is sold separately. |



Overview

Model

HP L6010 10.4-inch Retail Monitor

A1X76AA

Introduction

The HP L6010 Monitor is a sleek, stylish and compact, head-only display specifically designed to be used with the HP Retail Point of Sale systems. The small size and industry standard VESA mount capability make it an ideal secondary customer-facing display for sharing engaging video and graphical content or as an operator display in space-constrained environments. DisplayPort, DVI-D, and VGA video inputs provide the highest degree of connection flexibility.

Key Benefits

- Industrial design to help protect the monitor in the most demanding retail and hospitality environments
- Compact space saving design to best fit your environment
- Industry-standard, 75mm VESA patterns enable flexible mounting in a variety of retail settings
- Flush-glass design provides an easy-to-clean surface
- Designed to work with HP Retail Point of Sale systems to deliver a complete retail solution
- Optional dual height adjustable stand (sold separately) provides two height settings and viewing angle flexibility that allows the display to be customized for your exact countertop work space



Technical Specifications

| Panel | Туре | 10.4-inch TN (Twisted Nematic) LED Backlit LCD |
|-----------------------|--|---|
| | Viewable Image Area (diagonal) | 26.4 cm (10.4 in) |
| | Aspect Ratio | 4:3 |
| | Viewing Angle (typ)* | 176 degrees horizontal/176 degrees vertical (10:1 minimum contrast ratio) |
| | Response Rate | 25 ms (typical) |
| | Brightness (typ)* | 300 nits (cd/m ²) |
| | Contrast Ratio (typ)* | 1000:1 |
| | Pixel Pitch | 0.206 mm |
| | Color Gamut | 57% |
| | | ations represent the typical specifications provided by HP's component formance may vary either higher or lower. |
| On Screen Display | Buttons or Switches | Menu, Minus, Plus, OK, Power |
| (OSD) Controls | Languages | English, French, German, Italian, Dutch, Spanish, Japanese, Portuguese, Traditional Chinese, and Simplified Chinese. |
| | User Controls | Brightness Contrast Color Temperature Image Control OSD Control Management Language Information Factory Reset Source Control Exit |
| Signal Interface/ | Horizontal Frequency | 24 to 83 kHz |
| Performance | Vertical Frequency | 50 to 76 Hz |
| | Graphics Controller | VESA standard timings/formats supported |
| | Native Resolution | 1024 x 768 @ 60 Hz (recommended) |
| | Preset VESA Graphic | 1024 x 768 @ 60 Hz |
| | Modes (non-interlaced) | 800 x 600 @ 60 Hz |
| | | 720 x 400 @ 70 Hz |
| | | 640 x 480 @ 60 Hz |
| | Maximum Pixel Clock Speed | 140 MHz |
| | User Programmable Modes | Yes, 10 |
| | Anti-Glare | Yes |
| | Anti-Static | Yes |
| | Default Color Temperature | Standard (6500K) |



Technical Specifications

| Video/Other Inputs | Plug and Play | Yes | |
|--------------------|---------------------------------|--|--|
| | Input Signal | (1) VGA; (1) DisplayPort and (1) DVI-D NOTE: HDCP supported on digital inp | |
| | Input Impedance | 75 ohms (2 % value change allowed) | |
| | Sync Input | TTL separate synch | |
| | Video Cables | (1) VGA; (1) DisplayPort and (1) DVI-D |) included |
| | Video Cable Length | 1,8 m (5.9 ft.) | |
| | USB 2.0 | (1) USB 2.0 downstream; (1) USB ups | tream; (1) USB cable included |
| | USB Cable Length | 1,8 m (5.9 ft.) | |
| Audio | Speakers and I/O | (2) 1W/channel built-in speakers (rea included | r firing); (1) Audio-in; (1) audio cable |
| | Audio Cable Length | 1,8 m (5.9 ft.) | |
| Power | Input Voltage | 90 to 264 VAC | |
| | Frequency | 50/60 Hz | |
| | Typical Power Consumption | 11 W | |
| | Maximum | 18 W | |
| | Sleep | 1 W | |
| | Off | 0.5 W | |
| | Power Cable Length | 1,9 m (6.2 ft.); detachable | |
| Mechanical | Dimensions (Wx D x H) | Unpacked w/stand | 25,4 x 16,8 x 30,5 cm (10 x 6.6 x 12 in) |
| | | Display Head only | 25,4 x 4,1 x 20,8 cm (10 x 1.6 x 8.2 in) |
| | | Packaged | 36,2 x 15,6 x 28 cm (14.3 x 6.1 x 11 in) |
| | Weight | Unpacked | 1,2 kg (2.6 lb) |
| | | Unpacked (with stand – sold separately) | 2,2 kg (4.8 lb) |
| | | Packaged | 4 kg (8.8 lb) |
| Environmental | Temperature – Operating | 5° to 40° C (41° to 104° F) non-conde | nsing |
| | Temperature – Non- operating | -20° to 60° C (-4° to 140° F) non-cond | densing |
| | Humidity – Operating | 20% to 80% non-condensing | |
| | Humidity – Non-operating | 5 % to 95 % non-condensing | |
| | Altitude – Operating | 0 to 5000 m (0 to 16400 ft) | |
| | Altitude – Non-operating | 0 to 12192 m (0 to 40000 ft) | |
| | White LED Backlights | Yes | |
| | CCFL Panel | No | |
| | Arsenic-Free Display Glass | Yes | |



Technical Specifications

| Environmental Data | Low Halogen ¹ Mercury-Free Display Backlighting Eco-Label Certifications & declarations | - | pt external cables ed or is in the process of being o labeled with one or more of thes | |
|--------------------|--|--|---|---|
| | | IT ECO declaration US ENERGY STAR EPEAT[®] Gold where HP registers commercial display products. See http://www.epeat.net for registration status in your country US Federa Energy Management Program (FEMP) | | |
| | Energy Consumption (in accordance with US Energy Star test method) | JS | | 100VAC, 60Hz |
| | Normal Operation | 7.19 W | 7.19 W | 7.16 W |
| | Sleep | 0.49 W | 0.5 W | 0.5 W |
| | Off | 0.34 W | 0.34 W | 0.33 W |
| | Heat Dissipation* | 115VAC, 60Hz | 230VAC, 50Hz | 100VAC, 60Hz |
| | Normal Operation | 25 BTU/hr | 25 BTU/hr | 24 BTU/hr |
| | Sleep | 2 BTU/hr | 2 BTU/hr | 2 BTU/hr |
| | Off | 1 BTU/hr | 1 BTU/hr | 1 BTU/hr |
| | | *NOTE: Heat dissipatio the service level is atta | n is calculated based on the mea ined for one hour. | asured watts, assuming |
| | Additional Information | This product is in compliance with the Restrictions of Hazardous Substances (RoHS) directive - 2002/95/EC. This HP product is designed to comply with the Waste Electrical Electronic Equipment (WEEE) Directive - 2002/96/EC. This product is in compliance with California Proposition 65 (Sta California; Safe Drinking Water and Toxic Enforcement Act of 19 This product is in compliance with the IEEE 1680 (EPEAT) standa Gold level, see www.epeat.net Plastics parts weighing over 25 grams used in the product are m ISO 11469 and ISO1043. This product contains 15.7% post-consumer recycled plastic (by This product is 93.8% recycle-able when properly disposed of a life. | | Naste Electrical and 6/EC. position 65 (State of ement Act of 1986). (EPEAT) standard at the he product are marked per ycled plastic (by wt.) |
| | Packaging Materials | External: | PAPER/Cardboard & misc | 1100 g |
| | | Internal: | PLASTIC/Polyethylene low density | 12 g |
| | RoHS Compliance | laws and regulations, in Substances (RoHS) Dire meeting the requireme | nmitted to compliance with all a ncluding the European Union Re ective. HP's goal is to exceed cor nts of the RoHS Directive on a w s will be virtually eliminated (vir | striction of Hazardous npliance obligations by ⁄orldwide basis. By July 1, |



| Technical Specifications | |
|--|---|
| | legal limits) for all HP electronic products subject to the RoHS Directive, except where it is widely recognized that there is no technically feasible alternative (as indicated by an exemption under the EU RoHS Directive). |
| Material Usage | This product does not contain any of the following substances in excess of regulatory limits (refer to the HP General Specification for the Environment at http://www.hp.com/hpinfo/globalcitizenship/environment/supplychain/gen_specifications.html): |
| Destructions | Asbestos Certain Azo Colorants Certain Brominated Flame Retardants - may not be used as flame retardants in plastics Cadmium Chlorinated Hydrocarbons Chlorinated Paraffins Formaldehyde Halogenated Diphenyl Methanes Lead carbonates and sulfates Lead and Lead compounds Mercuric Oxide Batteries Nickel - finishes must not be used on the external surface designed to be frequently handled or carried by the user. Ozone Depleting Substances Polybrominated Biphenyl (PCB) Polybrominated Biphenyl (PCB) Polychlorinated Terphenyls (PCT) Polyvinyl Chloride (PVC) - except for wires and cables, and certain retail packaging has been voluntarily removed from most applications. Radioactive Substances Tributyl Tin (TBT), Triphenyl Tin (TPT), Tributyl Tin Oxide (TBTO) |
| Packaging | HP follows these guidelines to decrease the environmental impact of product packaging: |
| | Eliminate the use of heavy metals such as lead, chromium, mercury and cadmium in packaging materials. Eliminate the use of ozone-depleting substances (ODS) in packaging materials. Design packaging materials for ease of disassembly. Maximize the use of post-consumer recycled content materials in packaging materials. Use readily recyclable packaging materials such as paper and corrugated materials. Reduce size and weight of packages to improve transportation fuel efficiency. Plastic packaging materials are marked according to ISO 11469 and DIN 6120 standards. |
| End-of-life Managemen and Recycling | It Hewlett-Packard offers end-of-life HP product return and recycling programs in many geographic areas. To recycle your product, please go to: http://www.hp.com/go/reuse-recycle or contact your nearest HP sales office. |



| Technical Specificati | ons | | |
|---|--|---|--|
| | | Products returned to HP will be recycled, recovered or disposed of in a responsible manner. | |
| | | The EU WEEE directive (2002/95/EC) requires manufacturers to provide treatment information for each product type for use by treatment facilities. This information (product disassembly instructions) is posted on the Hewlett Packard web site at: http://www.hp.com/go/recyclers. These instructions may be used by recyclers and other WEEE treatment facilities as well as HP OEM customers who integrate and re-sell HP equipment. | |
| | Hewlett-Packard | For more information about HP's commitment to the environment: | |
| | Corporate | Clabel Citizenskia Desert | |
| | Environmental Information | Global Citizenship Report http://www.hp.com/hpinfo/globalcitizenship/gcreport/index.html Eco-label certifications http://www.hp.com/hpinfo/globalcitizenship/environment/ | |
| | | productdesign/ecolabels.html | |
| | | ISO 14001 certificates: | |
| | | http://www.hp.com/hpinfo/globalcitizenship/environment/ operations/envmanagement.html | |
| What's in the box? | Monitor and accessories | HP L6010 10.4-inch Retail Monitor; VGA cable; DisplayPort cable; DVI-D cables, USB cable; Audio cable; Power cord; Adapter | |
| | Documentation | Printed documentation and CD | |
| | Featured Software | None | |
| Other | User Guide Languages | English, French, German, Italian, Dutch, Spanish, Japanese, Portuguese, T. Chinese, S. Chinese. | |
| | Warranty Languages | English, French, German, Italian, Dutch, Spanish, Japanese, Portuguese, T. Chinese, S. Chinese. | |
| | Color | HP Jack Black | |
| | VESA External Mounting | Yes (Standard 4 hole pattern, 75 mm) | |
| | Kensington Lock-ready | Yes | |
| Certification and Compliance | | and US, FCC approval, ICES, BSMI for Taiwan, CCC/CECP/SEPA/CEL for China, C- for Argentina, CB, CE approval, VCCI, ENERGY STAR® | |
| Operating System Support | Microsoft Windows 7 32-bit Professional Microsoft Windows 7 64-bit Professional Microsoft Windows Embedded for Point of Service Microsoft Windows Embedded POSReady Microsoft Windows Vista Business 32 Edition Microsoft Windows XP Professional | | |
| Compatibility | Compatible with platform | is using the VESA standard video modes. | |
| Service and Warranty | Protected by HP, including | g a 3 year standard limited warranty. Optional Care Pack Services are extended o beyond your standard warranties.2 | |
| Additional Options (sold separately) | HP Dual Position L6010 Stand (A1X79AA) | The dual position stand supports the 10.4" monitor (L6010) | |
| | | Ruggedized, small footprint maximizes counter space for employees and customers Allows the monitor to be set on a counter for customer facing usage | |

- Allows the monitor to be set on a counter for customer facing usage
- The two height positions and tilt adjustments help you customize



Technical Specifications

| | | positioning to best meet | your environment's needs | |
|----------------------|----------------------------------|---|--------------------------|--|
| Stand Specifications | Tilt Range | -5 to +35 degrees | | |
| | Swivel Range | No | | |
| | Height Adjustable | Yes, two position (height differe | ential of 69 mm) | |
| | Pivot Rotation | No | | |
| | Base and Stand | Undetachable | | |
| | Dimensions (W x D x H) | 19,3 x 16,79 x 22,5 cm (7.59 x 6.6 x 8.86 in) | | |
| | Weight | Unpacked | 1 kg (2.25 lb) | |
| | | Packaged | 1,7 kg (3.75 lb) | |
| | Color | HP Jack Black | | |

©Copyright 2013 Hewlett-Packard Development Company, L.P.

ENERGY STAR® is a US registered mark of the United States Environmental Protection Agency.

¹ External power supplies, power cords, cables and peripherals are not Low Halogen. Service parts obtained after purchase may not be Low Halogen.

² HP Care Pack Services extend service contracts beyond the standard warranties. Service levels and response times for HP Care Packs may vary depending on your geographic location. Service starts from date of hardware purchase. To choose the right level of service for your HP product, use the HP Care Pack Services Lookup Tool at http://www.hp.com/go/lookuptool. Additional HP Care Pack Services information by product is available at http://www.hp.com/hps/carepack.

The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein. Microsoft, Windows, Windows XP, Windows Vista and Windows 7 are trademarks of the Microsoft group of companies. March 2013

