

Xerox[®] Phaser[®] 6500 Color Printer and WorkCentre[®] 6505 Color Multifunction Printer The right colors, the easy way



Phaser[®] 6500 Color Printer and WorkCentre[®] 6505 Color Multifunction Printer

The right solution for today's pace of business. Your busy workteam needs a value-packed color device that gets the job done with the rare combination of outstanding print quality, unparalleled simplicity, and day-in, day-out dependability. Introducing the Phaser 6500 and WorkCentre 6505.



The colors your business needs

The Phaser 6500 color printer and WorkCentre 6505 color multifunction printer give your important documents a powerful, colorful boost.

- **Outstanding print quality.** A print resolution of up to 600 x 600 x 4 dpi makes your printed communications stand out and grab attention.
- True Adobe[®] PostScript[®] 3[™]. Count on consistently precise print jobs with bright, true colors and superior graphics.
- Advanced toner technology. Xerox-exclusive EA Toner uses particles engineered for uniform size and shape, producing superior image detail and line definition, and text that's sharp and clear.
- Always the right color. Pantone[®] Color approved solid-color simulations and Xerox color correction technology ensure results that match your expectations.

Ready to help

We designed the Phaser 6500 and WorkCentre 6505 as simple color devices that support single users and small workteams.

- **Print and go.** Work quickly with print speeds of up to 24 ppm for color and black-and-white (letter) or 23 ppm for color and black-and-white (A4).
- More productivity for more people. Connect and go, thanks to built-in networking and seamless compatibility with mixed-user environments, including PC, Macintosh and Linux.
- Easy management. With Xerox CentreWare[®] IS, remote device administration is handled with ease right from your computer's browser.
- Out of color toner? Our Run Black feature lets you continue printing with black until you can replace toner.
- Total peace of mind. Our standard one-year on-site warranty is backed by the industry-lead-ing Xerox Total Satisfaction Guarantee.

Easy on your environment

From arrival to disposal, the Phaser 6500 and WorkCentre 6505 help you meet today's environmental challenges.

- Print more, use less. Whether you choose manual two-sided printing or upgrade to convenient automatic duplexing, you'll conserve paper for reduced costs and lower environmental impact.
- **Toner-only cartridges.** With minimal packaging, our toner-only cartridges allow for 80% less waste than comparable color devices, using integrated print cartridges.
- A perfect fit. Both devices feature a small footprint, which allows for easy integration within your work space, whether on your desk or in a shared location.
- The quiet partner. Engineered for extra-quiet operation to minimize impact on busy offices.
- **Consolidate and save.** The value-packed WorkCentre 6505 multifunction printer will save on energy and supplies costs by combining the functions of multiple devices into one.

Phaser® 6500 Quick Facts

- Print up to 24 ppm (letter) or 23 ppm (A4)
- 600 x 600 x 4 dpi
- Optional automatic two-sided printing*
- Powerful 400 MHz processor
- Robust 40,000 pages/month duty cycle
- 256 MB memory, expandable to 768 MB
- First page out time of 13 seconds color, 12 seconds black-and-white

* Standard on DN configuration



WxDxH:

15.9 x 16.75 x 16.4 in. 404 x 426 x 416 mm



Productivity, accelerated. The WorkCentre 6505 color multifunction printer builds on the outstanding print performance found in the Phaser 6500, delivering a host of powerful productivity tools designed to make your daily office tasks more efficient than ever.

0

The WorkCentre 6505 includes an intuitive front panel for configuring device settings and programming jobs.

A 35-sheet automatic document feeder handles media sizes from 5.5 x 5.5 in. to 8.5 x 14 in.

3

A front-side USB port allows users to quickly print from or scan to any standard USB memory device.

4

Powerful scanning capabilities include Scan to Email, Network Scanning, Direct Scan to Applications including Optical Character Recognition, and Scan to USB memory device.

6

Standard copy features include ID Card Copy, N-up, auto fit, cloning, collate and more.

6

Send faxes from the network using LAN Fax, or take advantage of full walkup fax features such as speed dial, remote receive and fax broadcast.

7

A standard 533 MHz processor and 256 MB memory (expandable to 768 MB) let the WorkCentre 6505 easily handle a heavy workload — even a steady stream of pages with graphics, photos and charts.

8

Optional 250-sheet paper tray increases capacity to 500 sheets — enough to load a full ream of paper.





- Print up to 24 ppm (letter) or 23 ppm (A4)
- 600 x 600 x 4 dpi
- Optional automatic two-sided printing*
- Powerful 533 MHz processor
- Robust 40,000 pages/month duty cycle256 MB memory, expandable to 768 MB
- First page out time of 12 seconds color,

 First page out time of 12 seconds cc and black-and-white
^{*} Standard on DN configuration



Phaser[®] 6500 and WorkCentre[®] 6505

		Phaser 6500N	Phaser 6500DN	WorkCentre 6505N	WorkCentre 6505DN	
Speed		Up to 24 ppm color and black-and-w	hite (Letter) / 23 ppm color and black-c	and-white (A4)		
Duty Cycle		Up to 40,000 pages / month ¹				
Paper Handling Paper input	Standard	NA			Automatic Document Feeder (ADF): 35 sheets: Custom Sizes: 5.5 x 5.5 in. to 8.5 x 14 in. / 139.7 x 139.7 mm to 215.9 x 355.6 mm	
		Manual Feed Slot: 1 sheet; Custom sizes: 3 x 5 in. to 8.5 x 14 in. / 76 x 127 mm to 216 x 356 mm				
		Tray 1: 250 sheets; Custom sizes: 3 x 5 in. to 8.5 x 14 in. / 76 x 127 mm to 216 x 356 mm				
	Optional	Tray 2: 250 sheets; Custom sizes: 5.8 x 8.3 in. to 8.5 x 14 in. / 148 x 210 mm to 216 x 356 mm				
Paper output		150 sheets face down				
Automatic two-sided pri	nting	Optional	Standard	Optional	Standard	
Print First-page-out-time		As fast as 13 seconds color / 12 seco	nds black-and-white	As fast as 12 seconds color / 12 seconds black-and-white		
Resolution (max)		Up to 600 x 600 x 4 dpi				
Processor		400 MHz		533 MHz	533 MHz	
Memory (std / max)		256 MB / 768 MB		·		
Connectivity		USB 2.0, 10/100/1000 Base-T Ethernet				
Page description languages		Adobe [®] PostScript [®] 3 [™] , PCL [®] 6 emulation				
Print features Standard		PANTONE® Color approved solid-color simulations, N-up, Fit to page, Booklet printing, Skip blank pages, Run black, Covers/Separators ² , Poster printing ² , Watermarks ² Overlays ² , Banner sheets ² , Draft mode ²				
	Optional ³	Secure print, Proof print, Personal print, Saved print, RAM collation				
Copy First-copy-out-ti	me			As fast as 20 seconds color	r / 13 seconds black-and-white	
Copy resolution		NA		600 x 600 dpi	600 x 600 dpi	
Copy features					1 sided to 2 sided copying ⁴ , Reduce/enlarge (25%-400%), N-up copying, Auto fit, Cloning, Collate, ID Card Copy, Edge erase	
Fax Fax features⁵		NA		Lighter / darker, Polling, Re	MR/JBIG/JPEG compression, Secure fax receive, mote receive (with external phone), Junk fax , Delay send, Broadcast, Address book (up to 200	
					Resolution up to 400 x 400 dpi, LAN Fax (Send)	
Scan destinations		NA		speed dials, 6 group dials), Scan to Email (local addres	Resolution up to 400 x 400 dpi, LAN Fax (Send) ss book or LDAP integration), Network Scanning server or computer), Direct Scan to Applications	
Scan		NA		speed dials, 6 group dials), Scan to Email (local addres via FTP (server) and SMB (including OCR, USB Memo	Resolution up to 400 x 400 dpi, LAN Fax (Send) ss book or LDAP integration), Network Scanning server or computer), Direct Scan to Applications ry Device olution, 24-bit color / 8-bit grayscale,	
Scan Scan destinations			Authentication, IPv6, SNMPv3, Audit	speed dials, 6 group dials), Scan to Email (local addres via FTP (server) and SMB (r including OCR, USB Memo Up to 1200 x 1200 dpi res PDF / JPEG / TIFF (single a	Resolution up to 400 x 400 dpi, LAN Fax (Send) ss book or LDAP integration), Network Scanning server or computer), Direct Scan to Applications ry Device olution, 24-bit color / 8-bit grayscale,	

¹ Monthly volume capacity expected in any one month. Not expected to be sustained on a regular basis; ² Accessed via PCL driver; ³ Requires optional Productivity Kit with 512 MB memory; ⁴ requires DN model or optional duplex unit; ⁵ Analog phone line required

Device Management

CentreWare $^{\otimes}$ Internet Services, CentreWare Web, PrintingScout $^{\otimes},$ Email alerts

Print Drivers

Windows® XP, Vista, Server 2003, Server 2008, 7; Mac OS® version 10.5 and higher; Linux, Xerox Global Print Driver®, Xerox Mobile Express Driver™

Media Handling

Automatic Document Feeder**: 12.5 lb. Bond – 45 lb. cover / 50 – 125 gsm; Manual Feed Slot and Trays: 16 lb. bond – 80 lb. cover / 60 – 216 gsm; Media types: Plain paper, glossy, business cards, envelopes, labels, cardstock

Operating Environment

Temperature: Storage: -4° to 104° F / -20° to 40° C; Operating: 50° to 90° F / 10° to 32° C; Humidity: 10° to 85° ; Sound pressure levels: 6500: Printing (Enhanced): 53 dB(A), Standby: 25 dB(A); 6505: Printing (Enhanced): 52 dB(A), Standby: 22 dB(A); Sound power levels: Printing (Enhanced): 6500: 67.3 dB(A), Standby: 38.6 dB(A); 6505: 66.3 dB(A), Standby: 36.5 dB(A); Warm-up time (from sleep mode): as fast as 31 seconds

Electrical

Power: 110-127 VAC, 50/60 Hz or 220-247 VAC, 50/60 Hz; Power consumption: 6500: Standby: 55 W, Printing: 375 W, Sleep: 15 W; 6505: Standby: 65 W, Printing: 425 W, Sleep: 18.4 W; ENERGY STAR[®] qualified

Dimensions (WxDxH)

6500N/DN: 15.9 x 16.75 x 16.4 in. / 403.5 x 425.5 x 415.6 mm; Weight: 6500N: 40 lbs / 18.2 kg; 6500DN: 42.7 lbs / 19.4 kg; 250sheet feeder: 15.75 x 18 x 4.2 in. / 400 x 457 x 107 mm; Weight: 9.7 lbs / 4.4 kg; 6505N/DN: 16.9 x 21.4 x 23 in. / 430 x 544.2 x 584.4 mm; Weight: 6505N: 62.5 lbs / 28.4 kg; 6505DN: 65.1 lbs / 29.6 kg; 250-sheet feeder: 16.5 x 20.4 x 4.2 in. / 419.2 x 518 x 107 mm; Weight: 9.9 lbs / 4.5 kg

Certifications

FCC Part 15, Class B, FCC Part 686, UL 60950-1/CSA 60950-1-07, 2nd Edition, CE Mark applicable to Low Voltage Directive (2006/95/ EC), EMC Directive (2004/108/EC), and R&TTE Directive (1999/5/ EC) 6, GOST, NOM, GS Mark, Citrix Ready, Section 508 (compliant with minor exceptions), ENERGY STAR[®] qualified

Supplies

High-capacity Print Cartridges*:	
Black: 3,000 std. pages	106R01597
Cyan: 2,500 std. pages	106R01594
Magenta: 2,500 std. pages	106R01595
Yellow: 2,500 std. pages	106R01596
Standard-capacity Print Cartridges*:	
Cyan: 1,000 std. pages	106R01591
Magenta: 1,000 std. pages	106R01592
Yellow: 1,000 std. pages	106R01593
Options	
Options 250-sheet feeder for Phaser 6500	097504070
•	097S04070 097S04264
250-sheet feeder for Phaser 6500	
250-sheet feeder for Phaser 6500 250-sheet feeder for WorkCentre 6505	097S04264
250-sheet feeder for Phaser 6500 250-sheet feeder for WorkCentre 6505 Productivity Kit	097S04264 097S04269
250-sheet feeder for Phaser 6500 250-sheet feeder for WorkCentre 6505 Productivity Kit Duplex unit	097S04264 097S04269
250-sheet feeder for Phaser 6500 250-sheet feeder for WorkCentre 6505 Productivity Kit Duplex unit Wireless network adapter – N. America power converter – European power converter	097S04264 097S04269 097S04069 097S03740 097S03741
250-sheet feeder for Phaser 6500 250-sheet feeder for WorkCentre 6505 Productivity Kit Duplex unit Wireless network adapter – N. America power converter	097S04264 097S04269 097S04069 097S03740

Average standard pages. Declared Yield in accordance with ISO/IEC 19798. Yield will vary based on image, area coverage and print mode.





For more information, call 1-877-362-6567 or visit us at www.xerox.com/office

© 2011 Xerox Corporation. All rights reserved. Contents of this publication may not be reproduced in any form without permission of Xerox Corporation. XEROX®, XEROX and Design®, CentreWare®, Phaser® and WorkCentre® are trademarks of Xerox Corporation in the U.S. and/or other countries. Adobe® and PostScript® 3th are registered trademarks or trademarks of Adobe Systems, Incorporated. PCL® is a registered trademark of Hewlett-Packard. As an ENERGY STAR® partner, Xerox Corporation has determined that this product meets the ENERGY STAR guidelines for energy efficiency, ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. All other trademarks are the property of their respective manufacturers. The information in this brochure is subject to change without notice. 2/11 610P730196