

Overview

Models

HP 2915-8G-PoE Switch

J9562A

Key features

- Scalable 10/100/1000 connectivity
- Layer 2 and 3 switching capabilities
- sFlow, ACLs, and rate limiting
- Energy-efficient design and quiet operation
- Rack-mountable, compact form factor

Product overview

The HP 2915-8G-PoE Switch is a fully managed 8-port 10/100/1000 switch with an additional two dual-personality Gigabit Ethernet ports for copper or SFP connectivity.

Together with static and RIP IPv4 routing, robust security and management, enterprise-class features, a free lifetime warranty, and free software updates, the HP 2915-8G-PoE Switch is a cost-effective solution. The switch is fanless, providing quiet operation and making it ideal for deployments in open spaces.

In addition, its compact form factor allows for flexible deployments, including wall, surface, or rack mounting. These switches can be deployed at enterprise edge and remote branch offices, as well as converged networks.

Features and benefits

Quality of Service (QoS)

- **Selectable queue configuration**
performance and/or traffic reliability can be increased by selecting the number of queues that best meet the requirements of network applications; the switch will map eight priorities to either two or four queues
- **Class of Service (CoS)**
sets the IEEE 802.1p priority tag based on IP address, IP Type of Service (ToS), Layer 3 protocol, TCP/UDP port number, source port, and DiffServ
- **Layer 4 prioritization**
enables prioritization based on TCP/UDP port numbers
- **Traffic prioritization (IEEE 802.1p)**
allows real-time traffic classification into eight priority levels mapped to four queues
- **Rate limiting**
per-port ingress-enforced maximums
- **Flow control**
helps ensure reliable communications during full-duplex operation
- **Type of service:**
 - **IP precedence**
honors IP precedence bits and allows mapping to a priority queue
 - **Differentiated Services Code Point values**
honors Differentiated Services Code Point (DSCP) bits and allows mapping to a priority queue

Overview

Management

- **Choice of management interfaces**
 - **Web GUI**
easy-to-use graphical interface allows configuration of the switch from any Web browser
 - **Command-line interface (CLI)**
robust CLI provides advanced configuration and diagnostics
 - **Simple Network Management Protocol (SNMPv2c/SNMPv3)**
allows switch to be managed with a variety of third-party network management applications
- **Multiple configuration files**
configuration file management tools allow up to three configuration files to be managed and stored on the switch
- **Dual flash images**
provide independent primary and secondary operating system files for backup while upgrading
- **Command authorization**
leverages RADIUS to link a custom list of CLI commands to an individual network administrator's login; also provides an audit trail
- **Front-panel LEDs**
 - **Locator LED**
allows users to set the locator LED on a specific switch to either turn on, blink, or turn off; simplifies troubleshooting by making it easy to locate a particular switch within a rack of similar switches
 - **Per-port LEDs**
provides an at-a-glance view of status, activity, speed, and full-duplex operation
 - **Power and fault LED**
display any issues
- **Integration with HP PCM**
enables discovery, mapping, logging, and configuration via PCM, which is available as a free download from the Web

Connectivity

- **Dual-personality functionality**
two 10/100/1000 ports or SFP slots provide optional fiber connectivity such as Gigabit-SX, -LX, -LH, 100-FX, 100-BX, and 1000-BX
- **IEEE 802.3af Power over Ethernet**
provides up to 15.4 W per port to IEEE 802.3af-compliant PoE-powered devices such as IP phones, wireless access points, and security cameras (see product specifications for total PoE power available)
- **Auto-MDIX**
automatically adjusts for straight-through or crossover cables on all 10/100/1000 ports
- **RJ-45 serial console port**
provides easy accessibility on the front of unit to the switch CLI
- **IPv6:**
 - IPv6 host
the switches can be managed and deployed at the edge of IPv6 networks
 - Dual stack (IPv4/IPv6)
provides transition mechanism from IPv4 to IPv6; supports connectivity for both protocols
- **Single IP address management**
provides single IP address management for a virtual stack of up to 16 switches

Resiliency and high availability

- **IEEE 802.1s Multiple Spanning Tree**

Overview

provides high link availability in multiple VLAN environments by allowing multiple spanning trees; provides legacy support for IEEE 802.1d and IEEE 802.1w

- **Port trunking and link aggregation**
 - **Trunking**
supports up to eight links per trunk to increase bandwidth and create redundant connections
 - **IEEE 802.3ad Link Aggregation Protocol (LACP)**
eases configuration of trunks through automatic configuration

Layer 2 switching

- **GARP VLAN Registration Protocol**
allows automatic learning and dynamic assignment of VLANs
- **VLAN support and tagging**
supports IEEE 802.1Q (4,094 VLAN IDs) and 256 VLANs simultaneously

Layer 3 routing

- **Static IP routing**
provides manually configured routing; includes ECMP capability
- **Routing Information Protocol (RIP)**
provides RIPv1 and RIPv2 routing

Security

- **Access control lists (ACLs)**
provide IP Layer 3 filtering based on source/destination IP address/subnet and source/destination TCP/UDP port number
- **Identity-driven ACL**
enables implementation of a highly granular and flexible access security policy and VLAN assignment specific to each authenticated network user
- **Source-port filtering**
allows only specified ports to communicate with each other
- **RADIUS/TACACS+**
eases switch management security administration by using a password authentication server
- **Secure protocols for encryption of management traffic**
 - **Secure Shell (SSHv2)**
encrypts all transmitted data for secure remote CLI access over IP networks
 - **Secure Sockets Layer (SSL)**
encrypts all HTTP traffic, allowing secure access to the browser-based management GUI in the switch
 - **Secure FTP (SFTP)**
encrypts uploads and downloads of configuration files
- **Port security**
allows access only to specified MAC addresses, which can be learned or specified by the administrator
- **Dynamic IP lockdown**
works with DHCP protection to block traffic from unauthorized hosts, preventing IP source address spoofing
- **DHCP protection**
blocks DHCP packets from unauthorized DHCP servers, preventing denial-of-service attacks
- **Dynamic ARP protection**
blocks ARP broadcasts from unauthorized hosts, preventing eavesdropping or theft of network data
- **MAC address lockout**
prevents configured particular MAC addresses from connecting to the network

Overview

- **MAC address lockdown**
allows only specified MAC addresses access to the network on a specified port
- **Multiple user authentication methods**
 - **IEEE 802.1X**
is an industry-standard method of user authentication using an IEEE 802.1X supplicant on the client in conjunction with a RADIUS server
 - **Web-based authentication**
similar to IEEE 802.1X, it provides a browser-based environment to authenticate clients that do not support the IEEE 802.1X supplicant
 - **MAC-based authentication**
client is authenticated with the RADIUS server based on the client's MAC address
- **Authentication flexibility—2 IEEE 802.1X**
provides authentication of multiple IEEE 802.1X users per port; prevents user "piggybacking" on another user's IEEE 802.1X authentication
- **Protected ports**
prevents designated ports from communicating with each other while allowing access to unprotected ports
- **Per-port broadcast throttling**
selectively configures broadcast control on heavy traffic port uplinks
- **Physical security**
 - **Front-panel buttons**
provides the ability to disable reset and clear buttons on the front panel for added security
 - **Kensington Lock slot**
includes a Kensington Lock slot for securing the switches in open-space deployments
- **Spanning Tree Protocol Root Guard**
when running the Spanning Tree Protocol, it protects the root bridge from malicious attacks or configuration mistakes
- **STP BPDU port protection**
blocks Bridge Protocol Data Units (BPDUs) on ports that do not require BPDUs, preventing forged BPDU attacks

Convergence

- **IP multicast snooping and data-driven IGMP**
automatically prevent flooding of IP multicast traffic
- **LLDP-MED (Media Endpoint Discovery)**
is a standard extension of LLDP that stores values for parameters such as QoS and VLAN to automatically configure network devices such as IP phones
- **IEEE 802.1AB Link Layer Discovery Protocol (LLDP)**
is an automated device discovery protocol that provides easy mapping of network management applications
- **PoE allocations**
support multiple methods (automatic, IEEE 802.3af class, LLDP-MED, or user specified) to allocate PoE power for more efficient energy savings

Monitor and diagnostics

- **Port mirroring**
enables traffic on a port to be simultaneously sent to a network analyzer for monitoring
- **Network tools**
CLI includes telnet client, ping, traceroute, and Layer 2 link test tools for diagnostics
- **Logging**
local and remote logging of events via SNMP (v2c and v3) and syslog
- **Troubleshooting**

Overview

ingress and egress port monitoring enable network problem solving

- **Uni-Directional Link Detection (UDLD)**
monitors a link between two switches and blocks the ports on both ends of the link if the link goes down at any point between the two devices
- **Find-Fix-Inform**
finds and fixes common network problems automatically, then informs the administrator
- **RMON, XRMON, sFlow, and SMON**
provide advanced monitoring and reporting capabilities for statistics, history, alarms, and events
- **Port monitoring for network threats**
provides sampled port traffic using sFlow technology to the HP Network Immunity Manager application for Network Behavior Anomaly Detection (NBAD) analysis to detect threats and mitigate threats at the port where they originated

Flexibility

- **Flexible mounting**
 - **Rackable**
can be mounted in a standard 19-inch rack with included hardware
 - **Wall mountable**
can be mounted to a wall using included hardware
 - **Surface mountable**
can be mounted above or below a surface (such as a desk or table) using included hardware
- **Compact size**
product is designed to reduce space requirements (see product specifications for exact dimensions)
- **NEW Power supply clip**
provides the ability to attach or detach the power supply from the device, allowing for either an integrated solution or a separate one, depending on deployment requirements

Product Architecture

- **Energy-efficient design**
 - **Fans**
fanless design helps reduce power consumption
 - **Port LEDs**
port link and activity LEDs can be turned off to conserve energy
 - **Port low-power mode option**
when no link is detected on a port, the port will automatically go into low-power mode to conserve energy

Warranty and support

- **Lifetime Warranty 2.0**
advance hardware replacement for as long as you own the product with next-business-day delivery (available in most countries)†
- **Electronic and telephone support (for Lifetime Warranty 2.0)**
limited 24x7 telephone support is available from HP for the first 3 years; limited electronic and business hours telephone support is available from HP for the entire warranty period; to reach our support centers, refer to www.hp.com/networking/contact-support; for details on the duration of support provided with your product purchase, refer to www.hp.com/networking/warrantysummary
- **Software releases**
to find software for your product, refer to www.hp.com/networking/support; for details on the software releases available with your product purchase, refer to www.hp.com/networking/warrantysummary

Overview

† Hardware warranty replacement for as long as you own the product, with next business day advance replacement (available in most countries) with a five-year hardware warranty replacement for the disk drive included with HP AllianceONE Services zI Module, HP Threat Management Services zI Module, HP PCM+ Agent with AllianceONE Services zI Module, and HP MSM765 zI Mobility Controller. For details, refer to the HP Software License, Warranty, and Support booklet at: www.hp.com/networking/warranty.

Technical Specifications

HP 2915-8G-PoE Switch (J9562A)

Included accessories	1 HP X520 1U Power Adapter Shelf (J9701A)	
I/O ports and slots	8 RJ-45 autosensing 10/100/1000 PoE ports; Media Type: Auto-MDIX; Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T, IEEE 802.3af PoE) 2 dual-personality ports; each port can be used as either an RJ-45 10/100/1000 port (IEEE 802.3 Type 10BASE-T; an IEEE 802.3u Type 100BASE-TX; an IEEE 802.3ab 1000BASE-T Gigabit Ethernet); or an SFP slot (for use with SFP transceivers) 1 RJ-45 serial console port	
Physical characteristics	Dimensions	10(w) x 6.28(d) x 1.75(h) in (25.4 x 15.95 x 4.45 cm) (1U height)
	Weight	3.66 lb (1.66 kg) including power adapter and power cord
Memory and processor	Processor	Freescall PowerPC 8313 @ 333 MHz, 32 MB flash, 128 MB DDR2 SDRAM; packet buffer size: 512 KB dynamically all
Mounting and enclosure	Mounts in an EIA-standard 19 in. telco rack or equipment cabinet; horizontal surface mounting, wall mounting	
Performance	100 Mb Latency	< 5.3 μ s (LIFO 64-byte packets)
	1000 Mb Latency	< 2.7 μ s (LIFO 64-byte packets)
	Throughput	14.8 million pps
	Switching capacity	20 Gb/s
	MAC address table size	8000 entries
Environment	Operating temperature	32°F to 113°F (0°C to 45°C)
	Operating relative humidity	15% to 95% @ 104°F (40°C), noncondensing
	Nonoperating/Storage temperature	-40°F to 158°F (-40°C to 70°C)
	Nonoperating/Storage relative humidity	15% to 95% @ 149°F (65°C), noncondensing
	Altitude	up to 10,000 ft (3 km)
	Acoustic	Power: 0 dB, Pressure: 0 dB
Electrical characteristics	Description	Use only the external power adapter module (5070-6082, PA1 AC adapter) supplied with this product.
	Maximum heat dissipation	89 BTU/hr (93.9 kJ/hr)
	AC voltage	100-240 VAC
	Current	1.5 A
	Maximum power rating	86 W
	Idle power	11 W
	PoE power	67 W
	Frequency	50/60 Hz
	Notes	Idle power is the actual power consumption of the device with no ports connected.

Technical Specifications

Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.

PoE power is the total power budget available to all PoE ports.

Safety	cUL (CSA 22.2 No. 60950); CE Labeled; UL 60950-1; UL Listed; CAN/CSA 22.2 No. 60950; EN 60825; AS/NZS 60950; IEC 60950-1; EN 60950-1																						
Emissions	FCC part 15 Class A; VCCI Class A; EN 55022 Class A; CISPR 22 Class A; ICES-003 (Canada); AS/NZS CISPR 22; IEC/EN 61000-3-2; IEC/EN 61000-3-3; IEC 61000:4-2, 4-3, 4-4, 4-5, 4-6, 4-8, 4-11																						
Immunity	<table><tr><td>Generic</td><td>EN 55024, CISPR 24</td></tr><tr><td>EN</td><td>EN 55024, CISPR 24</td></tr><tr><td>ESD</td><td>IEC 61000-4-2</td></tr><tr><td>Radiated</td><td>IEC 61000-4-3</td></tr><tr><td>EFT/Burst</td><td>IEC 61000-4-4</td></tr><tr><td>Surge</td><td>IEC 61000-4-5</td></tr><tr><td>Conducted</td><td>IEC 61000-4-6</td></tr><tr><td>Power frequency magnetic field</td><td>IEC 61000-4-8</td></tr><tr><td>Voltage dips and interruptions</td><td>IEC 61000-4-11</td></tr><tr><td>Harmonics</td><td>EN 61000-3-2, IEC 61000-3-2</td></tr><tr><td>Flicker</td><td>EN 61000-3-3, IEC 61000-3-3</td></tr></table>	Generic	EN 55024, CISPR 24	EN	EN 55024, CISPR 24	ESD	IEC 61000-4-2	Radiated	IEC 61000-4-3	EFT/Burst	IEC 61000-4-4	Surge	IEC 61000-4-5	Conducted	IEC 61000-4-6	Power frequency magnetic field	IEC 61000-4-8	Voltage dips and interruptions	IEC 61000-4-11	Harmonics	EN 61000-3-2, IEC 61000-3-2	Flicker	EN 61000-3-3, IEC 61000-3-3
Generic	EN 55024, CISPR 24																						
EN	EN 55024, CISPR 24																						
ESD	IEC 61000-4-2																						
Radiated	IEC 61000-4-3																						
EFT/Burst	IEC 61000-4-4																						
Surge	IEC 61000-4-5																						
Conducted	IEC 61000-4-6																						
Power frequency magnetic field	IEC 61000-4-8																						
Voltage dips and interruptions	IEC 61000-4-11																						
Harmonics	EN 61000-3-2, IEC 61000-3-2																						
Flicker	EN 61000-3-3, IEC 61000-3-3																						
Management	HP PCM+; HP PCM (included); command-line interface; Web browser; configuration menu; out-of-band management (serial RS-232C); IEEE 802.3 Ethernet MIB; Repeater MIB; Ethernet Interface MIB																						
Notes	When using mini-GBICs with this product, mini-GBICs with revision "B" or later (product number ends with the letter "B" or later, e.g., J4858B, J4859C) are required. This product comes with a power supply clip adapter. The adapter dimensions are 1.7(d) x 10.7(w) x 3.8(h) in. (4.35 x 27.25 x 9.6 cm). The weight of the power supply clip adapter is .31 lb (.14 kg).																						
Services	3-year, 4-hour onsite, 13x5 coverage for hardware (U4683E) 3-year, 4-hour onsite, 24x7 coverage for hardware (U4835E) 3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 SW phone support and SW updates (U6321E) 3-year, 24x7 SW phone support, software updates (UF792E) 1-year, post-warranty, 4-hour onsite, 13x5 coverage for hardware (HR849E) 1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware (HR850E) 1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (HR851E) Installation with minimum configuration, system-based pricing (U4826E) Installation with HP-provided configuration, system-based pricing (U4830E) 4-year, 4-hour onsite, 13x5 coverage for hardware (UR948E) 4-year, 4-hour onsite, 24x7 coverage for hardware (UR949E) 4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UR950E) 4-year, 24x7 SW phone support, software updates (UR951E) 5-year, 4-hour onsite, 13x5 coverage for hardware (UR952E) 5-year, 4-hour onsite, 24x7 coverage for hardware (UR953E) 5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UR954E)																						

Technical Specifications

5-year, 24x7 SW phone support, software updates (UR955E)
3 Yr 6 hr Call-to-Repair Onsite (UW368E)
4 Yr 6 hr Call-to-Repair Onsite (UW369E)
5 Yr 6 hr Call-to-Repair Onsite (UW370E)
1-year, 6 hour Call-To-Repair Onsite for hardware (HR853E)
1-year, 24x7 software phone support, software updates (HR852E)
1-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS554E)
1-year, 24x7 software phone support, software updates + 4 hour hardware exchange (HS555E)
3-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS556E)
3-year, 24x7 software phone support, software updates + 4 hour Hardware Exchange (HS557E)
4-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS558E)
4-year, 24x7 software phone support, software updates + 4 hour Hardware Exchange (HS559E)
5-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS560E)
5-year, 24x7 software phone support, software updates + 4 hour Hardware Exchange (HS561E)

Refer to the HP website at: www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Standards and protocols

Denial of service protection

Automatic Filtering of well known Denial of Service Packets

Device management

RFC 1591 DNS (client)
Multiple Configuration Files
Multiple Software Images
SSHv1/SSHv2 Secure Shell
TACACS/TACACS+
Web UI

General protocols

IEEE 802.1D MAC Bridges
IEEE 802.1p Priority
IEEE 802.1Q VLANs
IEEE 802.1s Multiple Spanning Trees
IEEE 802.1w Rapid Reconfiguration of Spanning Tree
IEEE 802.3 Type 10BASE-T
IEEE 802.3ab 100BASE-T
IEEE 802.3ad Link Aggregation Control Protocol (LACP)
IEEE 802.3af Power over Ethernet
IEEE 802.3u 100BASE-X
IEEE 802.3x Flow Control
RFC 768 UDP
RFC 783 TFTP Protocol (revision 2)
RFC 792 ICMP

RFC 4113 MIB for UDP

RFC 4251 SSHv6 Architecture
RFC 4252 SSHv6 Authentication
RFC 4253 SSHv6 Transport Layer
RFC 4293 MIB for IP
RFC 4419 Key Exchange for SSH
RFC 4443 ICMPv6
RFC 4861 IPv6 Neighbor Discovery
RFC 4862 IPv6 Stateless Address Auto-configuration

MIBs

RFC 1213 MIB II
RFC 1493 Bridge MIB
RFC 2021 RMONv2 MIB
RFC 2613 SMON MIB
RFC 2618 RADIUS Client MIB
RFC 2620 RADIUS Accounting MIB
RFC 2665 Ethernet-Like-MIB
RFC 2668 802.3 MAU MIB
RFC 2674 802.1p and IEEE 802.1Q Bridge MIB
RFC 2737 Entity MIB (Version 2)
RFC 2863 The Interfaces Group MIB

Network management

IEEE 802.1AB Link Layer Discovery Protocol (LLDP)
RFC 1098 A Simple Network Management Protocol (SNMP)
RFC 2819 Four groups of RMON: 1 (statistics), 2 (history), 3 (alarm) and 9 (events)

Technical Specifications

RFC 793 TCP
RFC 826 ARP
RFC 854 TELNET
RFC 868 Time Protocol
RFC 951 BOOTP
RFC 1058 RIPv1
RFC 1350 TFTP Protocol (revision 2)
RFC 1723 RIP v2
RFC 1812 IPv4 Routing
RFC 2030 Simple Network Time Protocol (SNTP) v4
RFC 2131 DHCP
RFC 2453 RIPv2
UDLD (Uni-directional Link Detection)

IP multicast

RFC 3376 IGMPv3 (host joins only)

IPv6

RFC 1981 IPv6 Path MTU Discovery
RFC 2460 IPv6 Specification
RFC 2925 Remote Operations MIB (Ping only)
RFC 3315 DHCPv6 (client only)
RFC 3513 IPv6 Addressing Architecture
RFC 3596 DNS Extension for IPv6
RFC 4022 MIB for TCP

RFC 3176 sFlow
SNMPv1/v2c/v3

QoS/CoS

RFC 2474 DiffServ precedence, with 4 queues per port
RFC 2475 DiffServ Architecture
RFC 2597 DiffServ Assured Forwarding (AF)
RFC 2598 DiffServ Expedited Forwarding (EF)
Ingress Rate Limiting

Security

IEEE 802.1X Port Based Network Access Control
RFC 1492 TACACS+
RFC 2138 RADIUS Authentication
RFC 2866 RADIUS Accounting
Access Control Lists (ACLs)
MAC Authentication
MAC Lockdown
MAC Lockout
Port Security
Secure Sockets Layer (SSL)
Web Authentication

Accessories

HP 2915 Switch Series accessories	HP 2915-8G-PoE Switch (J9562A)	
	HP X121 1G SFP LC SX Transceiver	J4858C
	HP X121 1G SFP LC LX Transceiver	J4859C
	HP X121 1G SFP LC LH Transceiver	J4860C
	HP X111 100M SFP LC FX Transceiver	J9054B
	HP X112 100M SFP LC BX-D Transceiver	J9099B
	HP X112 100M SFP LC BX-U Transceiver	J9100B
	HP X122 1G SFP LC BX-D Transceiver	J9142B
	HP X122 1G SFP LC BX-U Transceiver	J9143B
	HP 0.5 m Multimode OM3 LC/LC Optical Cable	AJ833A
	HP Premier Flex LC/LC Multi-mode OM4 2 fiber 1m Cable	QK732A
	HP Premier Flex LC/LC Multi-mode OM4 2 fiber 2m Cable	QK733A
	HP Premier Flex LC/LC Multi-mode OM4 2 fiber 5m Cable	QK734A
	HP Premier Flex LC/LC Multi-mode OM4 2 fiber 15m Cable	QK735A
	HP Premier Flex LC/LC Multi-mode OM4 2 fiber 30m Cable	QK736A
	HP Premier Flex LC/LC Multi-mode OM4 2 fiber 50m Cable	QK737A
	HP X510 1U Cable Guard	J9700A
	HP X520 1U Power Adapter Shelf	J9701A

Accessory Product Details

NOTE: Details are not available for all accessories. The following specifications were available at the time of publication.

HP X121 1G SFP LC SX Transceiver (J4858C)	Ports	1 LC 1000BASE-SX port; Duplex: full only
A small form-factor pluggable (SFP) Gigabit SX transceiver that provides a full-duplex Gigabit solution up to 550 m on multimode fiber.	Physical characteristics	Dimensions: 2.24(d) x 0.54(w) x 0.48(h) in. (5.69 x 1.37 x 1.22 cm) Weight: 0.04 lb. (0.02 kg) Transceiver form factor: SFP
	Environment	Operating temperature: 32°F to 158°F (0°C to 70°C) Operating relative humidity: 5% to 85%, noncondensing Nonoperating/Storage temperature: -40°F to 203°F (-40°C to 85°C) Altitude: up to 10,000 ft. (3 km)
	Electrical characteristics	Power consumption typical: 0.4 W Power consumption maximum: 0.7 W
	Cabling	Type: <ul style="list-style-type: none">● 62.5/125 µm or 50/125 µm (core/cladding) diameter, graded-index, low metal content, multimode fiber optic, complying with ITU-T G.651 and ISO/IEC 793-2 Type A1b or A1a, respectively; Maximum distance: <ul style="list-style-type: none">● 2-220 m (62.5 µm core diameter, 160 MHz*km bandwidth)● 2-275 m (62.5 µm core diameter, 200 MHz*km bandwidth)● 2-500 m (50 µm core diameter, 400 MHz*km bandwidth)● 2-550 m (50 µm core diameter, 500 MHz*km bandwidth) Cable length: 2-550m Fiber type: Multi Mode
	Services	Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

HP X121 1G SFP LC LX Transceiver (J4859C)	Ports	1 LC 1000BASE-LX port (IEEE 802.3z Type 1000BASE-LX); Duplex: full only
HP X121 1G SFP LC LX Transceiver: An SFP format gigabit transceiver with LC connectors using LX technology.	Physical characteristics	Dimensions: 2.24(d) x 0.54(w) x 0.486(h) in. (5.69 x 1.37 x 1.23 cm) Weight: 0.04 lb. (0.02 kg)
	Environment	Operating temperature: 32°F to 158°F (0°C to 70°C) Operating relative humidity: 0% to 85%, noncondensing Nonoperating/Storage temperature: -40°F to 212°F (-40°C to 100°C) Altitude: up to 10,000 ft. (3 km)
	Cabling	Type: <ul style="list-style-type: none">● Either single mode or multimode; 62.5/125 µm or 50/125 µm (core/cladding) diameter, graded-index, low metal content, multimode fiber optic, complying with ITU-T G.651 and ISO/IEC 793-2 Type A1b or A1a, respectively; Low metal content, single-mode fiber-optic, complying with ITU-T G.652 and ISO/IEC 793-2 Type B1; Maximum distance:

Accessory Product Details

	<ul style="list-style-type: none">• 2-550 m (multimode 62.5 µm core diameter, 500 MHz*km bandwidth)• 2-550 m (multimode 50 µm core diameter, 400 MHz*km bandwidth)• 2-550 m (multimode 50 µm core diameter, 500 MHz*km bandwidth)• 2-10,000 m (single-mode fiber)
Notes	A mode conditioning patch cord may be needed in some multimode fiber installations. Wavelength: 1310nm Power Consumption: < 500mW Typical
Services	Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

HP X121 1G SFP LC LH Transceiver (J4860C)

A small form-factor pluggable (SFP) Gigabit LH transceiver that provides a full-duplex Gigabit solution up to 70 km on single-mode fiber.

Ports	1 LC 1000BASE-LH port (no IEEE standard exists for 1550 nm optics); Duplex: full only
Physical characteristics	Dimensions: 2.17(d) x 0.60(w) x 0.46(h) in. (5.5 x 1.53 x 1.18 cm) Weight: 0.04 lb. (0.02 kg)
Environment	Operating temperature: -40°F to 185°F (-40°C to 85°C) Operating relative humidity: 0% to 95% @ 77°F (25°C), noncondensing Nonoperating/Storage temperature: -40°F to 185°F (-40°C to 85°C) Altitude: up to 10,000 ft. (3 km)
Cabling	Cable type: <ul style="list-style-type: none">• Low metal content, single-mode fiber-optic, complying with ITU-T G.652 and ISO/IEC 793-2 Type B1; Maximum distance: <ul style="list-style-type: none">• 10-70,000 m (single-mode fiber)
Notes	Power consumption is 0.8 watts typical with 1 watt maximum at 100% utilization. For distances less than 20 km, a 10 dB attenuator must be used. For distances between 20 km and 40 km, a 5 dB attenuator must be used. Attenuators can be purchased from most cable vendors.
Services	Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Accessory Product Details

<p>HP X111 100M SFP LC FX Transceiver (J9054C)</p> <p>HP X111 100M SFP LC FX Transceiver: An SFP format 100-megabit transceiver with LC connectors using FX technology.</p>	<p>Ports</p> <p>Physical characteristics</p> <p>Environment</p> <p>Cabling</p> <p>Notes</p> <p>Services</p>	<p>1 LC 100BASE-FX port (IEEE 802.3u Type 100BASE-FX); Duplex: half or full</p> <p>Dimensions: 2.7(d) x 0.54(w) x 0.48(h) in. (6.86 x 1.38 x 1.22 cm)</p> <p>Weight: 0.06 lb. (0.03 kg)</p> <p>Operating temperature: 32°F to 158°F (0°C to 70°C)</p> <p>Operating relative humidity: 5% to 95%</p> <p>Nonoperating/Storage temperature: -40°F to 185°F (-40°C to 85°C)</p> <p>Nonoperating/Storage relative humidity: 5% to 85%</p> <p>Altitude: up to 10,000 ft. (3 km)</p> <p>Cable type: 62.5/125 im or 50/125 im (core/cladding) diameter, graded-index, low metal content, multimode fiber optic, complying with ITU-T G.651 and ISO/IEC 793-2 Type A1b or A1a, respectively; Maximum distance: • 2 km (full duplex) or 412 m (half duplex)</p> <p>Transmitter wavelength: 1310nm</p> <p>Power consumption is 1.1 watt maximum.</p> <p>For supported platforms and minimum software requirements to support this product, see the document titled "Support for the J9054B 100-FX SFP-LC Transceiver" on the "ProCurve Mini-GBICs and SFPs" Manuals Web page.</p> <p>Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.</p>
--	---	---

<p>HP X112 100M SFP LC BX-D Ports Transceiver (J9099B)</p> <p>A small form-factor pluggable (SFP) 100-Megabit BX (bi-directional) "downstream" transceiver that provides 100 Mbps full-duplex connectivity up to 10 km on one strand of singlemode fiber. The J9099B connects to the J9100B "upstream" transceiver, or to any IEEE-standard 100BASE-BX10-U ("upstream") device.</p>	<p>Physical characteristics</p> <p>Environment</p> <p>Cabling</p> <p>Notes</p>	<p>1 LC 100BASE-BX10 port (IEEE 802.3ah Type 100BASE-BX10-D); Duplex: full only</p> <p>Dimensions 2.7(d) x 0.55(w) x 0.48(h) in. (6.86 x 1.39 x 1.22 cm)</p> <p>Weight 0.04 lb. (0.03 kg)</p> <p>Operating temperature 32°F to 158°F (0°C to 70°C)</p> <p>Operating relative humidity 0% to 95%, noncondensing</p> <p>Nonoperating/Storage temperature -40°F to 185°F (-40°C to 85°C)</p> <p>Type: Single-mode fiber optic, complying with ITU-T G.652;</p> <p>Maximum distance:</p> <ul style="list-style-type: none"> • 0.5-10,000 m (single-mode fiber) <p>Transmit wavelength: 1550 nm. Receive wavelength: 1310 nm.</p> <p>Power consumption is 1.1 watt maximum.</p> <p>For supported platforms and minimum software requirements to support this product, see the document titled "Support for the HP BX Transceivers" on the "HP Mini-GBICs and SFPs" Manuals Web page.</p> <p>The J9099B connects to the J9100B "upstream" transceiver, or to any IEEE-standard 100BASE-BX10-U ("upstream") device. (A 100-BX-D transceiver can</p>
--	--	--

Accessory Product Details

Services

only connect to a 100-BX-U product. You cannot connect two 100-BX-D transceivers together.)

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

HP X112 100M SFP LC BX-U Ports Transceiver (J9100B)

A small form-factor pluggable (SFP) 100-Megabit BX (bi-directional) "upstream" transceiver that provides 100 Mbps full-duplex connectivity up to 10 km on one strand of singlemode fiber. The J9100B connects to the J9099B "downstream" transceiver, or to any IEEE-standard 100BASE-BX10-D ("downstream") device.

Physical characteristics

1 LC 100BASE-BX10 port (IEEE 802.3ah Type 100BASE-BX10-U); Duplex: full only

Dimensions

2.7(d) x 0.55(w) x 0.48(h) in. (6.86 x 1.39 x 1.22 cm)

Weight

0.07 lb. (.03 kg)

Environment

Operating temperature

32°F to 158°F (0°C to 70°C)

Operating relative humidity

0% to 95%, noncondensing

Nonoperating/Storage temperature

-40°F to 185°F (-40°C to 85°C)

Cabling

Type:

Single-mode fiber optic, complying with ITU-T G.652;

Maximum distance:

- 0.5-10,000 m (single-mode fiber)

Notes

For supported platforms and minimum software requirements to support this product, see the document titled "Support for the HP BX Transceivers" on the "HP Mini-GBICs and SFPs" Manuals Web page.

The J9100B connects to the J9099B "downstream" transceiver, or to any IEEE-standard 100BASE-BX10-D ("downstream") device. (A 100-BX-U transceiver can only connect to a 100-BX-D product. You cannot connect two 100-BX-U transceivers together.)

Transmit wavelength: 1310 nm. Receive wavelength: 1550 nm.

Power consumption is 1.1 watts maximum.

Services

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Accessory Product Details

HP X122 1G SFP LC BX-D Transceiver (J9142B)

A small form-factor pluggable (SFP) Gigabit-BX (bi-directional) "downstream" transceiver that provides a full-duplex Gigabit solution up to 10 km on one strand of single-mode fiber. The J9142B connects to the J9143B "upstream" transceiver, or to any IEEE-standard 1000BASE-BX10-U ("upstream") device.

Ports	1 LC 1000BASE-BX10 port (IEEE 802.3ah Type 1000BASE-BX10-D); Duplex: full only						
Physical characteristics	<table border="0"> <tr> <td style="vertical-align: top;">Dimensions</td> <td>2.19(d) x 0.54(w) x 0.46(h) in. (5.57 x 1.37 x 1.18 cm)</td> </tr> <tr> <td style="vertical-align: top;">Weight</td> <td>0.04 lb. (0.02 kg)</td> </tr> </table>	Dimensions	2.19(d) x 0.54(w) x 0.46(h) in. (5.57 x 1.37 x 1.18 cm)	Weight	0.04 lb. (0.02 kg)		
Dimensions	2.19(d) x 0.54(w) x 0.46(h) in. (5.57 x 1.37 x 1.18 cm)						
Weight	0.04 lb. (0.02 kg)						
Environment	<table border="0"> <tr> <td style="vertical-align: top;">Operating temperature</td> <td>32°F to 158°F (0°C to 70°C)</td> </tr> <tr> <td style="vertical-align: top;">Operating relative humidity</td> <td>0% to 95%, non-condensing</td> </tr> <tr> <td style="vertical-align: top;">Non-operating/ Storage temperature</td> <td>-40°F to 185°F -40°C to 85°C)</td> </tr> </table>	Operating temperature	32°F to 158°F (0°C to 70°C)	Operating relative humidity	0% to 95%, non-condensing	Non-operating/ Storage temperature	-40°F to 185°F -40°C to 85°C)
Operating temperature	32°F to 158°F (0°C to 70°C)						
Operating relative humidity	0% to 95%, non-condensing						
Non-operating/ Storage temperature	-40°F to 185°F -40°C to 85°C)						
Cabling	Type: Single-mode fiber optic, complying with ITU-T G.652; Maximum distance: <ul style="list-style-type: none">● 0.5-10,000 m (single-mode fiber)						
Notes	Transmit wavelength: 1490 nm. Receive wavelength: 1310 nm. Power consumption is 1 watt maximum. For supported platforms and minimum software requirements to support this product, see the document titled "Support for the HP BX Transceivers" on the "HP Mini-GBICs and SFPs" Manuals Web page. The J9142B connects to the J9143B "upstream" transceiver, or to any IEEE-standard 1000BASE-BX10-U ("upstream") device. (A 1000-BX-D transceiver can only connect to a 1000-BX-U product. You cannot connect two 1000-BX-D transceivers together.)						
Services	Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.						

HP X122 1G SFP LC BX-U Transceiver (J9143B)

A small form-factor pluggable (SFP) Gigabit-BX (bi-directional) "upstream" transceiver that provides a full-duplex Gigabit solution up to 10 km on one strand of single-mode fiber. The J9143B connects to the J9142B "downstream" transceiver, or to any IEEE-standard 1000BASE-BX10-D ("downstream") device.

Ports	1 LC 1000BASE-BX10 port (IEEE 802.3ah Type 1000BASE-BX10-U); Duplex: full only						
Physical characteristics	<table border="0"> <tr> <td style="vertical-align: top;">Dimensions</td> <td>2.19(d) x 0.54(w) x 0.46(h) in. (5.57 x 1.37 x 1.18 cm)</td> </tr> <tr> <td style="vertical-align: top;">Weight</td> <td>0.04 lb. (0.02 kg)</td> </tr> </table>	Dimensions	2.19(d) x 0.54(w) x 0.46(h) in. (5.57 x 1.37 x 1.18 cm)	Weight	0.04 lb. (0.02 kg)		
Dimensions	2.19(d) x 0.54(w) x 0.46(h) in. (5.57 x 1.37 x 1.18 cm)						
Weight	0.04 lb. (0.02 kg)						
Environment	<table border="0"> <tr> <td style="vertical-align: top;">Operating temperature</td> <td>32°F to 158°F (0°C to 70°C)</td> </tr> <tr> <td style="vertical-align: top;">Operating relative humidity</td> <td>0% to 95%, non-condensing</td> </tr> <tr> <td style="vertical-align: top;">Non-operating/ Storage temperature</td> <td>-40°F to 185°F -40°C to 85°C)</td> </tr> </table>	Operating temperature	32°F to 158°F (0°C to 70°C)	Operating relative humidity	0% to 95%, non-condensing	Non-operating/ Storage temperature	-40°F to 185°F -40°C to 85°C)
Operating temperature	32°F to 158°F (0°C to 70°C)						
Operating relative humidity	0% to 95%, non-condensing						
Non-operating/ Storage temperature	-40°F to 185°F -40°C to 85°C)						
Cabling	Type: Single-mode fiber optic, complying with ITU-T G.652; Maximum distance: <ul style="list-style-type: none">● 0.5-10,000 m (single-mode fiber)						
Notes	Transmit wavelength: 1310 nm. Receive wavelength: 1490 nm.						

Accessory Product Details

For supported platforms and minimum software requirements to support this product, see the document titled "Support for the HP BX Transceivers" on the "HP Mini-GBICs and SFPs" Manuals Web page.

The J9143B connects to the J9142B "downstream" transceiver, or to any IEEE-standard 1000BASE-BX10-D ("downstream") device. (A 1000-BX-U transceiver can only connect to a 1000-BX-D product. You cannot connect two 1000-BX-U transceivers together.)

Power consumption is 1 watt maximum.

Services

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

HP 0.5 m Multimode OM3 LC/LC Optical Cable (AJ833A)

Cable type:

50/125 μm (core/cladding) diameter, multimode fiber optic, with effective modal bandwidth of 2000 MHz/km as detailed in TIA-492AAAC for distances of up to 300 m

Maximum distance:

10Gbps Transfer Rate (Ethernet): 300m

Notes

Cable Specs: Tight buffered duplex fiber optic multimode OM3 50/125 μm fiber optic cable and Ethernet assembly with LC duplex connectors on one end and LC duplex connectors on other end.

- Dimensions: Core diameter: $50 \pm 3.0\mu\text{m}$ Cladding diameter: $125 \pm 2.0\mu\text{m}$ Coating diameter: $245 \pm 10\mu\text{m}$
- Optical glass: Bandwidth: For LED sources: 1500/500 MHz-km @850/1300nm.
- Optical glass: Bandwidth: For Laser sources: 2000/500 MHz-km @850/1300nm. VCSEL Laser sources: 600 / 600 meters @850/1300nm for Gigabit Ethernet compliant links.
- CABLE: The cable is duplex zipcord graded index 50/125 μm multimode optical fiber and designed to work in both the 850 and 1300 nm wavelength windows.
- BULK CABLE & CABLE ASSEMBLY CONFIGURATION:
- Jacket Material: Riser Grade - Low Smoke Zero Halogen thermoplastic.
- Jacket Color: Aqua for OM3 multimode per TIA 598
- Boot Color: White
- Insertion Loss: less than 0.5 dB @ 850 with LED source, 0.003 dB/M added for lengths > 30 meters.
- Maximum Cable attenuation: 3.0 dB/km @ 850 nm, 1.0 dB/Km @ 1310 nm @ 23°C as tested in accordance with EIA 455-46.
- Weight: Air Packed Weight: 1 LB Net Weight: 0.454Kg

Services

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Accessory Product Details

**HP Premier Flex LC/LC
Multi-mode OM4 2 fiber
1m Cable (QK732A)**

Notes

Cable Specs: Graded-index, "bendable" fiber optic multimode OM3+ 50/125um duplex cable and Ethernet assembly with LC duplex connectors on each end.

- Core Diameter: 50um ±3um, Cladding diameter: 125um ±2um; Coating diameter: 245 ± 10um
- Bandwidth: 3000 MHz-km @ 850nm (Laser)
- Jacket Color: Blue
- Jacket Material: Riser Grade – Low Smoke Zero Halogen (LSZH) thermoplastic
- Boot Color: White
- Outer Jacket Print: HP PremierFlex OM3+ Fiber Optic Cable, 50/125um, Type OFNR (UL), LSZH, cUL, OFN FT4, ROHS. Cable also has a longitudinal white stripe that runs the entire length of the cable.
- Insertion Loss: Less than 0.5dB @ 850nm with LED source, 0.003dB/m added for lengths >30m
- Maximum Cable Attenuation: 3.0 dB/km @ 850nm, 1.0 dB/km @ 1310nm @ 23°C as tested in accordance with EIA 455-45

Services

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

**HP Premier Flex LC/LC
Multi-mode OM4 2 fiber
2m Cable (QK733A)**

Notes

Cable Specs: Graded-index, "bendable" fiber optic multimode OM3+ 50/125um duplex cable and Ethernet assembly with LC duplex connectors on each end.

- Core diameter: 50um ±3um, Cladding diameter: 125um ±2um; Coating diameter: 245 ± 10um
- Bandwidth: 3000 MHz-km @ 850nm (Laser)
- Jacket Color: Blue
- Jacket Material: Riser Grade – Low Smoke Zero Halogen (LSZH) thermoplastic
- Boot Color: White
- Outer Jacket Print: HP PremierFlex OM3+ Fiber Optic Cable, 50/125um, Type OFNR (UL), LSZH, cUL, OFN FT4, ROHS. Cable also has a longitudinal white stripe that runs the entire length of the cable.
- Insertion Loss: Less than 0.5dB @ 850nm with LED source, 0.003dB/m added for lengths >30m
- Maximum Cable Attenuation: 3.0 dB/km @ 850nm, 1.0 dB/km @ 1310nm @ 23°C as tested in accordance with EIA 455-45

Services

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Accessory Product Details

**HP Premier Flex LC/LC
Multi-mode OM4 2 fiber
5m Cable (QK734A)**

Notes

Cable Specs: Graded-index, "bendable" fiber optic multimode OM3+ 50/125um duplex cable and Ethernet assembly with LC duplex connectors on each end.

- Core diameter: 50um ±3um, Cladding diameter: 125um ±2um; Coating diameter: 245 ± 10um
- Bandwidth: 3000 MHz-km @ 850nm (Laser)
- Jacket Color: Blue
- Jacket Material: Riser Grade – Low Smoke Zero Halogen (LSZH) thermoplastic
- Boot Color: White
- Outer Jacket Print: HP PremierFlex OM3+ Fiber Optic Cable, 50/125um, Type OFNR (UL), LSZH, cUL, OFN FT4, ROHS. Cable also has a longitudinal white stripe that runs the entire length of the cable.
- Insertion Loss: Less than 0.5dB @ 850nm with LED source, 0.003dB/m added for lengths >30m
- Maximum Cable Attenuation: 3.0 dB/km @ 850nm, 1.0 dB/km @ 1310nm @ 23°C as tested in accordance with EIA 455-45

Services

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

**HP Premier Flex LC/LC
Multi-mode OM4 2 fiber
15m Cable (QK735A)**

Notes

Cable Specs: Graded-index, "bendable" fiber optic multimode OM3+ 50/125um duplex cable and Ethernet assembly with LC duplex connectors on each end.

- Core diameter: 50um ±3um, Cladding diameter: 125um ±2um; Coating diameter: 245 ± 10um
- Bandwidth: 3000 MHz-km @ 850nm (Laser)
- Jacket Color: Blue
- Jacket Material: Riser Grade – Low Smoke Zero Halogen (LSZH) thermoplastic
- Boot Color: White
- Outer Jacket Print: HP PremierFlex OM3+ Fiber Optic Cable, 50/125um, Type OFNR (UL), LSZH, cUL, OFN FT4, ROHS. Cable also has a longitudinal white stripe that runs the entire length of the cable.
- Insertion Loss: Less than 0.5dB @ 850nm with LED source, 0.003dB/m added for lengths >30m
- Maximum Cable Attenuation: 3.0 dB/km @ 850nm, 1.0 dB/km @ 1310nm @ 23°C as tested in accordance with EIA 455-45

Services

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Accessory Product Details

**HP Premier Flex LC/LC
Multi-mode OM4 2 fiber
30m Cable (QK736A)**

Notes

Cable Specs: Graded-index, "bendable" fiber optic multimode OM3+ 50/125um duplex cable and Ethernet assembly with LC duplex connectors on each end.

- Core diameter: 50um ±3um, Cladding diameter: 125um ±2um; Coating diameter: 245 ± 10um
- Bandwidth: 3000 MHz-km @ 850nm (Laser)
- Jacket Color: Blue
- Jacket Material: Riser Grade – Low Smoke Zero Halogen (LSZH) thermoplastic
- Boot Color: White
- Outer Jacket Print: HP PremierFlex OM3+ Fiber Optic Cable, 50/125um, Type OFNR (UL), LSZH, cUL, OFN FT4, ROHS. Cable also has a longitudinal white stripe that runs the entire length of the cable.
- Insertion Loss: Less than 0.5dB @ 850nm with LED source, 0.003dB/m added for lengths >30m
- Maximum Cable Attenuation: 3.0 dB/km @ 850nm, 1.0 dB/km @ 1310nm @ 23°C as tested in accordance with EIA 455-45

Services

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

**HP Premier Flex LC/LC
Multi-mode OM4 2 fiber
50m Cable (QK737A)**

Notes

Cable Specs: Graded-index, "bendable" fiber optic multimode OM3+ 50/125um duplex cable and Ethernet assembly with LC duplex connectors on each end.

- Core diameter: 50um ±3um, Cladding diameter: 125um ±2um; Coating diameter: 245 ± 10um
- Bandwidth: 3000 MHz-km @ 850nm (Laser)
- Jacket Color: Blue
- Jacket Material: Riser Grade – Low Smoke Zero Halogen (LSZH) thermoplastic
- Boot Color: White
- Outer Jacket Print: HP PremierFlex OM3+ Fiber Optic Cable, 50/125um, Type OFNR (UL), LSZH, cUL, OFN FT4, ROHS. Cable also has a longitudinal white stripe that runs the entire length of the cable.
- Insertion Loss: Less than 0.5dB @ 850nm with LED source, 0.003dB/m added for lengths >30m
- Maximum Cable Attenuation: 3.0 dB/km @ 850nm, 1.0 dB/km @ 1310nm @ 23°C as tested in accordance with EIA 455-45

Services

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

**HP X510 1U Cable Guard
(J9700A)**

Notes

Dimensions: 10.94" x 3.62" x 1.69" or 27.8cm x 9.2cm x 4.3cm w/ears
10.94" x 1.69" x 1.69" or 27.8cm x 4.3cm x 4.3cm without ears
Weight: 1.262 lbs or .57 kg (including faceplate, ears, and screws) 1.026 lbs or .47 kg (faceplate only)

Services

Refer to the HP website at: www.hp.com/networking/services for details

Accessory Product Details

HP X520 1U Power Adapter Notes Shelf (J9701A)

Dimensions: 10.75" x 3.75" x 1.75" or 27.3cm x 9.5cm x 4.4cm Weight: 0.316 lbs or .143 kg

Services

Refer to the HP website at: www.hp.com/networking/services for details

To learn more, visit: www.hp.com/networking

© Copyright 2010-2013 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.