

Phaser[®] 3635MFP Black-and-White Multifunction Printer



Phaser 3635MFP/S A powerful workgroup multi-tasker that offers printing, copying and advanced scanning.



Phaser 3635MFP/X This configuration adds embedded and LAN Fax and a convenience stapler.

	3635MFP/S 3635MFP/X			
Output Speed				
Single-Sided	Up to 35 ppm 8.5 x 11 in. Up to 33 ppm A4 (210 x 297 mm)			
Automatic Two-Sided	Up to 18 ppm 8.5 x 11 in. Up to 18 ppm A4 (210 x 297 mm)			
Paper Handling - Input				
Duplex Automatic Docume	nt Feeder			
Capacity*	50 sheets			
Sizes	Standard Selectable Sizes: 5.5 x 8.5 in., 8.5 x 11 in. to 8.5 x 14 in., A4, A5, JIS B5, 7.25 x 10.5, 8.5 x 13, Oficio			
Weights	12 lb. bond to 28 lb. bond (50 to 120 gsm)			
Bypass Tray				
Capacity*	50 sheets			
Sizes	Custom Sizes: 3.9 x 5.8 in. to 8.5 x 14 in. (98 x 148 mm to 216 x 356 mm)			
Weights	16 lb. bond to 43 lb. bond (60 to 163 gsm)			
Media Types	Plain paper Recycled Bond Lightweight Heavyweight Envelopes Labels Transparencies Punched Letterhead Pre-printed Archive			

Tray 1			
Capacity*	500 sheets		
Sizes	Standard Selectable Sizes: 8.5 x 11 in., 8.5 x 14 in., A4, A5, ISO B5, JIS B5, 7.25 x 10.5 in., 8.5 x 13 in., Oficio		
Weights	16 lb. bond to 28 lb. bond (60 to 105 gsm)		
Media Types	Plain paper Recycled Lightweight Punched Letterhead Pre-printed Archive		
Tray 2 (Optional)			
Capacity*	500 sheets		
Sizes	Standard Selectable Sizes: 8.5 x 11 in., 8.5 x 14 in., A4, A5, ISO B5, JIS B5, 7.25 x 10.5 in., 8.5 x 13 in., Oficio		
Weights	16 lb. bond to 28 lb. bond (60 to 105 gsm)		
Media Types	Plain paper Recycled Lightweight Punched Letterhead Pre-printed Archive		
Paper Handling - Output			
Standard Output	250 sheets		
Finishing	Offline Convenience Stapler: 20-sheet, single position (available with 3635MFP/X only)		
Print			
First-Page-Out-Time	As fast as 9 seconds		
Print Resolution	600 x 600 dpi (up to 1200 x 1200 enhanced image quality)		
Memory (Std/max)	256 MB / 512 MB		
Processor	360 MHz		
Hard Drive	80 GB		
Language Support	Postscript® 3™ compatibility PCL® 5e emulation PCL® 6 emulation		
Connectivity	10/100 Base-T Ethernet, USB 2.0		

Printing Features	Custom page size Automatic two-sided printing Watermark Secure print Sample set Delayed print Cover selection Paper selection by attribute Toner saver N-Up Mirror image Negative image Image rotation Saved settings Booklet creation Fit to new paper size Collation Print to Hard Drive Print from Hard Drive Print from Hard Drive	
Print Drivers	Microsoft® Windows® 2000//2003 Server/XP/XP Professional/Vista Mac OS® X version 10.3 Sun Microsystems Solaris™ 9/10 Linux Red Hat® ES Fedora™ Core 4 SUSE IBM AIX® 5 HP-UX 11.0/11i Novell NetWare® (IP only) SCO®	
Font Capability	136 PostScript [®] fonts 45 PCL [®] fonts	
Сору		
Document Scanner	Duplex Automatic Document Feeder with 50-sheet capacity	
Sides (input:output)	1:1, 1:2, 2:2 and 2:1	
Quantity	1 to 999	
Resolution	600 x 600 dpi	
Concurrency	Concurrent scanning and printing	
First-Copy-Out-Time	As fast as 9 seconds	

Copy Feαtures	Automatic two-sided Collation Reduce/Enlarge 25 to 400% (from Platen and ADF) Book Copying Mixed-size Originals Edge Erase Image Shift Booklet Creation Covers Auto Paper Select Lighten/Darken Transparency Separators Multi-up ID Card Copy Copy to hard drive Background Suppression			
	Color touch screen interface			
Foreign Device Interface	Interface to third-party access control devices, coin machines and card readers Supports a variety of vending stations available through the Xerox Custom Application Service			
Fax				
Embedded Fax, LAN Fax (A	Available with 3635MFP/X – 1 line)			
Fax Speed	33.6 Kbps			
Memory	Up to 40 GB of the 80 GB hard drive			
Resolution	Up to 600 x 600 dpi (superfine) resolution			
Compression	MH, MR, MMR, JPEG and JBIG			
Fax Features	Auto reduction Junk fax barrier Memory fax Polling Background suppression Mailboxes Secure Fax Fax reports			
Fax Send Features	Audio line monitor Auto fax transmission reduction Fax broadcast Fax from platen Priority send Transmission options (Report/header) Delay fax Priority fax Batch transmission Color Fax send Address book			
Fax Receive Features	Auto answer delay Junk fax prevention One or two-sided printing Fit to page Secure receive Fax forward to fax / email Fax memory receive Color fax receive			

Network Server Fax Enabl	ement (Optional)		
Fax Send Features	One- or two-sided scanning Phone number entry Add to send list (50 numbers maximum) Delay send (specific time) Resolution selection (super fine/600 x 600, super fine/400 x 400, fine/200 x 200, standard/200 x 100 dpi) Original type (photo and text, photo, text)		
Fax Print Features	One- or two-sided printing Quantity Collate on/off Secure print on/off		
Fax Vendors	Multiple vendors, certified by the Xerox Alliance Partner Program For details, visit www.xerox.com		
Scan			
Capability	Black-and-white and color scanning		
Concurrency	Scan while the system is printing copy or network print jobs, or while it is transferring scan to network or fax jobs		
Input Speed	Scan at 35 ipm (images per minute) black-and-white (8.5 x 11) / 33 ipm (A4) Scan at 24 ipm color (8.5 x 11) / 22 ipm (A4) @ 300 dpi		
Resolution	600 x 600 dpi (black-and-white only) 400 x 400 dpi (black-and-white only) 300 x 300 dpi 200 x 200 dpi 100 x 100 dpi 72 x 72 dpi		
Maximum Scan Area	8.6 x 11.9 in. / 219 x 303 mm		
Network Protocol	FTP HTTP HTTPS SMB		
File Formats	TIFF Multipage TIFF PDF JPEG		
Supported Scan Destinations	Scan to Email Scan to Network Scan to USB Memory Drive / Thumb Drive Scan to PC Desktop SE		
Scan to Email	 Direct document email from device Manual or directory Exchange/Notes/LDAP address searching "From" field auto-populated from LDAP (only when authentication is used) 		
Scan to Network	Uses templates to send scanned images to predefined locations		
Scan to USB	Scans can be loaded directly onto a user's portable USB storage device		
Scanning Solutions			
Scan to PC Desktop® SE	 A desktop and server-based offering that provides document imaging, archiving, editing and organization tools ScanSoft PaperPort – image viewing and file management software ScanSoft OmniPage (for desktop/client installation) – OCR and file format conversion software Image Retriever – provides fully automated retrieval of scanned images direct from a scan enabled Xerox WorkCentre to individual desktops 		

Accounting				
Xerox Standard Accountir	ng			
Tracking	Copy, Print, Fax and Scan usage			
Accounting	Up to 500 User accounts Up to 250 General accounts Up to 250 Group accounts			
Features	Enable/disable via the web UI or the GUI in tools, admin can manage the feature remotely via the web UI, Data can be exported via a CSV file, user required to enter XSA ID into the print driver when submitting a print job, similar to secure print.			
Network Accounting Enablement (Optional)	Enhanced Network Accounting with up to the minute data on how the device is being used; comprehensive management and enterprise scale tracking and reporting of device usage of copy, print, scan and server fax. Various options available through Xerox Alliance Partner solutions. For details visit www.xerox.com			
Accounting Control	Xerox Standard Accounting Network Accounting (with third party integration) Supports Foreign Device Interface			
Security				
Security Features	Audit log Fax security HTTPS (secure scan and network server) Image overwrite security Network authentication Secure Print User authentication			
Device Management				
Xerox CentreWare® Web				
	 A Web-based server application for network administrators that permits Web browser-based device management from any workstation, whether running Windows or UNIX or any other operating system Works with any SNMP-managed printer from any manufacturer Provides help with device discovery and installations, health checks and troubleshooting, and device upgrades, as well as basic Accounting and asset management 			
Xerox CentreWare® Interr	net Services - Integrated Device Web Page			
Device Status	Web server embedded • Tray status/contents • Consumables status			
Print Queue Viewing	Complete job print queue management – hold, release, promote and delete			
Job Submission	Print-ready files (PS, PCL, TIFF, PDF) Output feature selection			
Device Administration	Allows simple, remote installation setting of configuration options and management of the device			
Browsers	Windows® XP, 2000: Netscape Navigator®, Firefox® Microsoft® Internet Explorer Macintosh® 9.x/OS X: Netscape Navigator® 6.x, Apple® Safari™, Firefox® Linux: Netscape® 6.x			

Xerox CentreWare® for HP®	Xerox CentreWare® for HP® OpenView			
	 Provides for the identification of Xerox printers/devices in the general discovery performed by HP OpenView Provides the ability to see the current status of discovered Xerox printers/devices under a Xerox PrinterMap and IP Map via color coded icons Provides traps and message updates to the OpenView alarm browser and the ability to launch CentreWare Internet Services for device management directly from OpenView 			
Xerox CentreWare® for Tivoli® NetWare				
	 Provides for the identification of printers/devices in the general discovery performed by Tivoli NetView Provides the ability to see the discovered Xerox printers/devices in a Xerox Printers Set in addition to the Printers SmartSet Provides full integration with the NetView and Event Browser and Tivoli Enterprise Console (TEC) 			
Xerox CentreWare® for Uni	center TNG®			
	 Provides added identification to the general discovery performed by Unicenter TNG and the ability to see the device under a Unicenter TNG Business Process View Provides full integration with event management and the choice to integrate with problem management and advanced Help Desk 			
Xerox Novell Distributed Print Services Solution (NDPS)				
	Group of applications that allows an administrator to install and centrally manage printers from anywhere on a Novell network			
Device Specifications				
Duty Cycle				
	Up to 75,000 pages / month			
Electrical Requirements				
	220-240 VAC, 50/60 Hz 110-127 VAC, 50/60 Hz ENERGY STAR® qualified			
Power Consumption				
Average	600 watts			
Standby	55 watts			
Power save	15 watts			
Warm up (from power save)	25 seconds (maximum)			
Maximum Temperature Range	50° to 90° F (10° to 32° C)			
Recommended Temperature Range	61° to 86° F (16° to 30° C)			
Maximum Humidity Range	20% to 80%			
Recommended Humidity Range	30% to 70%			

Dimensions and Weights	Width	Depth	Height	Weight	
Product	18.6 in. / 472 mm	18.8 in. / 478 mm	21.4 in. / 543 mm	48.6 lbs / 22.1 kg	
Package	23.6 in. / 599 mm	23.6 in. / 599 mm	27.8 in. / 707 mm	62.17 in. / 28.2 kg	
Certifications					
	Listed to UL 60950-1/CSA 22.2 No. 60950-1-03, Class 1 Laser Product, FCC Part 15, Class A, CE marked in accor- dance with Low Voltage Directive, 2006/95/EC and EMC Directive 2004/108/EC, CB Certified against IEC 60950, Section 508 ADA				
What Comes in the Box					
	 Phaser 3635MFP Multifunction Printer Print cartridge (5,000 print capacity) Printer Installer and Utilities CD, Software and documentation CD, Registration card, Warranty booklet Power cord 				
Supplies and Options	Description			Order Number	
	High Capacity Print Cartridge – approx. 10,000*			108R00795	
				108R00793	
				098504928	
	Network Fax Server Enablement 098S04931				
	256 MB Memory Upgrade	098N02189			
	Paper Tray			098N02190	
	097N01674				
	Foreign Device Interface Kit 097N				
	Staple Cartridge			108R00823	

* Declared Yield in accordance with ISO/IEC 19752. Yield will vary based on image, area coverage and media used.

** Yield will vary depending on job run length, media size and orientation



xerox 🌒

© 2009 Xerox Corporation. All rights reserved. XEROX[®], CentreWare[®], Phaser[®], Phase