Speed, quality and productive performance in a compact, elegant design.



Canon

you can

A compact A4 mono laser printer with all the capabilities small and medium-sized businesses demand.

This network ready, compact mono laser printer with duplex printing keeps you productive and offers the performance that dynamic small and medium-sized businesses demand.

Key features

- Compact, 33ppm mono laser printer keeps you productive
- Efficient automatic double-sided printing
- Network ready for easy integration and operation
- Fast First Print Out Time of just 6 seconds or less
- No waiting with Quick First-Print technologies
- Up to 2400 x 600 dpi print resolution with Automatic Image Refinement
- Max. 800-sheet paper capacity (250-sheet cassette, 50-sheet multi-purpose tray, optional 500-sheet cassette)
- Energy efficient and silent in standby
- Maintenance-free All-in-One cartridge for continuous high quality output

What's in the box

Main unit, 719 cartridge, power cord, quick setup guide and warranty card with user software and manual CDs.

Dimensions (W x D x H)

400mm x 376mm x 263mm

Supported OS

Windows 7 (32/64bit) / Vista (32/64bit) / XP (32/64bit) / Server 2003 (32/64bit / Server 2008 (32/64bit) / Server 2008 R2 (64bit) Mac OS 10.5 and up (Web distribution only) Linux (Web distribution only) Citrix





FΔX







Specifications:





1 50-sheet multi-purpose tray 2 250-sheet cassette 3 Cartridge 719 4 Cartridge 719H

PRINTER ENGINE Print speed Printing method Print quality Print resolution Warm-up time First Page Out Time Duty cycle Print margins	33ppm mono (A4) Monochrome laser beam printing Up to 2400 x 600 dpi with Automatic Image Refinement Up to 600 x 600 dpi Approx. 10 seconds or less from power on Approx. 6 seconds or less Max. 25,000 pages per month ¹ 5mm – top, bottom, left and right	CONTROLLER Memory Printer languages Interface and connectivity Software and printer management Operating systems compatibility	16 MB CAPT (Canon Advanced Printing Technology) USB 2.0 High-Speed, 10BASE-T/100BASE-TX NetSpot Device Installer, Remote User Interface (RUI) Windows 7 (32/64bit) / Vista (32/64bit) / XP (32/64bit) / Server 2003 (32/64bit) / Server 2008 (32/64bit) / Server 2008 / R2 (64bit) / Mac OS 10.5 and up ^{34.5} / Linux ^{3.4} / Citrix
MEDIA HANDLING Paper input (Standard) Paper input (Option)	250-sheet cassette 50-sheet multi-purpose tray 500-sheet cassette	CONSUMABLES All-in-One cartridges	Standard: Cartridge 719 (2,100 pages ⁶) High yield: Cartridge 719H (6,400 pages ⁶)
Paper niput (Option) Paper output Media types	150-sheet face down Plain paper, Heavy paper, Transparency, Label, Index card, Envelope	ACCESSORIES / OPTIONS Items	Paper Feeder PF-44 (500-sheet cassette)
Media sizes	Cassette (Standard and optional): A4, B5, A5, A6, Legal, Letter, Executive, 16K, Custom sizes: Width: 105.0mm to 215.9mm; Length: 148.0mm to 355.6mm Multi-purpose tray: A4, B5, A5, A6, Legal, Letter, Executive, 16K, Envelope DL, Envelope COM10, Envelope C5, Envelope B5, Envelope Monarch, Index Card, Custom sizes: Width: 76.2mm to 215.9mm; Length: 127.0mm to 355.6mm	 Standard disclaimers. All specifications subject to change without notice. 1) Duty cycle is defined as the maximum number of printed pages for a single peak month. Any usage above the recommended duty cycle may decrease the life of the product 2) Declared noise emission in accordance with ISO 9296 3) Web distribution only 4) English driver only 5) The driver will be released in February 2013 6) Based on ISO/IEC 19752 	
Media weights	Cassette (Standard and optional): 60 to 120 g/m ² Multi-purpose tray: 60 to 163 g/m ²		
Double sided printing	Automatic		
GENERAL FEATURES			
Power requirements Power consumption	220-240V (±10%) 50/60Hz (±2Hz) Maximum: Approx. 1170 W or less Active: Approx. 540 W Standby: Approx. 9 W Sleep: 1 W Typical Electricity Consumption (TEC): 1.9 kWh/week		
Noise level	Sound power ² : Active: 7.06 B or less Standby: Inaudible Sound pressure ² : Active: 54.2 dB(A) or less Standby: Inaudible		
Dimensions (W x D x H)	400mm x 376mm x 263mm		
Weight	Approx. 11.2kg		
Operating environment	Temperature: 10 to 30°C (50 to 86°F) Humidity 20 to 80% RH (no condensation)		
Control panel	4 LED indicators 1 Operation key	J	











Canon Inc canon.com

Canon Europe canon-europe.com

European Edition © Canon Europa N.V., 2012

