

Xerox® Phaser® 6600 Color Printer and WorkCentre 6605 Color Multifunction Printer



	Phaser 6600N	Phaser 6600DN	WorkCentre 6605N	WorkCentre 6605DN
Output Speed - Color and Black and White				
One-sided	Up to 36 ppm 8.5 x 11 in. Up to 35 ppm A4 (210 x 297 mm)			
Automatic Two-sided	N/A	Up to 24 ppm 8.5 x 11 in. Up to 24 ppm A4 (210 x 297 mm)	N/A	Up to 24 ppm 8.5 x 11 in. Up to 24 ppm A4 (210 x 297 mm)
Paper Handling - Input				
Duplex Automatic Document Feeder (DADF)				
Capacity¹	N/A		50 sheets	
Sizes			Custom Sizes: 5 x 5 in. to 8.5 x 14 in. / 140 x 140 mm to 216 x 356 mm	
Weights			Simplex: 13 lb. to 32 lb. bond / 50 to 125 gsm Duplex: 16 lb. bond to 32 lb. cover / 60 to 125 gsm	
Multipurpose Tray				
Capacity¹	150 sheets			
Sizes	Custom Sizes: 3 x 5 in. to 8.5 x 14 in. / 76.2 x 127 mm to 216 x 356 mm			
Weights	16 lb. bond to 58 lb. cover / 60 to 216 gsm			
Media Types	Plain paper Hole punched Letterhead Colored Lightweight Cardstock Lightweight Glossy Cardstock Heavyweight Cardstock Heavyweight Glossy Cardstock Labels Envelopes			

¹ Paper capacities are based on 20 lb. / 75 gsm stock; capacities will vary with different weight stocks.

Xerox® Phaser® 6600 and WorkCentre® 6605

Tray 1				
Capacity ¹	550 sheets			
Sizes	Sizes: 5.8 x 8.3 in. to 8.5 x 14 in. / 148 x 210 mm to 216 x 356 mm			
Weights	16 lb. bond to 58 lb. cover / 60 to 216 gsm			
Media Types	Plain paper Hole punched Letterhead Colored Lightweight Cardstock Lightweight Glossy Cardstock Heavyweight Cardstock Heavyweight Glossy Cardstock			
Tray 2 (Optional)				
Capacity ¹	550 sheets			
Sizes	Sizes: 5.8 x 8.3 in. to 8.5 x 14 in. / 148 x 210 mm to 216 x 356 mm			
Weights	16 lb. bond to 58 lb. cover / 60 to 216 gsm			
Media Types	Plain paper Hole punched Letterhead Colored Lightweight Cardstock Lightweight Glossy Cardstock Heavyweight Cardstock Heavyweight Glossy Cards tock			
Paper Input Capacity				
Standard Capacity ¹	700 sheets			
Maximum Capacity ¹	1250 sheets			
Paper Output	Phaser 6600N	Phaser 6600DN	WorkCentre 6605N	WorkCentre 6605DN
Output Capacity ¹	250 sheets			
Automatic Two-sided Output	N/A	Standard	N/A	Standard
Print				
First-Page-Out Time	As fast as 9 seconds black-and-white / 10 seconds color			
Print Resolution	Up to 600 x 600 x 4 dpi (1200 x 1200 enhanced image quality)			
Maximum Print Area	4.1 mm from all edges			
Memory (Std/max)	256 MB / 768 MB		512 MB / 1 GB	
Optional Hard Drive	160 GB			
Processor	533 MHz			
Language Support	True Adobe® Postscript® 3™ PCL® 5 PCL® 6 XPS PDF Emulation			

¹ Paper capacities are based on 20 lb. / 75 gsm stock; capacities will vary with different weight stocks.

Xerox® Phaser® 6600 and WorkCentre® 6605

Connectivity	USB 2.0 10/100/1000Base-TX Ethernet Optional Wi-Fi (802.11 n/g/b)
Printing Features	PANTONE® Color calibrated solid-color simulations Saved settings Earth Smart settings Color Corrections N-up Booklet layout Watermark Photo mode Collation Secure Print ² Saved Print ² Font/Form/Macro Storage ³
Supported Operating Systems	Windows® XP SP1, Vista, 7, 2008 Server, 2003 Server Mac OS® 10.5 and later Various Linux and Unix distributions, including: IBM® AIX 5 HP-UX® 11i v2 Open SUSE 11 Red Hat Fedora Core 11-14 Ubuntu
Print Drivers	Windows® XP and later Mac OS® 10.5 and later Xerox® Global Print Driver® Xerox® Mobile Express Driver®
Font Capability	176 PostScript® fonts 88 PCL® fonts
Xerox® Mobile Express Driver® (X-MED)	Makes it easy for mobile users to find, use and manage Xerox® and non-Xerox devices in every new location. Plug into a new network, and X-MED automatically discovers available printers and provides status and capability information. Save a list of “favorite” printers for each location, store application print settings for use on any printer in any network, and greatly reduce mobile support calls to IT. <ul style="list-style-type: none"> • Printers are automatically discovered • Printer list can be managed based on location • Gives Bi-directional feedback device status, supplies, queue management
Xerox® Global Print Driver® (X-GPD)	A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non-Xerox devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management. <ul style="list-style-type: none"> • Printers are automatically discovered • Printer list can be managed based on location • Gives Bi-directional feedback device status, supplies, queue management

² Standard on WorkCentre 6605, requires optional Productivity Kit on Phaser 6600

³ Requires Productivity Kit (with 160 GB Hard Drive)

Xerox® Phaser® 6600 and WorkCentre® 6605

Copy	Phaser 6600	WorkCentre 6605
Copy Speed		Simplex: Up to 36 ipm (images per minute) 8.5 x 11 in. / 35 ipm A4 Duplex: Up to 24 ipm 8.5 x 11 in. / A4
Document Scanner		Duplex Automatic Document Feeder with 50-sheet capacity
Document Scanner Size		Platen: Up to 8.5 x 11 in. / A4 DADF: Up to 8.5 x 14 in. / 216 x 356 mm
Sides (input:output)		1:1, 1:2, 2:2 and 2:1
Quantity		1 to 99
Resolution		Up to 600 x 600 dpi
First-copy-out Time		As fast as 13 seconds black-and-white / 16 seconds color
Copy Features		Reduce/Enlarge (25% - 400%) Lighter/Darker Color Saturation Sharpness Color Balance Auto Exposure 2-up Output AutoFit Cloning Collate (up to 50 pages)
Fax	Phaser 6600	WorkCentre 6605
Fax Speed		33.6 Kbps
Memory		4 MB
Resolution		Up to 300 x 300 dpi (Super Fine / Photo) resolution Up to 203 x 196 dpi (Fine) resolution Up to 203 x 98 dpi (Standard) resolution
Compression		MH, MR, MMR, JBIG
Walk-up Fax Features ⁴		Reject Junk Fax Distinctive Ring Pattern Detection Fax Forwarding and Local Print Polling Receive Delayed Start (up to 24 hours) Broadcast Sending (up to 200 destinations) Fax Address Book (up to 200 speed dials) Secure Fax Receive
LAN Fax Features		Delayed Start (up to 24 hours) Broadcast Sending (up to 30 destinations) Zoom Auto Fit Rotation N-up Watermark Phonebook (Up to 500 speed dial numbers, up to 500 group dials, phonebook stored on PC)

⁴ Analog phone line required

Xerox® Phaser® 6600 and WorkCentre® 6605

Scan	Phaser 6600	WorkCentre 6605
Capability	N/A	Black-and-white and color scanning
Input Speed - B/W		Simplex: Scan up to 22 ipm – 8.5 x 11 in. / A4 Duplex: Scan up to 7 ipm – 8.5 x 11 in. / A4
Input Speed - Color		Simplex: Scan up to 13 ipm – 8.5 x 11 in. / A4 Scan up to 4 ipm – 8.5 x 11 in. / A4
Resolution (maximum)		Up to 1200 x 1200 dpi
Bit Depth		48-bit color, 16-bit grayscale
Maximum Scan Area		Platen: Up to 8.5 x 11 in. / A4 DADF: Up to 8.5 x 14 in. / 216 x 356 mm
Network Filing Protocol		FTP SMB
File Formats		PDF TIFF (single and multi-page) JPEG
Scan Driver Compatibility		WIA TWAIN
Supported Scan Destinations		Scan to Computer via SMB Scan to Server via FTP Scan to Email with LDAP support Scan to USB Memory Device WSD Scanning
Scanning Solutions		
Xerox® Scan to PC Desktop Personal Edition	N/A	A desktop and server-based offering that provides document imaging, archiving, editing and organization tools <ul style="list-style-type: none"> • Nuance PaperPort – image viewing and file management software • Nuance OmniPage (for desktop/client installation) – OCR and file format conversion software • Image Retriever – provides fully automated retrieval of scanned images direct from a scan enabled Xerox® WorkCentre to individual desktops.
		For a complete list of scanning solutions, visit www.xerox.com
Security		
Security Features	Secure Fax Receive (WorkCentre 6605 only) Secure Print ⁵ 256-bit disk encryption and overwrite ⁶ Secure HTTPS (SSL, Secure LDAP ⁶) IPsec 802.1X Authentication IPv6 SNMPv3 Audit Log IP Filtering	

⁵ Standard on WorkCentre 6605, requires optional Productivity Kit on Phaser 6600

⁶ Requires Productivity Kit (with 160 GB Hard Drive)

Xerox® Phaser® 6600 and WorkCentre® 6605

Wi-Fi Security			
	Authentication Method	Encryption	Hard Drive Required
	Open WPA PSK WPA PSK / WPA2 PSK	WEP 64/128 ASCII/HEX TKIP AES	No
	WPA Enterprise WPA Enterprise / WPA 2 Enterprise WPA Enterprise AuthenticationMethod options: PEAPVO MS-CHAPV2 EAP-TLS EAP-TTLS PAP EAP-TTLS CHAP	TKIP AES	Yes
Device Management			
Xerox CentreWare® Web			
	<ul style="list-style-type: none"> • A Web-based server application for network administrators that permits web browser-based device management from any workstation, whether running Windows or UNIX or any other operating system • Works with any SNMP-managed printer from any manufacturer • Provides help with device discovery and installations, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management 		
Xerox® CentreWare® Internet Services - Integrated Device Web Page			
Device Status	Web server embedded <ul style="list-style-type: none"> • Tray status/contents • Consumables status 		
Print Queue Viewing	Complete job print queue management—hold, release, promote and delete		
Job Submission	Print-ready files (PS, PCL, TIFF, PDF) Output feature selection		
Device Administration	Allows simple, remote installation setting of configuration options and management of the device		
Browsers	Microsoft® Internet Explorer 7 Firefox® version 4 and above		
Xerox® Mobile Solutions			
Xerox® PrintBack	PrintBack takes the capabilities of the printer you already use, and extends them beyond your computer and out to your Apple iOS- or Android-based mobile device. When you're working offsite or away from your desk and receive an important document via your mobile device, simply use PrintBack to print it with your default printer back at your office or desk. Plus, it supports the most common office file types (Microsoft® Office documents, PDF, etc.) with uncompromised print quality.		
Xerox® Mobile Express Driver®	The Xerox® Mobile Express Driver is a single, universal printer driver that can be downloaded to a PC and used to print to virtually any PostScript device on the network, including printers made by other manufacturers. Instead of downloading individual printer drivers for each product in each office, users can download the single, simple, Mobile Express Driver.		
Device Specifications			
Duty Cycle			
	Up to 80,000 pages per month ⁷		
Recommended Monthly Print Volume			
	Up to 5,000 pages per month ⁸		

⁷ Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

⁸ Range reflects the number of pages per month the product can regularly print while maintaining optimal performance (considering factors including supplies replenishment and reliability over the expected product life).

Xerox® Phaser® 6600 and WorkCentre® 6605

Power Consumption	Phaser 6600	WorkCentre 6605
110-127 VAC, 50/60 Hz, 10A		
Printing (average operations)	540 watts	520 watts
Standby Mode	65 watts	69 watts
Power Save Mode	3.3 watts	5.7 watts
220-240 VAC, 50/60 Hz, 5A		
Printing (average operations)	520 watts	560 watts
Standby Mode	64 watts	72 watts
Sleep Mode	4 watts	5.9 watts
Warm up (from sleep)	As fast as 21 seconds	As fast as 25 seconds
Warm up (from power on)	As fast as 40 seconds	As fast as 44 seconds
Storage Temperature Range	32° to 95° F (0° to 35° C)	
Operating Temperature Range	50° to 90° F (10° to 32° C)	
Operating Humidity	10% to 85%	
Storage Humidity	5% to 85%	
Operating Altitude	Up to 3,100 meters	
Shipping Altitude	Up to 15,000 meters when pressurized at 70.9275 kPa or greater	
Sound Pressure Levels	Phaser 6600	WorkCentre 6605
Printing / Copying	53 dB(A)	52 dB(A)
Standby	29 dB(A)	29 dB(A)
Sound Power Levels		
Printing / Copying	6.9 B	6.8 B
Standby	4.5 B	4.4 B

Xerox® Phaser® 6600 and WorkCentre® 6605

Dimensions and Weights (Unpackaged)	Width	Depth	Height	Weight (with CRUs)
Phaser 6600	16.9 in. / 430 mm	19.2 in. / 488 mm	15.1 in. / 384 mm	56.2 lbs / 25.5 kg
WorkCentre 6605	16.9 in. / 430 mm	20.8 in. / 528 mm	22 in. / 560 mm	71.7 lbs / 32.5 kg
550-sheet Feeder	16.8 in. / 427 mm	19.1 in. / 485 mm	5.4 in. / 138 mm	5.7 lbs / 2.6 kg
Dimensions and Weights (Packaged)	Width	Depth	Height	Weight
Phaser 6600	22.4 in. / 570 mm	27 in. / 686 mm	20.7 in. / 526 mm	67.2 lbs / 30.5 kg
WorkCentre 6605	22.4 in. / 570 mm	27 in. / 686 mm	27.8 in. / 706 mm	82.7 lbs / 37.5 kg
550-sheet Feeder	23.2 in. / 590 mm	21.4 in. / 544 mm	9.5 in. / 241 mm	11.5 lbs / 5.2 kg
Certifications				
	<p>FCC Part 15 Class B, RoHS Directive 2002/95/EC, WEEE Directive 2002/96/EC, Low Voltage Directive 2006/95/EC, EN 60950-1, EN 60825-1 – Class 1 Laser Product, EMC Directive 2004/108/EC, EN 55022, Class B, EN 55024, Listed to UL/CSA 60950-1, FDA 21 CFR Part 1010, 1040 – Class 1 Laser Product, CB Report, IEC 60950-1, IEC 60825-1 – Class 1 Laser Product, Section 508 ADA</p> <p>ENERGY STAR® (DN configuration), Microsoft WHQL, Adobe® PostScript®, PANTONE®, ECMA 370 Declaration (Nordic), GOST/NOM, GS Mark, Environmental Choice, Xerox® Green World Alliance, USB 2.0 Hi-Speed, WiFi Alliance (option), WLAN certified (option), Apple® Bonjour, IPv6 Ready logo, Citrix Ready, SAP, PTT (WorkCentre 6505 only)</p>			
What Comes in the Box				
	<p>Phaser 6600 or WorkCentre 6605 Starter Toner Cartridges – One of each (Cyan, Magenta, Yellow: 2,000 print capacity⁹; Black: 3,000 print capacity⁹) Quick Use Guide, Quick Install Guide Software and Documentation CD (with Drivers, User Manual and Warranty Statement) Scan Software (WorkCentre 6505 only) Power cord Fax cord (WorkCentre 6505 only)</p>			

⁹ Average standard pages. Declared Yield in accordance with ISO/IEC 19798. Yield will vary based on image, area coverage and print mode.

¹⁰ Average standard pages. Yield will vary depending on job run length, media size and orientation.

Xerox® Phaser® 6600 and WorkCentre® 6605

Supplies and Options	Description	Order Number
Standard-Capacity Print Cartridges ⁹	Black: 3,000 pages	106R02244
	Cyan: 2,000 pages	106R02241
	Magenta: 2,000 pages	106R02242
	Yellow: 2,000 pages	106R02243
High-Capacity Print Cartridges ⁹	Black: 8,000 pages	106R02228
	Cyan: 6,000 pages	106R02225
	Magenta: 6,000 pages	106R02226
	Yellow: 6,000 pages	106R02227
Routine Maintenance Items ¹⁰	Imaging Unit Kit: Up to 60,000 pages	108R01121
	Waste Cartridge: Up to 30,000 pages	108R01124
	550-sheet Feeder	097S04400
	Productivity Kit (512 MB RAM)	097S04269
	Productivity Kit (160 GB Hard Drive)	097S04403
	Wireless Networking Adapter	097S04409
	Wireless Network Adapter North American power converter European power converter UK power converter	097S03740 097S03741 097S03742

⁹ Average standard pages. Declared Yield in accordance with ISO/IEC 19798. Yield will vary based on image, area coverage and print mode.

¹⁰ Approximate pages. Declared yield based on an average job size of 3 A4-/letter-size pages. Yield will vary depending on job run length and media size and orientation.

