APC Back-UPS[®] Pro 1200/1500

Premium Battery Backup with Surge Protection for Electronics and Computers

The Back-UPS Pro provides abundant battery backup power, so you can work through medium and extended length power outages. It safeguards your equipment against damaging surges and spikes that travel along utility and data lines. The Back-UPS Pro also features automatic voltage regulation (AVR), which instantly adjusts high and low voltages to safe levels, so you can work indefinitely during brownouts and overvoltages. The Back-UPS Pro also includes unique "green" features, like power-saving outlets that automatically turn off idle peripherals. A high efficiency charging system and "AVR Bypass" also reduce power consumption. With the rest of the Back-UPS Pro's standard features, this is the perfect unit to protect your productivity from the constant threat of bad power and lost data.



Back-UPS Pro 1200 & 1500 Specifications		
Model Number	BR1200GI	BR1500GI
Output		
Output Capacity	1200 VA / 720 Watts	1500 VA / 865 Watts
Output Volt., Freq. (on utility)	230V, 50 or 60 Hz, +/- 3Hz (auto sensing)	230V, 50 or 60 Hz, +/- 3Hz (auto sensing)
Output Volt., Freq. (on battery)	230V +/-8%, 50 or 60 Hz +/-1 Hz (auto sensing)	230V +/-8%, 50 or 60 Hz +/-1 Hz (auto sensing)
Output Connections	10 total IEC outlets: 5 battery & surge (incl. 1 power-saving <i>Controlled</i> outlet) 5 surge only (incl. 3 power-saving <i>Controlled</i> outlets)	10 total IEC outlets: 5 battery & surge (incl. 1 power-saving <i>Controlled</i> outlet) 5 surge only (incl. 3 power-saving <i>Controlled</i> outlets)
Waveform Type	Stepped Approximation to Sine Wave	Stepped Approximation to Sine Wave
Input		
Input Voltage, Frequency	230V, 50 or 60 Hz, +/- 3Hz	230V, 50 or 60 Hz, +/- 3Hz
Input Connection	Use existing power cord for system (2 ea 1,8 m IEC-320 jumpers also provided)	Use existing power cord for system (2 ea 1,8 m IEC-320 jumpers also provided)
Surge Protection		
AC Power Surge Protection	All outlets	All outlets
Data Line Surge Protection	Analog phone line for phone/fax/modem/DSL Network: 10/100/1000 Base-T (gigabit) Ethernet	Analog phone line for phone/fax/modem/DSL Network: 10/100/1000 Base-T (gigabit) Ethernet
Physical		
Unit Dimensions (H x W x D)	30,2 x 11,2 x 38,1 cm	30,2 x 11,2 x 38,1 cm
Unit Weight	12,8 kg	13,4 kg
Shipping Dims. (H x W x D)	38,2 x 23,8 x 48,9 cm	38,2 x 23,8 x 48,9 cm
Shipping Weight	13,9 kg	14,5 kg
Color	Black	Black
UPC Code	731304268758	731304268741
Battery		
Battery Type	Sealed, lead-acid, maintenance-free	Sealed, lead-acid, maintenance-free
External Battery Pack Compatibility	No	Yes p/n: BR24BPG
Management		
Alarms	Visual (LCD) and audible alarms	Visual (LCD) and audible alarms
Auto-Shutdown Software	PowerChute Personal Edition (via USB and serial interface)	PowerChute Personal Edition (via USB and serial interface)
Safety		
Certification/Approvals	NEMKO-GS, GOST, CE	NEMKO-GS, GOST, CE

APC by Schneider Electric 132 Fairgrounds Rd West Kingston, RI 02892



www.apc.com