The robust, smart and fast colour printer that thrives in busy environments.





## you can

Canon's flagship colour laser printer with MEAP is the premier choice for office environments.

Canon's premier A4 laser printer offers up to 32ppm in both colour and mono. Next-generation MEAP technology makes it a versatile addition to busy enterprise workgroups that print in high volumes.

### **Key features**

- 32ppm colour and mono laser printer for busy enterprise workgroups
- Up to 9600 x 600 dpi equivalent print resolution creates superb quality results
- No waiting with Quick First-Print technologies
- Productive First Print Out Time of 10.4 seconds
- MEAP enabled for uniFLOW and solution integration
- Max. 1100-sheet paper capacity to keep downtime to a minimum
- Productive automatic double-sided printing
- Network ready
- PCL5c/6 and Adobe PostScript Level 3 support
- Direct print from USB storage
- Highly energy efficient
- Canon Mobile Printing app for iPad<sup>®</sup> and iPhone<sup>®</sup>

#### What's in the box

Main unit, 732 C/M/Y/K cartridge, power cord, starter guide and warranty card with user software and manual CDs.

**Dimensions (W x D x H)** 517mm x 530mm x 401mm

#### Supported OS

Windows 7 (32bit/64bit) / XP (32bit/64bit) / Vista (32bit/64bit) / Server 2003 (32bit/64bit) / Server 2008 (32bit/64bit) Mac OS 10.5 and up (Web distribution only) Linux (Web distribution only) Citrix



SCAN







# Specifications:



#### 1 5-line LCD display

- 2 100 sheet multi-purpose tray
- 3 500-sheet tray
- 4 Optional 500-sheet cassette 5 Cartridge 732:
- 5 cartridges available: Cyan, Magenta, Yellow, Black and Black H

PRINTER ENGINE	)	CONTROLLER	
Print speed	Up to 32ppm colour and mono (A4)	Processor Speed	528MHz + 264MHz
Printing method	Colour laser beam printing	Memory	768 MB
Print quality	Up to 9600 x 600 dpi with Automatic Image Refinement	Printer languages	UFRII (Ultra Fast Rendering), PCL5c, PCL6, Adobe PostScript
Print resolution	Up to 600 x 600 dpi	Fonts	93 Scalable fonts, 10 Bitmap fonts, 136 PS fonts
Warm-up time	Approx. 39 seconds or less from power on	Software and	Remote User Interface (RUI), Secure Print with optional
First Page Out Time	Mono: Approx. 10.2 seconds or less	printer management	SD Card-B1, Canon Mobile Printing app for iPad® and iPhone®
i iisti üğe ölüt iline	Colour: Approx. 10.4 seconds or less	Interface and connectivity	USB Host, USB 2.0 High-Speed, 10BASE-T/100/1000BASE-TX
Duty cycle	Max. 75,000 pages per month <sup>1</sup>	Operating systems	Windows 7 (32bit/64bit) / XP (32bit/64bit) / Vista (32bit/64bit) /
Print margins	5mm – top, bottom, left and right	compatibility	Server 2003 (32bit/64bit) / Server 2008 (32bit/64bit) /
, internargins	Sinn top, bottom, icit and right	compatibility	Mac OS 10.5 and up <sup>3</sup> / Linux <sup>3</sup> / Citrix
MEDIA HANDLING			•
Paper input (Standard)	500-sheet cassette	CONSUMABLES	
	100-sheet multi-purpose tray	All-in-One cartridges	Cartridge 732 Black (6,100 pages⁴)
Paper input (Option)	500-sheet cassette	5	Cartridge 732H Black (12,000 pages <sup>4</sup> )
Paper output	200-sheet face down		Cartridge 732 Cyan (6,400 pages <sup>4</sup> )
Media types	Plain paper, Recycled paper, Heavy paper, Transparency,		Cartridge 732 Magenta (6,400 pages <sup>4</sup> )
	Label, Envelope		Cartridge 732 Yellow (6,400 pages <sup>4</sup> )
Media sizes	Cassette (Standard):		Waste Toner Box: WT-723 (Approx.18,000 A4 pages)
incuta sizes	A4, B5, A5, A6, Letter, Executive, Foolscap, 16K, Statement		
	Custom sizes: Width: 101.6mm to 215.9mm;	ACCESSORIES / OPTIONS	
	Length: 148.0mm to 297.0mm	ltems	Paper Feeder PF-723A (500-sheet cassette)
	When width is 215.9mm, max length is 279.4mm		SD Card-B1 Barcode Printing Kit - F1 (Barcode ROM module)
	When length is 297.0mm, max width is 210.0mm		barcode Frinking Kit - Fri (barcode Kom module)
	Multi-purpose tray:	Standard disclaimers All spec	ifications subject to change without notice.
	A4, B5, A5, A6, Legal, Letter, Executive, Statement, Foolscap,		maximum number of printed pages for a single peak month.
	16K, Envelope DL, Envelope COM10, Envelope C5, Envelope		nmended duty cycle may decrease the life of the product
	Monarch, 3x5 Index Card,	2] Declared noise emission in	
	Custom sizes: Width: 76.2mm to 215.9mm;	3] Web distribution only	
	Length: 127.0mm to 355.6mm	4] Based on ISO/IEC 19798	
	Cassette (Optional):		)
	A4, B5, A5, Legal, Letter, Executive, 16K, Foolscap		
	Custom sizes: Width: 148.0mm to 215.9mm; Length: 210.0mm to 355.6mm		
Media weights	Cassette (Standard): 60 to 163 g/m <sup>2</sup>		
	Multi-purpose tray: 60 to 216 g/m <sup>2</sup>		
	Cassette (Optional): 60 to 176 g/m <sup>2</sup>		
Double sided printing	Automatic		
GENERAL FEATURES			
Power requirements	220-240V (±10%) 50/60Hz (±2Hz)		
Power consumption	Maximum: 1270 W or less		
	Active: Approx. 580 W or less		
	Standby: Approx. 35 W		
	Sleep mode: Approx. 1 W		
	Typical Electricity Consumption (TEC): 2.0kWh/week		
Noise level	Sound power <sup>2</sup> :		
	Active: 7 B or less		
	Standby: 5.3 B or less		
	Sound pressure <sup>2</sup> :		
	Active: 52 dB(A) or less		
<b>D</b>	Standby: 32.4 dB(A) or less		
Dimensions (W x D x H)	517mm x 530mm x 401mm		
Weight	Approx. 31kg		
Operating environment	Temperature: 10 to 30°C (50 to 86°F)		
	Humidity 20 to 80% RH (no condensation)		
Control panel	LCD 22 characters x 5 line LCD display		
	8 LED indicators		
	12 Operation keys		







Canon Inc canon.com

Canon Europe canon-europe.com

**European Edition** © Canon Europa N.V., 2012

