Overview



- 1. Power LED
- 2. HP Webcam Control Center button
- **3.** Integrated microphone

Model

HP USB HD 720p v2 Business Webcam

Introduction

Easily connect with colleagues for all of your videoconferencing needs.1 The HP USB HD 720p v2 Business Webcam delivers professional video/audio in a compact design that connects to any USB port on your PC and sits neatly on top of your monitor.

4. USB connector cable

5. Adjustable clip/stand



D8Z08AA

Overview

Performance and Features

- Enjoy a business-class 720p, true 16:9 HD image and 360° pan/30° tilt adjustability that captures multiple users. Reduce background noise during videoconferencing1 with the directional microphone.
- Get up and running quickly with the included USB cable and easy software installation. Simply clip the webcam to your monitor and you're ready to go.
- The lightweight and ultra-compact design clips neatly onto your LED or LCD monitor without blocking the screen, so you can leave it attached when not in use.

Compatibility

The HP USB HD 720p v2 Business Webcam is compatible with the HP ProDesk 600 G1 TWR, SFF; HP EliteDesk800 G1 TWR, SFF, USDT; HP Compaq 6305 Pro MT, SFF.

NOTE: Please check this product's web page on HP.com for current compatibility information. **NOTE:** Not all models are available in all regions.

Service and Support

Your Option Limited Warranty is a one (1) year (HP Option Limited Warranty Period) parts replacement warranty on any HP-branded or Compaq-branded options (HP Options). If your HP Option is installed in an HP Hardware Product, HP may provide warranty service either for the HP Option Limited Warranty Period or the remaining Limited Warranty Period of the HP Hardware Product in which the HP Option is being installed, whichever period is the longer but not to exceed three (3) years from the date you purchased the HP Option.



QuickSpecs

Technical Specifications

Main Features

Image sensor	1 Megapixel sensor, 1280 x 800p, CMOS
Chipset	Realtek RTS5822
Focusing	Fixed focus (30-70 cm)
Audio	Built-in high quality microphone
Power LED	White LED on during video preview, LED off when camera not in use
Color Depth	24-bit true color
Video Resolution	VGA – up to 30 fps
	1280 x 720 p – up to 30 fps

Navigation Controls

Snapshot	Button
----------	--------

Single frame still image captureQuick launch application software

Cables and Connectors

PC Connection	USB 2.0 (high speed and full speed)
Cable Type	Tethered USB cable with type A receptacle
Cable Length	120 cm (from connector housing to USB plug)

Performance

Image Sensor	1 Megapixel sensor, 1280 x 800p, CMOS
Array Format (active)	1280 (H) x 800 (V) pixels
Scan Mode	Progressive
Color Filter Array	RGB Bayer pattern
Pixel Size	1.75pm x 1.75pm

Optics

Lens type	3P
F/#	2.4
Effective Focal Length	1.92 mm
Effective Focal Range	Range of 30 to 70 cm
View Angle	69 degrees diagonal

Video Control

Exposure Control	Auto with target brightness adjustable
White Balance	Auto & manual

Video Modes & Resolutions



QuickSpecs

Humidity 0% to 90% 0% to 90%

Technical Specifications

Video Resolutions	The frame rates below are supported.
	 160 x 120, 30 fps. (SQVGA) 176 x 144, 30 fps. (QCIF) 320 x 240, 30 fps. (QVGA) 352 x 288, 30 fps. (CIF) 640 x 480, 30 fps. (VGA) 800 x 600, 30 fps 1280 x 720, 30 fps
Frequency Range	50 Hz/60Hz selectable
Video Mode	YUY2, MJPG
Power Consumption	
Source	USB DC 5V + 5%V supply
Voltage	Min 4.75V, Max 5.25V
Environmental	Temperature
Operating	32° to 104° F (0° to 40° C)
Storage (Non-Operating)	-4° to 140° F (-20° to 60° C)
Regulatory Approvals	& Certifications
Main Camera Ilnit	FCC_CE_LIIMicrosoft WHOL_LISB version 2.0 compliance and L

Main Camera Unit FCC, CE, UL, Microsoft WHQL, USB version 2.0 compliance and USB 1.1 compatible.

Software Specifications

oor that o op contract	
USB Driver PID	03F0
USB Driver VID	E207
Driver Support	Windows Driver Model (WDM) for DirectShow
Included Software	The CD that comes with your webcam includes the following software:
	 Webcam drivers – enable your webcam to operate with optimum performance. Video Call Quick Launch – helps you set up your chat program to communicate with your webcam. Video/photo capture program HP Webcam Control Center – enables you to access all of your webcam functions from a single location on your desktop.
	You can download webcam software from www.hp.com/support .
Operating System Support	Windows 8 Pro Windows 8 Windows 7 (With WHQL) Windows Vista® (With WHQL) Windows XP® (SP2 with WHQL)

Minimum System Requirements

PC Platform The HP Webcam HD can record video up to 720p resolution 30 fps. To use your webcam with the included



QuickSpecs

Technical Specifications

software, your computer must meet the following minimum system requirements:

- Windows® XP, Windows Vista®, Windows 7, or Windows 8
- Intel[®] Pentium 4 with 2.4 GHz or AMD Athlon equivalent processor or faster; 1.6-GHz Dual Core recommended
- 1 GB RAM minimum; 2 GB RAM recommended
- 230 MB free hard drive space required for program installation
- DVD/CD-ROM drive
- USB 2.0 high speed port

Mechanical Specifications

Dimensions ($H \times W \times D$)	1.85 x 2.73 x 1.69 in (47 x 69.3 x 43.1 mm)
Weight (unboxed, webcam only)	1.59 oz (45 g)
Base	Adjustable clip/stand for notebooks/LCD monitors
Tilt Angle/Pan	30° ±3° / 360°

Other

Option kit contents

- One HP USB HD 720p v2 Business Webcam with attached USB cable to connect to your PC
- Software CD
- User Guide
- HP Warranty documentation

© Copyright 2013 Hewlett-Packard Development Company, L.P.

The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein. The information contained herein is subject to change without notice. Windows and Vista are U.S. registered trademarks of Microsoft Corporation.

