

Overview

Models

HP 2615-8-PoE Switch

J9565A

Key features

- Scalable 10/100 connectivity
- Layer 2 and 3 switching capabilities
- sFlow, ACLs, and rate limiting
- Energy-efficient design and quiet operation
- Rack-mountable, compact form factor

Product overview

The HP 2615-8-PoE Switch is a fully managed 8-port 10/100 switch with an additional two dual-personality Gigabit Ethernet ports for copper or SFP connectivity. Together with static and RIP IPv4 routing, robust security and management, enterprise-class features, a free lifetime warranty, and free software updates, the HP 2615-8-PoE Switch is a cost-effective solution.

The HP 2615-8-PoE Switch is fanless, providing quiet operation and making it ideal for deployments in open spaces. In addition, the compact form factor allows for flexible deployments, including wall, surface, or rack mounting.

These switches can be deployed at enterprise edge and remote branch offices, as well as converged networks.

Features and benefits

Quality of Service (QoS)

- **Selectable queue configuration**
performance and/or traffic reliability can be increased by selecting the number of queues that best meet the requirements of network applications; the switch will map 8 priorities to either 2 or 4 queues
- **Class of Service (CoS)**
sets the IEEE 802.1p priority tag based on IP address, IP Type of Service (ToS), Layer 3 protocol, TCP/UDP port number, source port, and DiffServ
- **Layer 4 prioritization**
enables prioritization based on TCP/UDP port numbers
- **Traffic prioritization (IEEE 802.1p)**
allows real-time traffic classification into eight priority levels mapped to four queues
- **Rate limiting**
per-port ingress-enforced maximum
- **Flow control**
helps ensure reliable communications during full-duplex operation
- **Type of service**
 - **IP precedence**
honors IP precedence bits and allows mapping to a priority queue
 - **Differentiated Services Code Point values**
honors Differentiated Services Code Point (DSCP) bits and allows mapping to a priority queue

Management



Overview

- **Choice of management interfaces**
 - **Web graphical user interface (GUI)**
easy-to-use graphical interface allows configuration of the switch from any Web browser
 - **Command-line interface (CLI)**
robust command-line interface provides advanced configuration and diagnostics
 - **Simple Network Management Protocol (SNMPv2c/SNMPv3)**
allows switch to be managed with a variety of third-party network management applications
- **Multiple configuration files**
configuration file management tools allow up to three configuration files to be managed and stored on the switch
- **Dual flash images**
provide independent primary and secondary operating system files for backup while upgrading
- **Dual flash images**
provide independent primary and secondary operating system files for backup while upgrading
- **Command authorization**
leverages RADIUS to link a custom list of CLI commands to an individual network administrator's login; also provides an audit trail
- **Front-panel LEDs**
 - **Locator LED**
allows users to set the locator LED on a specific switch to either turn on, blink, or turn off; simplifies troubleshooting by making it easy to locate a particular switch within a rack of similar switches
 - **Per-port LEDs**
provides an at-a-glance view of status, activity, speed, and full-duplex operation
 - **provides an at-a-glance view of status, activity, speed, and full-duplex operation**
power LED and fault LEDs display any issues

Connectivity

- **Dual-personality functionality**
two 10/100/1000 ports or SFP slots provide optional fiber connectivity such as Gigabit-SX, -LX, -LH, 100-FX, 100-BX, and 1000-BX
- **IEEE 802.3af Power over Ethernet**
provides up to 15.4 W per port to IEEE 802.3af-compliant PoE-powered devices such as IP phones, wireless access points, and security cameras (see product specifications for total PoE power available)
- **Auto-MDIX**
automatically adjusts for straight-through or crossover cables on all 10/100 ports
- **RJ-45 serial console port**
provides easy accessibility on front of the unit to the switch CLI
- **IPv6**
 - **IPv6 host**
the switches can be managed and deployed at the edge of IPv6 networks
 - **Dual stack (IPv4/IPv6)**
provides transition mechanism from IPv4 to IPv6; supports connectivity for both protocols
- **Single IP address management**
single IP address management for a virtual stack of up to 16 switch

Resiliency and high availability

- **IEEE 802.1s Multiple Spanning Tree**
provides high link availability in multiple VLAN environments by allowing multiple spanning trees; provides legacy support for IEEE 802.1d and IEEE 802.1w

Overview

- **Port trunking and link aggregation**
 - **Trunking**
supports up to eight links per trunk to increase bandwidth and create redundant connections
 - **IEEE 802.3ad Link Aggregation Protocol (LACP)**
eases configuration of trunks through automatic configuration
- **SmartLink**
provides easy-to-configure link redundancy of active and standby links

Layer 2 switching

- **GARP VLAN Registration Protocol**
allows automatic learning and dynamic assignment of VLANs
- **VLAN support and tagging**
supports IEEE 802.1Q (4,094 VLAN IDs) and 256 VLANs simultaneously
- **Per-VLAN Spanning Tree Plus (PVST+)**
allows each VLAN to build a separate spanning tree to improve link bandwidth usage in network environments with multiple VLANs

Layer 3 routing

- **Static IP routing**
provides manually configured routing; includes ECMP capability
- **Routing Information Protocol (RIP)**
provides RIPv1 and RIPv2 routing

Security

- **Access control lists (ACLs)**
provide IP Layer 3 filtering based on source/destination IP address/subnet and source/destination TCP/UDP port number
- **Identity-driven ACL**
enables implementation of a highly granular and flexible access security policy and VLAN assignment specific to each authenticated network user
- **Source-port filtering**
allows only specified ports to communicate with each other
- **RADIUS/TACACS+**
eases switch management security administration by using a password authentication server
- **Secure protocols for encryption of management traffic**
- **Secure Shell (SSHv2)**
encrypts all transmitted data for secure, remote CLI access over IP networks
- **Secure Sockets Layer (SSL)**
encrypts all HTTP traffic, allowing secure access to the browser-based management GUI in the switch
- **Secure FTP (SFTP)**
encrypts uploads and downloads of configuration file
- **Port security**
allows access only to specified MAC addresses, which can be learned or specified by the administrator
- **Dynamic IP lockdown**
works with DHCP protection to block traffic from unauthorized hosts, preventing IP source address spoofing
- **DHCP protection**
blocks DHCP packets from unauthorized DHCP servers, preventing denial-of-service attacks
- **Dynamic ARP protection**

Overview

blocks ARP broadcasts from unauthorized hosts, preventing eavesdropping or theft of network data

- **MAC address lockout**
prevents configured particular MAC addresses from connecting to the network
- **MAC address lockdown**
allows only specified MAC addresses access to the network on a specified port
- **Multiple user authentication methods**
- **IEEE 802.1X**
uses an IEEE 802.1X supplicant on the client in conjunction with a RADIUS server to authenticate in accordance with industry standards
- **Web-based authentication**
provides a browser-based environment, similar to IEEE 802.1X, to authenticate clients that do not support the IEEE 802.1X supplicant
- **MAC-based authentication**
authenticates the client with the RADIUS server based on the client's MAC address
- **Authentication flexibility—2 IEEE 802.1X**
provides authentication of multiple IEEE 802.1X users per port; prevents user "piggybacking" on another user's IEEE 802.1X authentication
- **Protected ports**
prevents designated ports from communicating with each other while allowing access to unprotected ports
- **Per-port broadcast throttling**
selectively configures broadcast control on heavy traffic port uplinks
- **Physical security**
- **Front-panel buttons**
provides the ability to disable reset and clear buttons on front panel for added security
- **Kensington Lock slot**
includes a Kensington Lock slot for securing the switches in open-space deployments
- **Spanning Tree Protocol Root Guard**
when running the spanning tree protocol, protects root bridge from malicious attacks or configuration mistakes
- **STP BPDU port protection**
blocks Bridge Protocol Data Units (BPDUs) on ports that do not require BPDUs, preventing forged BPDU attacks

Convergence

- **IP multicast snooping and data-driven IGMP**
automatically prevent flooding of IP multicast traffic
- **LLDP-MED (Media Endpoint Discovery)**
defines a standard extension of LLDP that stores values for parameters such as QoS and VLAN to automatically configure network devices such as IP phones
- **IEEE 802.1AB Link Layer Discovery Protocol (LLDP)**
facilitates easy mapping using network management applications with LLDP automated device discovery protocol
- **PoE allocations**
supports multiple methods (automatic, IEEE 802.3af class, LLDP-MED, or user-specified) to allocate PoE power for more efficient energy savings

Monitor and diagnostics

- **Port mirroring**
enables traffic on a port to be simultaneously sent to a network analyzer for monitoring
- **Network tools**
command-line interface includes telnet client, ping, traceroute, and Layer 2 link test tools for diagnostics

Overview

- **Logging**
local and remote logging of events via SNMP (v2c and v3) and syslog
- **Troubleshooting**
ingress and egress port monitoring enable network problem solving
- **Uni-Directional Link Detection (UDLD)**
monitors a link between two switches and blocks the ports on both ends of the link if the link goes down at any point between the two devices
- **Find-Fix-Inform**
finds and fixes common network problems automatically, then informs the administrator
- **RMON, XRMON, sFlow, and SMON**
provide advanced monitoring and reporting capabilities for statistics, history, alarms, and events

Flexibility

- **Flexible mounting**
 - **Rackable**
can be mounted in a standard 19-inch rack with included hardware
 - **Wall mountable**
allows the switch to be mounted to a wall using included hardware
 - **Surface mountable**
allows the product to be mounted above or below a surface (such as a desk or table) with included hardware
- **Compact size**
product is designed to reduce space requirements (see product specifications for exact dimensions)
- **Power supply clip**
provides the ability to attach or detach the power supply to the device, allowing for either an integrated solution or a separate one, depending on deployment requirements

Product Architecture

- **Energy-efficient design:**
 - **Fans**
fanless design helps reduce power consumption
 - **Port LEDs**
port link and activity LEDs can be turned off to conserve energy
 - **Port low-power mode option**
when no link is detected on a port, the port will automatically go into low-power mode to conserve energy

Warranty and support

- **Lifetime Warranty 2.0**
advance hardware replacement for as long as you own the product with next-business-day delivery (available in most countries)†
- **Electronic and telephone support (for Lifetime Warranty 2.0)**
limited 24x7 telephone support is available from HP for the first 3 years; limited electronic and business hours telephone support is available from HP for the entire warranty period; to reach our support centers, refer to www.hp.com/networking/contact-support; for details on the duration of support provided with your product purchase, refer to www.hp.com/networking/warrantysummary
- **Software releases**
to find software for your product, refer to www.hp.com/networking/support; for details on the software releases available with your product purchase, refer to www.hp.com/networking/warrantysummary

Overview

†HP warranty includes repair or replacement of hardware for as long as you own the product, with next business day advance replacement (available in most countries). The disk drive included with HP AllianceOne Advanced Services and Services zL Modules, HP Threat Management Services zL Module, HP AllianceOne Extended zL Module with Riverbed Steelhead, HP MSM765zL Mobility Controller and HP Survivable Branch Communication zL Module powered by Microsoft Lync has a five-year hardware warranty. For details, refer to the Software license and hardware warranty statements at: www.hp.com/networking/warranty.

Configuration

Build To Order:

BTO is a standalone unit with no integration. BTO products ship standalone are not part of a CTO or Rack-Shippable solution.

HP E2615-8-PoE Switch

- 8 autosensing 10/100 ports
- 2 dual-personality ports RJ-45 10/100/1000 port ; or an SFP slot
- 1 - J9701A -
- 1U - Height

J9565A

See Configuration
Note:1, 2

Configuration Rules:

Note 1 The following Transceivers install into this switch:

HP X121 1G SFP LC SX Transceiver	J4858C
HP X121 1G SFP LC LX Transceiver	J4859C
HP X111 100M SFP LC FX Transceiver	J9054C
HP X112 100M SFP LC BX-D Transceiver	J9099B
HP X112 100M SFP LC BX-U Transceiver	J9100B
HP X121 1G SFP LC LH Transceiver	J4860C
HP X122 1G SFP LC BX-D Transceiver	J9142B
HP X122 1G SFP LC BX-U Transceiver	J9143A
HP X111 100M SFP LC FX Transceiver	J9054C

Note 2 Localization required. (See Localization Menu for list.)

Internal Power Supplies

No Power supplies

Transceivers

SFP Transceivers

HP X121 1G SFP LC SX Transceiver	J4858C
HP X121 1G SFP LC LX Transceiver	J4859C
HP X111 100M SFP LC FX Transceiver	J9054C
HP X121 1G SFP LC LH Transceiver	J4860C
HP X122 1G SFP LC BX-D Transceiver	J9142B
HP X122 1G SFP LC BX-U Transceiver	J9143B

Configuration

HP X112 100M SFP LC BX-D Transceiver	J9099B
HP X112 100M SFP LC BX-U Transceiver	J9100B

Cables

Multi-Mode Cables

HP .5m Multi-mode OM3 LC/LC FC Cable	AJ833A
HP 1m Multi-mode OM3 LC/LC FC Cable	AJ834A
HP 2 m Multimode OM3 LC/LC FC Cable	AJ835A
HP 5 m Multimode OM3 LC/LC FC Cable	AJ836A
HP 15 m Multimode OM3 LC/LC FC Cable	AJ837A
HP 30 m Multimode OM3 LC/LC FC Cable	AJ838A
HP 50 m Multimode OM3 LC/LC FC Cable	AJ839A

OM4 Cables

HP Premier Flex LC/LC OM4 2f 1m Cbl	QK732A
HP Premier Flex LC/LC OM4 2f 2m Cbl	QK733A
HP Premier Flex LC/LC OM4 2f 5m Cbl	QK734A
HP Premier Flex LC/LC OM4 2f 15m Cbl	QK735A
HP Premier Flex LC/LC OM4 2f 30m Cbl	QK736A
HP Premier Flex LC/LC OM4 2f 50m Cbl	QK737A

Switch Enclosure Options

Rack Mount Kit

HP X410 1U Univ 4-post Rack Mnt Kit	J9583A See Configuration Note:1
HP X410 1U Integ Univ 4-post Rck Mnt Kit	J9583AZ

Configuration

See Configuration
Note:1

Configuration Rules:

Note 1 If this Mounting Kit is order with #0D1 or Z then it integrates to the HP Universal Rack. (not the switch)

External Redundant Power Supplies

HP 600 Redundant and Extrnl Power Supply

- Height = 1U

J8168A
See Configuration
Note:1

Configuration Rules:

Note 1 Localization required.

Option Mounting Kit

HP X510 1U Cable Guard

J9700A

HP X520 1U Power Adapter Shelf

J9701A

Technical Specifications

HP 2615-8-PoE Switch (J9565A)

I/O ports and slots	8 RJ-45 autosensing 10/100 PoE ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3af PoE); Media Type: Auto-MDIX; Duplex: half or full 2 dual-personality ports; each port can be used as either an RJ-45 10/100/1000 port (IEEE 802.3 Type 10Base-T; an IEEE 802.3u Type 100Base-TX; an IEEE 802.3ab 1000Base-T Gigabit Ethernet); or an SFP slot (for use with SFP transceivers) 1 RJ-45 serial console port
Physical characteristics	Dimensions 10(w) x 6.28(d) x 1.75(h) in (25.4 x 15.95 x 4.45 cm) (1U height) Weight 3.66 lb (1.66 kg) including power adapter and power cord
Memory and processor	Processor Freescale PowerPC 8313 @ 333 MHz, 32 MB flash, 128 MB DDR2 SDRAM; packet buffer size: 512 KB dynamically allocated
Mounting and enclosure	Mounts in an EIA-standard 19-inch telco rack or equipment cabinet; horizontal surface mounting; wall mounting
Performance	100 Mb Latency < 5.3 μ s (LIFO 64-byte packets) 1000 Mb Latency < 2.7 μ s (LIFO 64-byte packets) Throughput 4.1 million pps Switching capacity 5.6 Gbps MAC address table size 8000 entries
Environment	Operating temperature 32°F to 113°F (0°C to 45°C) Operating relative humidity 15% to 95% @ 104°F (40°C), noncondensing Nonoperating/Storage temperature -40°F to 158°F (-40°C to 70°C) Nonoperating/Storage temperature 15% to 95% @ 149°F (65°C), noncondensing Altitude up to 10,000 ft (3 km) Acoustic Power: 0 dB, Pressure: 0 dB
Electrical characteristics	Description Use only the external power adapter module (5070-6082, PA1 AC adapter) supplied with this product Maximum heat dissipation 87 BTU/hr (91.79 kJ/hr) AC voltage 100 - 240 VAC Current 1.5 A Maximum power rating 86 W Idle power 11 W PoE power 67 W Frequency 50/60 Hz
Safety	cUL (CSA 22.2 No. 60950); CE Labeled; UL 60950-1; UL Listed; CAN/CSA 22.2 No. 60950; EN 60825; AS/NZS 60950; IEC 60950-1; EN 60950-1
Emissions	FCC part 15 Class A; VCCI Class A; EN 55022 Class A; CISPR 22 Class A; ICES-003 (Canada); AS/NZS CISPR 22; IEC/EN 61000-3-2; IEC/EN 61000-3-3; IEC 61000:4-2, 4-3, 4-4, 4-5, 4-6, 4-8, 4-11

Technical Specifications

Immunity	Generic	EN 55024, CISPR 24
	EN	EN 55024, CISPR 24
	ESD	IEC 61000-4-2
	Radiated	IEC 61000-4-3
	EFT/Burst	IEC 61000-4-4
	Surge	IEC 61000-4-5
	Conducted	IEC 61000-4-6
	Power frequency magnetic field	IEC 61000-4-8
	Voltage dips and interruptions	IEC 61000-4-11
	Harmonics	EN 61000-3-2, IEC 61000-3-2
	Flicker	EN 61000-3-3, IEC 61000-3-3
Management	HP PCM+; HP PCM (included); command-line interface; Web browser; configuration menu; out-of-band management (serial RS-232C); IEEE 802.3 Ethernet MIB; Repeater MIB; Ethernet Interface MIB	
Notes	When using mini-GBICs with this product, mini-GBICs with revision "B" or later (product number ends with the letter "B" or later, e.g., J4858B, J4859C) are required. This product comes with a power supply clip adapter. The adapter dimensions are 1.7(d) x 10.7(w) x 3.8(h) in. (4.35 x 27.25 x 9.6 cm). The weight of the power supply clip adapter is .31 lb (.14 kg).	
Services	3-year, 4-hour onsite, 13x5 coverage for hardware (U4683E) 3-year, 4-hour onsite, 24x7 coverage for hardware (U4835E) 3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 SW phone support and SW updates (U6321E) 3-year, 24x7 SW phone support, software updates (UF792E) 1-year, post-warranty, 4-hour onsite, 13x5 coverage for hardware (HR849E) 1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware (HR850E) 1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (HR851E) Installation with minimum configuration, system-based pricing (U4826E) Installation with HP-provided configuration, system-based pricing (U4830E) 4-year, 4-hour onsite, 13x5 coverage for hardware (UR948E) 4-year, 4-hour onsite, 24x7 coverage for hardware (UR949E) 4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UR950E) 4-year, 24x7 SW phone support, software updates (UR951E) 5-year, 4-hour onsite, 13x5 coverage for hardware (UR952E) 5-year, 4-hour onsite, 24x7 coverage for hardware (UR953E) 5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UR954E) 5-year, 24x7 SW phone support, software updates (UR955E) 3 Yr 6 hr Call-to-Repair Onsite (UW368E) 4 Yr 6 hr Call-to-Repair Onsite (UW369E) 5 Yr 6 hr Call-to-Repair Onsite (UW370E) 1-year, 6 hour Call-To-Repair Onsite for hardware (HR853E) 1-year, 24x7 software phone support, software updates (HR852E) 1-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS554E) 1-year, 24x7 software phone support, software updates + 4 hour hardware exchange (HS555E) 3-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS556E)	

Technical Specifications

- 3-year, 24x7 software phone support, software updates + 4 hour Hardware Exchange (HS557E)
- 4-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS558E)
- 4-year, 24x7 software phone support, software updates + 4 hour Hardware Exchange (HS559E)
- 5-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (HS560E)
- 5-year, 24x7 software phone support, software updates + 4 hour Hardware Exchange (HS561E)

Refer to the HP website at: www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Standards and protocols

Denial of service protection

Automatic Filtering of well known Denial of Service Packets

Device management

RFC 1591 DNS (client)
Multiple Configuration Files
Multiple Software Images
SSHv1/SSHv2 Secure Shell
TACACS/TACACS+
Web UI

General protocols

IEEE 802.1D MAC Bridges
IEEE 802.1p Priority
IEEE 802.1Q VLANs
IEEE 802.1s Multiple Spanning Trees
IEEE 802.1w Rapid Reconfiguration of Spanning Tree
IEEE 802.3 Type 10BASE-T
IEEE 802.3ab 100BASE-T
IEEE 802.3ad Link Aggregation Control Protocol (LACP)
IEEE 802.3af Power over Ethernet
IEEE 802.3u 100BASE-X
IEEE 802.3x Flow Control
RFC 768 UDP
RFC 783 TFTP Protocol (revision 2)
RFC 792 ICMP
RFC 793 TCP
RFC 826 ARP
RFC 854 TELNET
RFC 868 Time Protocol
RFC 951 BOOTP
RFC 1058 RIPv1
RFC 1350 TFTP Protocol (revision 2)
RFC 1723 RIP v2
RFC 1812 IPv4 Routing
RFC 2030 Simple Network Time Protocol (SNTP) v4

RFC 4113 MIB for UDP

RFC 4251 SSHv6 Architecture
RFC 4252 SSHv6 Authentication
RFC 4253 SSHv6 Transport Layer
RFC 4293 MIB for IP
RFC 4419 Key Exchange for SSH
RFC 4443 ICMPv6
RFC 4861 IPv6 Neighbor Discovery
RFC 4862 IPv6 Stateless Address Auto-configuration

MIBs

RFC 1213 MIB II
RFC 1493 Bridge MIB
RFC 2021 RMONv2 MIB
RFC 2613 SMON MIB
RFC 2618 RADIUS Client MIB
RFC 2620 RADIUS Accounting MIB
RFC 2665 Ethernet-Like-MIB
RFC 2668 802.3 MAU MIB
RFC 2674 802.1p and IEEE 802.1Q Bridge MIB
RFC 2737 Entity MIB (Version 2)
RFC 2863 The Interfaces Group MIB

Network management

IEEE 802.1AB Link Layer Discovery Protocol (LLDP)
RFC 1098 A Simple Network Management Protocol (SNMP)
RFC 2819 Four groups of RMON: 1 (statistics), 2 (history), 3 (alarm) and 9 (events)
RFC 3176 sFlow
SNMPv1/v2c/v3

QoS/CoS

RFC 2474 DiffServ precedence, with 4 queues per port
RFC 2475 DiffServ Architecture
RFC 2597 DiffServ Assured Forwarding (AF)
RFC 2598 DiffServ Expedited Forwarding (EF)
Ingress Rate Limiting

Technical Specifications

RFC 2131 DHCP
RFC 2453 RIPv2
UDLD (Uni-directional Link Detection)

IP multicast

RFC 3376 IGMPv3 (host joins only)

IPv6

RFC 1981 IPv6 Path MTU Discovery
RFC 2460 IPv6 Specification
RFC 2925 Remote Operations MIB (Ping only)
RFC 3315 DHCPv6 (client only)
RFC 3513 IPv6 Addressing Architecture
RFC 3596 DNS Extension for IPv6
RFC 4022 MIB for TCP

Security

IEEE 802.1X Port Based Network Access Control
RFC 1492 TACACS+
RFC 2138 RADIUS Authentication
RFC 2866 RADIUS Accounting
Access Control Lists (ACLs)
MAC Authentication
MAC Lockdown
MAC Lockout
Port Security
Secure Sockets Layer (SSL)
Web Authentication

Accessories

HP E2615-8-PoE Switch accessories

HP 2615-8-PoE Switch (J9565A)

HP X121 1G SFP LC SX Transceiver	J4858C
HP X121 1G SFP LC LX Transceiver	J4859C
HP X121 1G SFP LC LH Transceiver	J4860C
HP X111 100M SFP LC FX Transceiver	J9054C
HP X112 100M SFP LC BX-D Transceiver	J9099B
HP X112 100M SFP LC BX-U Transceiver	J9100B
HP X122 1G SFP LC BX-D Transceiver	J9142B
HP X122 1G SFP LC BX-U Transceiver	J9143B
HP 0.5 m Multimode OM3 LC/LC Optical Cable	AJ833A
HP Premier Flex LC/LC Multi-mode OM4 2 fiber 1m Cable	QK732A
HP Premier Flex LC/LC Multi-mode OM4 2 fiber 2m Cable	QK733A
HP Premier Flex LC/LC Multi-mode OM4 2 fiber 5m Cable	QK734A
HP Premier Flex LC/LC Multi-mode OM4 2 fiber 15m Cable	QK735A
HP Premier Flex LC/LC Multi-mode OM4 2 fiber 30m Cable	QK736A
HP Premier Flex LC/LC Multi-mode OM4 2 fiber 50m Cable	QK737A
HP X510 1U Cable Guard	J9700A

Accessory Product Details

NOTE: Details are not available for all accessories. The following specifications were available at the time of publication.

<p>HP X121 1G SFP LC SX Transceiver (J4858C)</p> <p>A small form-factor pluggable (SFP) Gigabit SX transceiver that provides a full-duplex Gigabit solution up to 550 m on multimode fiber.</p>	<p>Ports</p> <p>Physical characteristics</p> <p>Environment</p> <p>Electrical characteristics</p> <p>Cabling</p>	<p>1 LC 1000BASE-SX port; Duplex: full only</p> <p>Dimensions: 2.24(d) x 0.54(w) x 0.48(h) in. (5.69 x 1.37 x 1.22 cm)</p> <p>Weight: 0.04 lb. (0.02 kg)</p> <p>Transceiver form factor: SFP</p> <p>Operating temperature: 32°F to 158°F (0°C to 70°C)</p> <p>Operating relative humidity: 5% to 85%, noncondensing</p> <p>Nonoperating/Storage temperature: -40°F to 203°F (-40°C to 85°C)</p> <p>Altitude: up to 10,000 ft. (3 km)</p> <p>Power consumption typical: 0.4 W</p> <p>Power consumption maximum: 0.7 W</p> <p>Type:</p> <ul style="list-style-type: none"> ● 62.5/125 µm or 50/125 µm (core/cladding) diameter, graded-index, low metal content, multimode fiber optic, complying with ITU-T G.651 and ISO/IEC 793-2 Type A1b or A1a, respectively; <p>Maximum distance:</p> <ul style="list-style-type: none"> ● 2-220 m (62.5 µm core diameter, 160 MHz*km bandwidth) ● 2-275 m (62.5 µm core diameter, 200 MHz*km bandwidth) ● 2-500 m (50 µm core diameter, 400 MHz*km bandwidth) ● 2-550 m (50 µm core diameter, 500 MHz*km bandwidth) <p>Cable length: 2-550m</p> <p>Fiber type: Multi Mode</p>
<p>HP X121 1G SFP LC LX Transceiver (J4859C)</p> <p>HP X121 1G SFP LC LX Transceiver: An SFP format gigabit transceiver with LC connectors using LX technology.</p>	<p>Ports</p> <p>Physical characteristics</p> <p>Environment</p> <p>Cabling</p>	<p>1 LC 1000BASE-LX port (IEEE 802.3z Type 1000BASE-LX); Duplex: full only</p> <p>Dimensions: 2.24(d) x 0.54(w) x 0.486(h) in. (5.69 x 1.37 x 1.23 cm)</p> <p>Weight: 0.04 lb. (0.02 kg)</p> <p>Operating temperature: 32°F to 158°F (0°C to 70°C)</p> <p>Operating relative humidity: 0% to 85%, noncondensing</p> <p>Nonoperating/Storage temperature: -40°F to 212°F (-40°C to 100°C)</p> <p>Altitude: up to 10,000 ft. (3 km)</p> <p>Type:</p> <ul style="list-style-type: none"> ● Either single mode or multimode; 62.5/125 µm or 50/125 µm (core/cladding) diameter, graded-index, low metal content, multimode fiber optic, complying with ITU-T G.651 and ISO/IEC 793-2 Type A1b or A1a, respectively; Low metal content, single-mode fiber-optic, complying with ITU-T G.652 and ISO/IEC 793-2 Type B1; <p>Maximum distance:</p>
	<p>Services</p>	<p>Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.</p>

Accessory Product Details

- 2-550 m (multimode 62.5 µm core diameter, 500 MHz*km bandwidth)
- 2-550 m (multimode 50 µm core diameter, 400 MHz*km bandwidth)
- 2-550 m (multimode 50 µm core diameter, 500 MHz*km bandwidth)
- 2-10,000 m (single-mode fiber)

Notes

A mode conditioning patch cord may be needed in some multimode fiber installations.

Wavelength: 1310nm

Power Consumption: < 500mW Typical

Services

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

HP X121 1G SFP LC LH Transceiver (J4860C)

A small form-factor pluggable (SFP) Gigabit LH transceiver that provides a full-duplex Gigabit solution up to 70 km on single-mode fiber.

Ports

1 LC 1000BASE-LH port (no IEEE standard exists for 1550 nm optics); Duplex: full only

Physical characteristics

Dimensions: 2.17(d) x 0.60(w) x 0.46(h) in. (5.5 x 1.53 x 1.18 cm)

Weight: 0.04 lb. (0.02 kg)

Environment

Operating temperature: -40°F to 185°F (-40°C to 85°C)

Operating relative humidity: 0% to 95% @ 77°F (25°C), noncondensing

Nonoperating/Storage temperature: -40°F to 185°F (-40°C to 85°C)

Altitude: up to 10,000 ft. (3 km)

Cabling

Cable type:

- Low metal content, single-mode fiber-optic, complying with ITU-T G.652 and ISO/IEC 793-2 Type B1;

Maximum distance:

- 10-70,000 m (single-mode fiber)

Notes

Power consumption is 0.8 watts typical with 1 watt maximum at 100% utilization.

For distances less than 20 km, a 10 dB attenuator must be used.

For distances between 20 km and 40 km, a 5 dB attenuator must be used.

Attenuators can be purchased from most cable vendors.

Services

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Accessory Product Details

<p>HP X111 100M SFP LC FX Transceiver (J9054C)</p> <p>HP X111 100M SFP LC FX Transceiver: An SFP format 100-megabit transceiver with LC connectors using FX technology.</p>	<p>Ports</p> <p>Physical characteristics</p> <p>Environment</p> <p>Cabling</p> <p>Notes</p> <p>Services</p>	<p>1 LC 100BASE-FX port (IEEE 802.3u Type 100BASE-FX); Duplex: half or full</p> <p>Dimensions: 2.7(d) x 0.54(w) x 0.48(h) in. (6.86 x 1.38 x 1.22 cm)</p> <p>Weight: 0.06 lb. (0.03 kg)</p> <p>Operating temperature: 32°F to 158°F (0°C to 70°C)</p> <p>Operating relative humidity: 5% to 95%</p> <p>Nonoperating/Storage temperature: -40°F to 185°F (-40°C to 85°C)</p> <p>Nonoperating/Storage relative humidity: 5% to 85%</p> <p>Altitude: up to 10,000 ft. (3 km)</p> <p>Cable type: 62.5/125 im or 50/125 im (core/cladding) diameter, graded-index, low metal content, multimode fiber optic, complying with ITU-T G.651 and ISO/IEC 793-2 Type A1b or A1a, respectively; Maximum distance: • 2 km (full duplex) or 412 m (half duplex)</p> <p>Transmitter wavelength: 1310nm</p> <p>Power consumption is 1.1 watt maximum.</p> <p>For supported platforms and minimum software requirements to support this product, see the document titled "Support for the J9054B 100-FX SFP-LC Transceiver" on the "ProCurve Mini-GBICs and SFPs" Manuals Web page.</p> <p>Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.</p>
--	---	---

<p>HP X112 100M SFP LC BX-D Ports Transceiver (J9099B)</p> <p>A small form-factor pluggable (SFP) 100-Megabit BX (bi-directional) "downstream" transceiver that provides 100 Mbps full-duplex connectivity up to 10 km on one strand of singlemode fiber. The J9099B connects to the J9100B "upstream" transceiver, or to any IEEE-standard 100BASE-BX10-U ("upstream") device.</p>	<p>Physical characteristics</p> <p>Environment</p> <p>Cabling</p> <p>Notes</p>	<p>1 LC 100BASE-BX10 port (IEEE 802.3ah Type 100BASE-BX10-D); Duplex: full only</p> <p>Dimensions 2.7(d) x 0.55(w) x 0.48(h) in. (6.86 x 1.39 x 1.22 cm)</p> <p>Weight 0.04 lb. (0.03 kg)</p> <p>Operating temperature 32°F to 158°F (0°C to 70°C)</p> <p>Operating relative humidity 0% to 95%, noncondensing</p> <p>Nonoperating/Storage temperature -40°F to 185°F (-40°C to 85°C)</p> <p>Type: Single-mode fiber optic, complying with ITU-T G.652;</p> <p>Maximum distance:</p> <ul style="list-style-type: none"> • 0.5-10,000 m (single-mode fiber) <p>Transmit wavelength: 1550 nm. Receive wavelength: 1310 nm.</p> <p>Power consumption is 1.1 watt maximum.</p> <p>For supported platforms and minimum software requirements to support this product, see the document titled "Support for the HP BX Transceivers" on the "HP Mini-GBICs and SFPs" Manuals Web page.</p> <p>The J9099B connects to the J9100B "upstream" transceiver, or to any IEEE-standard 100BASE-BX10-U ("upstream") device. (A 100-BX-D transceiver can</p>
--	--	--

Accessory Product Details

Services

only connect to a 100-BX-U product. You cannot connect two 100-BX-D transceivers together.)

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

HP X112 100M SFP LC BX-U Ports Transceiver (J9100B)

A small form-factor pluggable (SFP) 100-Megabit BX (bi-directional) "upstream" transceiver that provides 100 Mbps full-duplex connectivity up to 10 km on one strand of singlemode fiber. The J9100B connects to the J9099B "downstream" transceiver, or to any IEEE-standard 100BASE-BX10-D ("downstream") device.

Physical characteristics

1 LC 100BASE-BX10 port (IEEE 802.3ah Type 100BASE-BX10-U); Duplex: full only

Dimensions

2.7(d) x 0.55(w) x 0.48(h) in. (6.86 x 1.39 x 1.22 cm)

Weight

0.07 lb. (.03 kg)

Environment

Operating temperature

32°F to 158°F (0°C to 70°C)

Operating relative humidity

0% to 95%, noncondensing

Nonoperating/Storage temperature

-40°F to 185°F (-40°C to 85°C)

Cabling

Type:

Single-mode fiber optic, complying with ITU-T G.652;

Maximum distance:

- 0.5-10,000 m (single-mode fiber)

Notes

For supported platforms and minimum software requirements to support this product, see the document titled "Support for the HP BX Transceivers" on the "HP Mini-GBICs and SFPs" Manuals Web page.

The J9100B connects to the J9099B "downstream" transceiver, or to any IEEE-standard 100BASE-BX10-D ("downstream") device. (A 100-BX-U transceiver can only connect to a 100-BX-D product. You cannot connect two 100-BX-U transceivers together.)

Transmit wavelength: 1310 nm. Receive wavelength: 1550 nm.

Power consumption is 1.1 watts maximum.

Services

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Accessory Product Details

<p>HP X122 1G SFP LC BX-D Transceiver (J9142B)</p> <p>A small form-factor pluggable (SFP) Gigabit-BX (bi-directional) "downstream" transceiver that provides a full-duplex Gigabit solution up to 10 km on one strand of single-mode fiber. The J9142B connects to the J9143B "upstream" transceiver, or to any IEEE-standard 1000BASE-BX10-U ("upstream") device.</p>	<p>Ports</p> <p>1 LC 1000BASE-BX10 port (IEEE 802.3ah Type 1000BASE-BX10-D); Duplex: full only</p>	<p>Physical characteristics</p> <p>Dimensions 2.19(d) x 0.54(w) x 0.46(h) in. (5.57 x 1.37 x 1.18 cm)</p> <p>Weight 0.04 lb. (0.02 kg)</p>
<p>Environment</p>	<p>Operating temperature 32°F to 158°F (0°C to 70°C)</p> <p>Operating relative humidity 0% to 95%, non-condensing</p> <p>Non-operating/Storage temperature -40°F to 185°F -40°C to 85°C</p>	<p>Cabling</p> <p>Type: Single-mode fiber optic, complying with ITU-T G.652;</p> <p>Maximum distance:</p> <ul style="list-style-type: none"> ● 0.5-10,000 m (single-mode fiber)
<p>Notes</p>	<p>Transmit wavelength: 1490 nm. Receive wavelength: 1310 nm. Power consumption is 1 watt maximum. For supported platforms and minimum software requirements to support this product, see the document titled "Support for the HP BX Transceivers" on the "HP Mini-GBICs and SFPs" Manuals Web page. The J9142B connects to the J9143B "upstream" transceiver, or to any IEEE-standard 1000BASE-BX10-U ("upstream") device. (A 1000-BX-D transceiver can only connect to a 1000-BX-U product. You cannot connect two 1000-BX-D transceivers together.)</p>	
<p>Services</p>	<p>Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.</p>	

<p>HP X122 1G SFP LC BX-U Transceiver (J9143B)</p> <p>A small form-factor pluggable (SFP) Gigabit-BX (bi-directional) "upstream" transceiver that provides a full-duplex Gigabit solution up to 10 km on one strand of single-mode fiber. The J9143B connects to the J9142B "downstream" transceiver, or to any IEEE-standard 1000BASE-BX10-D ("downstream") device.</p>	<p>Ports</p> <p>1 LC 1000BASE-BX10 port (IEEE 802.3ah Type 1000BASE-BX10-U); Duplex: full only</p>	<p>Physical characteristics</p> <p>Dimensions 2.19(d) x 0.54(w) x 0.46(h) in. (5.57 x 1.37 x 1.18 cm)</p> <p>Weight 0.04 lb. (0.02 kg)</p>
<p>Environment</p>	<p>Operating temperature 32°F to 158°F (0°C to 70°C)</p> <p>Operating relative humidity 0% to 95%, non-condensing</p> <p>Non-operating/Storage temperature -40°F to 185°F -40°C to 85°C</p>	<p>Cabling</p> <p>Type: Single-mode fiber optic, complying with ITU-T G.652;</p> <p>Maximum distance:</p> <ul style="list-style-type: none"> ● 0.5-10,000 m (single-mode fiber)
<p>Notes</p>	<p>Transmit wavelength: 1310 nm. Receive wavelength: 1490 nm.</p>	

Accessory Product Details

For supported platforms and minimum software requirements to support this product, see the document titled "Support for the HP BX Transceivers" on the "HP Mini-GBICs and SFPs" Manuals Web page.

The J9143B connects to the J9142B "downstream" transceiver, or to any IEEE-standard 1000BASE-BX10-D ("downstream") device. (A 1000-BX-U transceiver can only connect to a 1000-BX-D product. You cannot connect two 1000-BX-U transceivers together.)

Power consumption is 1 watt maximum.

Services

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

HP 0.5 m Multimode OM3 LC/LC Optical Cable (AJ833A)

Cable type:

50/125 µm (core/cladding) diameter, multimode fiber optic, with effective modal bandwidth of 2000 MHz/km as detailed in TIA-492AAAC for distances of up to 300 m

Maximum distance:

10Gbps Transfer Rate (Ethernet): 300m

Notes

Cable Specs: Tight buffered duplex fiber optic multimode OM3 50/125 µm fiber optic cable and Ethernet assembly with LC duplex connectors on one end and LC duplex connectors on other end.

- Dimensions: Core diameter: $50 \pm 3.0\mu\text{m}$ Cladding diameter: $125 \pm 2.0\mu\text{m}$ Coating diameter: $245 \pm 10\mu\text{m}$
- Optical glass: Bandwidth: For LED sources: 1500/500 MHz-km @850/1300nm.
- Optical glass: Bandwidth: For Laser sources: 2000/500 MHz-km @850/1300nm. VCSEL Laser sources: 600 / 600 meters @850/1300nm for Gigabit Ethernet compliant links.
- CABLE: The cable is duplex zipcord graded index 50/125µm multimode optical fiber and designed to work in both the 850 and 1300 nm wavelength windows.
- BULK CABLE & CABLE ASSEMBLY CONFIGURATION:
- Jacket Material: Riser Grade - Low Smoke Zero Halogen thermoplastic.
- Jacket Color: Aqua for OM3 multimode per TIA 598
- Boot Color: White
- Insertion Loss: less than 0.5 dB @ 850 with LED source, 0.003 dB/M added for lengths > 30 meters.
- Maximum Cable attenuation: 3.0 dB/km @ 850 nm, 1.0 dB/Km @ 1310 nm @ 23°C as tested in accordance with EIA 455-46.
- Weight: Air Packed Weight: 1 LB Net Weight: 0.454Kg

Services

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Accessory Product Details

**HP Premier Flex LC/LC
Multi-mode OM4 2 fiber
1m Cable (QK732A)**

Notes

Cable Specs: Graded-index, "bendable" fiber optic multimode OM3+ 50/125um duplex cable and Ethernet assembly with LC duplex connectors on each end.

- Core Diameter: 50um \pm 3um, Cladding diameter: 125um \pm 2um; Coating diameter: 245 \pm 10um
- Bandwidth: 3000 MHz-km @ 850nm (Laser)
- Jacket Color: Blue
- Jacket Material: Riser Grade – Low Smoke Zero Halogen (LSZH) thermoplastic
- Boot Color: White
- Outer Jacket Print: HP PremierFlex OM3+ Fiber Optic Cable, 50/125um, Type OFNR (UL), LSZH, cUL, OFN FT4, ROHS. Cable also has a longitudinal white stripe that runs the entire length of the cable.
- Insertion Loss: Less than 0.5dB @ 850nm with LED source, 0.003dB/m added for lengths >30m
- Maximum Cable Attenuation: 3.0 dB/km @ 850nm, 1.0 dB/km @ 1310nm @ 23°C as tested in accordance with EIA 455-45

Services

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

**HP Premier Flex LC/LC
Multi-mode OM4 2 fiber
2m Cable (QK733A)**

Notes

Cable Specs: Graded-index, "bendable" fiber optic multimode OM3+ 50/125um duplex cable and Ethernet assembly with LC duplex connectors on each end.

- Core diameter: 50um \pm 3um, Cladding diameter: 125um \pm 2um; Coating diameter: 245 \pm 10um
- Bandwidth: 3000 MHz-km @ 850nm (Laser)
- Jacket Color: Blue
- Jacket Material: Riser Grade – Low Smoke Zero Halogen (LSZH) thermoplastic
- Boot Color: White
- Outer Jacket Print: HP PremierFlex OM3+ Fiber Optic Cable, 50/125um, Type OFNR (UL), LSZH, cUL, OFN FT4, ROHS. Cable also has a longitudinal white stripe that runs the entire length of the cable.
- Insertion Loss: Less than 0.5dB @ 850nm with LED source, 0.003dB/m added for lengths >30m
- Maximum Cable Attenuation: 3.0 dB/km @ 850nm, 1.0 dB/km @ 1310nm @ 23°C as tested in accordance with EIA 455-45

Services

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Accessory Product Details

**HP Premier Flex LC/LC
Multi-mode OM4 2 fiber
5m Cable (QK734A)**

Notes

Cable Specs: Graded-index, "bendable" fiber optic multimode OM3+ 50/125um duplex cable and Ethernet assembly with LC duplex connectors on each end.

- Core diameter: 50um \pm 3um, Cladding diameter: 125um \pm 2um; Coating diameter: 245 \pm 10um
- Bandwidth: 3000 MHz-km @ 850nm (Laser)
- Jacket Color: Blue
- Jacket Material: Riser Grade – Low Smoke Zero Halogen (LSZH) thermoplastic
- Boot Color: White
- Outer Jacket Print: HP PremierFlex OM3+ Fiber Optic Cable, 50/125um, Type OFNR (UL), LSZH, cUL, OFN FT4, ROHS. Cable also has a longitudinal white stripe that runs the entire length of the cable.
- Insertion Loss: Less than 0.5dB @ 850nm with LED source, 0.003dB/m added for lengths >30m
- Maximum Cable Attenuation: 3.0 dB/km @ 850nm, 1.0 dB/km @ 1310nm @ 23°C as tested in accordance with EIA 455-45

Services

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

**HP Premier Flex LC/LC
Multi-mode OM4 2 fiber
15m Cable (QK735A)**

Notes

Cable Specs: Graded-index, "bendable" fiber optic multimode OM3+ 50/125um duplex cable and Ethernet assembly with LC duplex connectors on each end.

- Core diameter: 50um \pm 3um, Cladding diameter: 125um \pm 2um; Coating diameter: 245 \pm 10um
- Bandwidth: 3000 MHz-km @ 850nm (Laser)
- Jacket Color: Blue
- Jacket Material: Riser Grade – Low Smoke Zero Halogen (LSZH) thermoplastic
- Boot Color: White
- Outer Jacket Print: HP PremierFlex OM3+ Fiber Optic Cable, 50/125um, Type OFNR (UL), LSZH, cUL, OFN FT4, ROHS. Cable also has a longitudinal white stripe that runs the entire length of the cable.
- Insertion Loss: Less than 0.5dB @ 850nm with LED source, 0.003dB/m added for lengths >30m
- Maximum Cable Attenuation: 3.0 dB/km @ 850nm, 1.0 dB/km @ 1310nm @ 23°C as tested in accordance with EIA 455-45

Services

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Accessory Product Details

**HP Premier Flex LC/LC
Multi-mode OM4 2 fiber
30m Cable (QK736A)**

Notes

Cable Specs: Graded-index, "bendable" fiber optic multimode OM3+ 50/125um duplex cable and Ethernet assembly with LC duplex connectors on each end.

- Core diameter: 50um ±3um, Cladding diameter: 125um ±2um; Coating diameter: 245 ± 10um
- Bandwidth: 3000 MHz-km @ 850nm (Laser)
- Jacket Color: Blue
- Jacket Material: Riser Grade – Low Smoke Zero Halogen (LSZH) thermoplastic
- Boot Color: White
- Outer Jacket Print: HP PremierFlex OM3+ Fiber Optic Cable, 50/125um, Type OFNR (UL), LSZH, cUL, OFN FT4, ROHS. Cable also has a longitudinal white stripe that runs the entire length of the cable.
- Insertion Loss: Less than 0.5dB @ 850nm with LED source, 0.003dB/m added for lengths >30m
- Maximum Cable Attenuation: 3.0 dB/km @ 850nm, 1.0 dB/km @ 1310nm @ 23°C as tested in accordance with EIA 455-45

Services

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

**HP Premier Flex LC/LC
Multi-mode OM4 2 fiber
50m Cable (QK737A)**

Notes

Cable Specs: Graded-index, "bendable" fiber optic multimode OM3+ 50/125um duplex cable and Ethernet assembly with LC duplex connectors on each end.

- Core diameter: 50um ±3um, Cladding diameter: 125um ±2um; Coating diameter: 245 ± 10um
- Bandwidth: 3000 MHz-km @ 850nm (Laser)
- Jacket Color: Blue
- Jacket Material: Riser Grade – Low Smoke Zero Halogen (LSZH) thermoplastic
- Boot Color: White
- Outer Jacket Print: HP PremierFlex OM3+ Fiber Optic Cable, 50/125um, Type OFNR (UL), LSZH, cUL, OFN FT4, ROHS. Cable also has a longitudinal white stripe that runs the entire length of the cable.
- Insertion Loss: Less than 0.5dB @ 850nm with LED source, 0.003dB/m added for lengths >30m
- Maximum Cable Attenuation: 3.0 dB/km @ 850nm, 1.0 dB/km @ 1310nm @ 23°C as tested in accordance with EIA 455-45

Services

Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

**HP X510 1U Cable Guard
(J9700A)**

Notes

Dimensions: 10.94" x 3.62" x 1.69" or 27.8cm x 9.2cm x 4.3cm w/ears
10.94" x 1.69" x 1.69" or 27.8cm x 4.3cm x 4.3cm without ears
Weight: 1.262 lbs or .57 kg (including faceplate, ears, and screws) 1.026 lbs or .47 kg (faceplate only)

Services

Refer to the HP website at: www.hp.com/networking/services for details

Accessory Product Details

To learn more, visit: www.hp.com/networking

© Copyright 2010-2013 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.